



A MITEL
PRODUCT
GUIDE

Unify OpenScape Contact Center V12

REST SDK Framework

Programming Guide

02/2026

Notices

The information contained in this document is believed to be accurate in all respects but is not warranted by Mitel Europe Limited. The information is subject to change without notice and should not be construed in any way as a commitment by Mitel or any of its affiliates or subsidiaries. Mitel and its affiliates and subsidiaries assume no responsibility for any errors or omissions in this document. Revisions of this document or new editions of it may be issued to incorporate such changes. No part of this document can be reproduced or transmitted in any form or by any means - electronic or mechanical - for any purpose without written permission from Mitel Networks Corporation.

Trademarks

The trademarks, service marks, logos, and graphics (collectively "Trademarks") appearing on Mitel's Internet sites or in its publications are registered and unregistered trademarks of Mitel Networks Corporation (MNC) or its subsidiaries (collectively "Mitel"), Unify Software and Solutions GmbH & Co. KG or its affiliates (collectively "Unify") or others. Use of the Trademarks is prohibited without the express consent from Mitel and/or Unify. Please contact our legal department at iplegal@mitel.com for additional information. For a list of the worldwide Mitel and Unify registered trademarks, please refer to the website: <http://www.mitel.com/trademarks>.

© Copyright 2026, Mitel Networks Corporation

All rights reserved

Contents

| | |
|--|-----------|
| 1. About the REST SDK Framework | 9 |
| 1.1. REST SDK Framework solution overview | 9 |
| 2. REST SDK Framework prerequisites | 10 |
| 3. REST SDK Principles | 11 |
| 3.1. Functional Description | 11 |
| 3.2. Configuration | 11 |
| 3.3. Simple REST SDK flow examples | 12 |
| 3.4. HTTP Messages..... | 14 |
| 4. REST SDK Messages | 16 |
| 4.1. Main..... | 16 |
| 4.1.1. Main Commands..... | 16 |
| 4.1.1.1. RegisterApplication | 16 |
| 4.1.1.2. UnregisterApplication | 17 |
| 4.1.1.3. Logon | 17 |
| 4.1.1.4. KeepAlive | 18 |
| 4.1.1.5. GetServerState..... | 18 |
| 4.1.2. Main Commands (old versions) | 19 |
| 4.1.2.1. UnregisterApplication (v1) | 19 |
| 4.2. Admin | 20 |
| 4.2.1. Admin Commands | 20 |
| 4.2.1.1. GetUsers | 20 |
| 4.2.1.2. GetQueues | 22 |
| 4.2.1.3. GetQueues V2..... | 22 |
| 4.2.1.4. GetHotStandbyState | 24 |
| 4.2.1.5. SetHotStandbyState | 24 |
| 4.2.1.6. GetGroups..... | 25 |
| 4.2.1.7. GetDepartments | 26 |
| 4.2.1.8. GetAggregates | 26 |
| 4.2.1.9. GetUnavailableReasons..... | 27 |
| 4.2.1.10. GetWrapUpReasons | 28 |
| 4.2.1.11. GetWorkReasons | 29 |
| 4.2.1.12. GetPostProcessingReasons..... | 30 |
| 4.2.1.13. GetCallbackRetryReasons | 30 |
| 4.2.1.14. GetCallbackDeleteReasons | 31 |
| 4.2.1.15. GetOpenMediaConnectors..... | 31 |
| 4.2.1.16. GetOpenMediaDiscardReasons..... | 32 |
| 4.2.1.17. StartListenForEvents | 33 |
| 4.2.1.18. StopListenForEvents | 33 |
| 4.2.2. Admin Events..... | 34 |
| 4.2.2.1. OnUserUpdateEvent | 34 |
| 4.2.2.2. OnQueueUpdateEvent | 35 |
| 4.2.2.3. OnGroupUpdateEvent..... | 36 |
| 4.2.2.4. OnDepartmentUpdateEvent | 37 |
| 4.2.2.5. OnAggregateUpdateEvent | 38 |

| | |
|---|----|
| 4.2.2.6. OnPostProcessingReasonUpdateEvent | 39 |
| 4.2.2.7. OnUnavailableReasonUpdateEvent | 40 |
| 4.2.2.8. OnWrapUpReasonUpdateEvent | 40 |
| 4.2.2.9. OnCallbackReasonUpdateEvent | 41 |
| 4.2.2.10. OnOpenMediaDiscardReasonUpdateEvent | 43 |
| 4.2.2.11. OnDeleteEvent | 43 |
| 4.2.2.12. OnServerConnectedEvent | 44 |
| 4.2.2.13. OnServerDisconnectedEvent | 45 |
| 4.2.3. Admin Events (old versions) | 45 |
| 4.2.3.1. OnUserUpdateEvent (v1) | 46 |
| 4.2.3.2. OnQueueUpdateEvent (v1) | 47 |
| 4.2.3.3. OnGroupUpdateEvent (v1) | 47 |
| 4.2.3.4. OnDepartmentUpdateEvent (v1) | 48 |
| 4.2.3.5. OnAggregateUpdateEvent (v1) | 49 |
| 4.2.3.6. OnPostProcessingReasonUpdateEvent (v1) | 50 |
| 4.2.3.7. OnUnavailableReasonUpdateEvent (v1) | 50 |
| 4.2.3.8. OnWrapUpReasonUpdateEvent (v1) | 51 |
| 4.2.3.9. OnCallbackReasonUpdateEvent (V1) | 52 |
| 4.2.3.10. OnDeleteEvent (v1) | 53 |
| 4.3. Presence | 53 |
| 4.3.1. Presence Commands | 53 |
| 4.3.1.1. SetRoutingState | 53 |
| 4.3.1.2. GetRoutingState | 54 |
| 4.3.1.3. RequestPostProcessing | 55 |
| 4.3.1.4. ExitPostProcessing | 55 |
| 4.3.1.5. SetPrimary | 56 |
| 4.3.1.6. CancelMandatoryWrappingUp | 56 |
| 4.3.1.7. SetWrapUpReason | 57 |
| 4.3.1.8. StartListenForEvents | 58 |
| 4.3.1.9. StopListenForEvents | 58 |
| 4.3.2. Presence Events | 58 |
| 4.3.2.1. OnUserMediaEvent | 59 |
| 4.3.2.2. OnRoutingStateEvent | 60 |
| 4.3.2.3. OnUserHandlingStateEvent | 61 |
| 4.3.2.4. OnUserMediaReadyEvent | 62 |
| 4.3.2.5. OnUserMediaNotReadyEvent | 63 |
| 4.3.2.6. OnServerConnected | 63 |
| 4.3.2.7. OnServerDisconnected | 64 |
| 4.4. Routing | 64 |
| 4.4.1. Routing Commands | 64 |
| 4.4.1.1. QueryCall | 65 |
| 4.4.1.2. UpdateCall | 66 |
| 4.4.1.3. GetQueueData | 66 |
| 4.4.1.4. EnqueueCall | 67 |
| 4.4.1.5. DequeueCall | 68 |
| 4.4.1.6. AddContactData | 69 |
| 4.4.1.7. RemoveContactData | 69 |
| 4.4.1.8. ClearContactData | 70 |
| 4.4.1.9. StartListenForEvents | 70 |
| 4.4.1.10. StopListenForEvents | 70 |
| 4.4.2. Routing Events | 71 |
| 4.4.2.1. OnAssignCallEvent | 71 |
| 4.4.2.2. OnUnassignCallEvent | 72 |
| 4.4.2.3. OnEnqueueCallEvent | 72 |

| | |
|---|-----|
| 4.4.2.4. OnDequeueCallEvent..... | 73 |
| 4.4.2.5. OnRoutingUpdateInformationEvent..... | 74 |
| 4.4.2.6. OnTimeoutCallEvent..... | 75 |
| 4.4.2.7. OnServerConnected..... | 76 |
| 4.4.2.8. OnServerDisconnected..... | 77 |
| 4.5. Telephony..... | 77 |
| 4.5.1. Telephony Commands..... | 77 |
| 4.5.1.1. Logon..... | 77 |
| 4.5.1.2. Logoff..... | 78 |
| 4.5.1.3. Dial..... | 78 |
| 4.5.1.4. Answer..... | 78 |
| 4.5.1.5. Disconnect..... | 79 |
| 4.5.1.6. Consult..... | 79 |
| 4.5.1.7. Hold..... | 80 |
| 4.5.1.8. Retrieve..... | 80 |
| 4.5.1.9. Reconnect..... | 80 |
| 4.5.1.10. Conference..... | 81 |
| 4.5.1.11. Transfer..... | 81 |
| 4.5.1.12. SingleStepTransfer..... | 81 |
| 4.5.1.13. TransferToVoiceMail..... | 82 |
| 4.5.1.14. Divert..... | 82 |
| 4.5.1.15. SetUserPreferredDevice..... | 83 |
| 4.5.1.16. RemoveUserPreferredDevice..... | 83 |
| 4.5.1.17. UpdateContactData..... | 83 |
| 4.5.1.18. QueryLine..... | 84 |
| 4.5.1.19. QueryCall..... | 85 |
| 4.5.1.20. StartListenForEvents..... | 87 |
| 4.5.1.21. StopListenForEvents..... | 87 |
| 4.5.2. Telephony Events..... | 89 |
| 4.5.2.1. OnDeliveredEvent..... | 89 |
| 4.5.2.2. OnDisconnectedEvent..... | 90 |
| 4.5.2.3. OnQueuedEvent..... | 92 |
| 4.5.2.4. OnEstablishedEvent..... | 93 |
| 4.5.2.5. OnDivertedEvent..... | 95 |
| 4.5.2.6. OnHeldEvent..... | 96 |
| 4.5.2.7. OnRetrievedEvent..... | 97 |
| 4.5.2.8. OnConferencedEvent..... | 99 |
| 4.5.2.9. OnFailedEvent..... | 100 |
| 4.5.2.10. OnOriginatedEvent..... | 102 |
| 4.5.2.11. OnServiceInitiatedEvent..... | 103 |
| 4.5.2.12. OnTransferredEvent..... | 104 |
| 4.5.2.13. OnNetworkReachedEvent..... | 106 |
| 4.5.2.14. OnServicesEnabled..... | 107 |
| 4.5.2.15. OnServerConnectedEvent..... | 108 |
| 4.5.2.16. OnServerDisconnectedEvent..... | 109 |
| 4.5.2.17. HotStandby_Event..... | 110 |
| 4.5.3. Telephony Common Objects..... | 110 |
| 4.5.4. Telephony Commands (old versions)..... | 111 |
| 4.5.4.1. Logon (v1)..... | 111 |
| 4.5.4.2. Logoff (v1)..... | 111 |
| 4.5.4.3. QueryLine (v1)..... | 112 |

| | |
|--|-----|
| 4.6. Callback..... | 113 |
| 4.6.1. Callback Commands..... | 113 |
| 4.6.1.1. Logon | 113 |
| 4.6.1.2. Logoff | 113 |
| 4.6.1.3. Accept | 114 |
| 4.6.1.4. Complete | 114 |
| 4.6.1.5. Create | 114 |
| 4.6.1.6. Delete..... | 115 |
| 4.6.1.7. QueryNewCallbacks..... | 116 |
| 4.6.1.8. Update..... | 116 |
| 4.6.1.9. StartListenForEvents..... | 117 |
| 4.6.1.10. StopListenForEvents | 118 |
| 4.6.2. Callback Events | 118 |
| 4.6.2.1. OnDeliveredCallbackEvent..... | 118 |
| 4.6.2.2. OnDivertedCallbackEvent | 119 |
| 4.6.2.3. OnMakeCallFailedCallbackEvent..... | 120 |
| 4.6.2.4. OnServerConnected..... | 121 |
| 4.6.2.5. OnServerDisconnected | 121 |
| 4.6.3. Callback Common Objects | 122 |
| 4.6.3.1. Schedule Object..... | 122 |
| 4.6.3.2. Schedules Object | 122 |
| 4.6.3.3. ContactData Object | 123 |
| 4.7. Web Collaboration..... | 123 |
| 4.7.1. Web Collaboration Commands..... | 123 |
| 4.7.1.1. Logon | 123 |
| 4.7.1.2. Logoff | 123 |
| 4.7.1.3. Accept | 124 |
| 4.7.1.4. Disconnect..... | 124 |
| 4.7.1.5. InviteAgent | 125 |
| 4.7.1.6. DeclineInvite..... | 125 |
| 4.7.1.7. CallMe | 125 |
| 4.7.1.8. RequeueToQueue | 126 |
| 4.7.1.9. RequeueToAgent | 126 |
| 4.7.1.10. AddContent | 127 |
| 4.7.1.11. UpdateContactData | 127 |
| 4.7.1.12. StartListenForEvents | 128 |
| 4.7.1.13. StopListenForEvents | 128 |
| 4.7.2. Web Collaboration Events | 129 |
| 4.7.2.1. OnDeliveredWebChatEvent | 129 |
| 4.7.2.2. OnDivertedWebChatEvent | 131 |
| 4.7.2.3. OnContentWebChatEvent..... | 131 |
| 4.7.2.4. OnDisconnectedWebChatEvent..... | 132 |
| 4.7.2.5. OnEstablishedWebChatEvent | 133 |
| 4.7.2.6. OnConferencedWebChatEvent | 134 |
| 4.7.2.7. OnCallMeAnswerWebChatEvent | 135 |
| 4.7.2.8. OnServerConnectedEvent..... | 136 |
| 4.7.2.9. OnServerDisconnectedEvent | 136 |
| 4.7.3. Web Collaboration Common Objects..... | 137 |
| 4.7.3.1. ChatContent Object..... | 137 |
| 4.7.3.2. ContactData Object | 137 |
| 4.8. OpenMedia..... | 138 |
| 4.8.1. OpenMedia Commands | 138 |
| 4.8.1.1. Logon | 138 |
| 4.8.1.2. Logoff | 138 |

| | |
|--|-----|
| 4.8.1.3. Accept | 139 |
| 4.8.1.4. Disconnect..... | 139 |
| 4.8.1.5. QueryEligibleUsers..... | 139 |
| 4.8.1.6. Reply | 140 |
| 4.8.1.7. Defer | 140 |
| 4.8.1.8. Resume | 141 |
| 4.8.1.9. RequeueToQueue | 141 |
| 4.8.1.10. RequeueToAgent | 142 |
| 4.8.1.11. Discard | 142 |
| 4.8.1.12. QueryDeferredMessages | 143 |
| 4.8.1.13. GetStream | 144 |
| 4.8.1.14. StartListenForEvents | 144 |
| 4.8.1.15. StopListenForEvents | 144 |
| 4.8.2. OpenMedia Events | 145 |
| 4.8.2.1. OnDeliveredOpenMediaEvent..... | 145 |
| 4.8.2.2. OnDisconnectedOpenMediaEvent | 147 |
| 4.8.2.3. OnDivertedOpenMediaEvent..... | 147 |
| 4.8.2.4. OnEstablishedOpenMediaEvent | 148 |
| 4.8.2.5. OnDeferredOpenMediaEvent | 149 |
| 4.8.2.6. OnResumedOpenMediaEvent..... | 150 |
| 4.8.2.7. OnTransferredOpenMediaEvent | 151 |
| 4.8.2.8. OnContentAddedOpenMediaEvent | 151 |
| 4.8.2.9. StreamResponseOpenMediaEvent | 152 |
| 4.8.2.10. OnServerConnected..... | 153 |
| 4.8.2.11. OnServerDisconnected | 154 |
| 4.8.3. OpenMedia Common Objects..... | 155 |
| 4.8.3.1. DeferredList Object | 155 |
| 4.8.3.2. OpenMediaContent Object..... | 155 |
| 4.8.3.3. Attachments Object | 155 |
| 4.8.3.4. Stream Object | 156 |
| 4.9. Real-Time Statistics..... | 156 |
| 4.9.1. Real-Time Statistics Commands..... | 156 |
| 4.9.1.1. StartQuery | 156 |
| 4.9.1.2. StopQuery | 157 |
| 4.9.2. Real Time Statistics Events | 158 |
| 4.9.2.1. UserRealTimeEvent | 159 |
| 4.9.2.2. QueueRealTimeEvent | 160 |
| 4.9.2.3. GroupRealTimeEvent..... | 162 |
| 4.9.2.4. AggregateRealTimeEvent | 163 |
| 4.9.2.5. ContactRealTimeEvent | 164 |
| 4.9.2.6. CallbackRealTimeEvent | 165 |
| 4.9.2.7. UserCumulativeEvent..... | 166 |
| 4.9.2.8. QueueCumulativeEvent | 168 |
| 4.9.2.9. GroupCumulativeEvent | 169 |
| 4.9.2.10. AggregateCumulativeEvent..... | 170 |
| 4.9.2.11. UserWrapUpReasonCumulativeEvent | 172 |
| 4.9.2.12. QueueWrapUpReasonCumulativeEvent | 173 |
| 4.9.2.13. AggregateWrapUpReasonCumulativeEvent | 174 |
| 4.9.2.14. OnServerConnected..... | 175 |
| 4.9.2.15. OnServerDisconnected | 175 |

| | |
|---|------------|
| 5. Definitions | 177 |
| 6. Scenarios with High Availability..... | 194 |
| 6.1. Redundant OpenScape Voice | 195 |
| 6.2. Redundant OSCC..... | 196 |
| 6.3. Redundant Application Server..... | 200 |
| 6.4. Redundant REST SDK Application..... | 201 |


1. About the REST SDK Framework

The REST SDK Framework allows the development of multimedia applications that integrate with the OpenScape Contact Center system.

The framework consists of a REST interface, which allows sending commands from the application to the OpenScape Contact Center and sending monitoring events from the OpenScape Contact Center to the application.

1.1. REST SDK Framework solution overview

The figure below shows a high level overview of the REST SDK architecture.



2. REST SDK Framework prerequisites

For Virtual Agent REST interface there are some steps that must be performed before using the API.

- Knowledge on REST (Representational state transfer) web services.
- Configure a REST SDK profile via the Web Manager.
- Install the **OpenScape Contact Center Application Server** (it can be collocated into OSCC server or into another machine).
- Request for an Integration User license.

Note: For more details about the configuration, see *OpenScape Contact Center Manager Administration Guide*.

Note: For more details about installation of the Application Server, see *OpenScape Contact Center Installation Guide*.

3. REST SDK Principles

3.1. Functional Description

To get access to the REST SDK functions, the external application must register on the REST SDK server.

The monitoring events shall be provided by the REST SDK by means of a Webhook mechanism. During the registration process, the application shall provide the URL which OSCC shall access to send the events.

In a multitenant system, the application must send the business unit name in the registration request. The OpenScape Contact Center will validate the received value against the business unit which is configured for the REST SDK application.


3.2. Configuration

The REST SDK instances must be configured in the Web Manager.

To create a new REST SDK instance:

1. Select the tab REST SDK
2. Click **+ Add REST SDK Client**.
3. A pop-up window with the parameters **Client Name** and **Client Token** appears.
 - a. **Client Name**: Uniquely identifies the REST SDK instance. The Client Name is a string with up to 32 characters.
 - b. **Client Token**: This is a type of password, used to authenticate the REST SDK client during the registration process of the client on the server. You can configure it either manually or generate it automatically by means of a token. Click **Generate Token** and a random 64 bytes token is automatically generated.
4. Click **Add**


The Business Unit Name defines the tenant for which the application has permission to interact in a multitenant system.



3.3. Simple REST SDK flow examples

Below we can see a simple sequence flow that demonstrates how the entire system will integrate with each system processes.

This is the example of an application connection initiation. The application registers on the OpenScape Contact Center, it logs on to the server with a valid user and requests for monitoring for Admin events, Telephony events, Routing events and Presence events.



3.4. HTTP Messages

All REST SDK HTTP requests need to pass the sessionToken in the Authorization Header.

The Registration does not require this Authorization in the header because the session was not established yet.

Then to register a REST SDK application, a Registration Request must be sent as below:

Sample HTTP RegisterApplication Request with body:

```
POST /restsdk/webapi/main/registerApplication HTTP/1.1
Host: 10.80.199.15:8080
Content-Type: application/json; charset=utf-8
Cache-Control: no-cache
{
  "webhookURL": "10.80.199.11",
  "application" :
  {
    "name": "client0",
    "token": "aaaa",
    "busUnitName": "Default"
  }
}
```

A sessionToken will be received in the RegisterApplication Response as below:

Sample HTTP Registration Response (trace from Wireshark):

```
HTTP/1.1 200
Content-Type: application/json
Content-Length: 129
Date: Thu, 18 Oct 2018 12:38:58 GMT
{
  "errorCode": "NO_ERROR",
  "errorText": "NO_ERROR",
  "sessionToken": "895d36c1dc6dd7851d714a85917edfb7fca9dd9365ad971ff5978696f1b3f20c"
}
```

The HTTP message for a Keep Alive Request is as follows:

Sample request:

```
POST /restsdk/webapi/main/keepalive HTTP/1.1
Host: 10.80.199.15:8080
Content-Type: application/json; charset=utf-8
Authorization: Bearer 895d36c1dc6dd7851d714a85917edfb7fca9dd9365ad971ff5978696f1b3f20c
Cache-Control: no-cache
```

Postman-Token: 3b6b9be9-56ce-aa5b-317a-c218cd2bcc82

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4. REST SDK Messages

4.1. Main

4.1.1. Main Commands

4.1.1.1. RegisterApplication

Description: request to register an SDK application. The REST SDK Service answers with a session token which must be used on subsequent requests.

Note: In order to register, the client must provide a valid client name and token. The client name and token can be created via WebManager.

URL: POST /restsdk/webapi/main/registerApplication

| RegisterApplication Request Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| webhookURL | String | URL which shall be used by the OpenScape Contact Center to send the monitoring events. |
| webhookAPIVersion | String | It indicates the version which is being used by OpenScape Contact Center to send the events. |
| application | Object | Credentials to be used for application authentication |

Message Example:

```
//registerApplication request Object
{
  "webhookURL" : "https://applicationhostaddress/applicationpath",
  "webhookAPIVersion" : "V1",
  "application" : {
    "name" : "client0",
    "token" : "a5e272bcfa964c6dea958b583da4e721703bb2a74bff8533a5818ccaedd71669",
    "busUnitName" : "Company1"
  }
}
```

| RegisterApplication Response Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| sessionToken | String | This token must be used in each subsequent request which is sent by the application. It allows the server to validate the request. |

Message Example

```
//RegisterApplication Response
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
  "sessionToken" : "11da906e0dbd3a4ac1b5e53a0b245df97bb1158ad3b211e96c1eb5c4af26ff52"
}
```

4.1.1.2. UnregisterApplication

Description: request to unregister the REST SDK application. It requires Authorization header with session token.

Note: When an application is unregistered, it is unsubscribed from all events it previously subscribed and it is logged off from all media. It cannot send requests anymore unless it is registered again.

URL: POST /restsdk/webapi/v2/main/unregisterApplication

| unregisterApplication Response Object | | |
|---------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example

```
//unregisterApplication Response
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
}
```

4.1.1.3. Logon

Description: request to logon the REST SDK application. The REST SDK application must be logged on to Admin before sending most of the requests, with a few exceptions.

Note 1: It requires Authorization header with session token.

Note 2: The user which logs on here will be used to determine some permissions like for Statistics.

URL: POST /restsdk/webapi/main/logon

| Logon Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the user which shall be used for the application logon. |
| password | String | Password of the user. |

Message Example:

```
//Admin Logon Request Object
{
  "agentKey" : 3,
  "password" : "p"
}
```

| Logon Response Object | | |
|-----------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|---------------------|--------|--|
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//Admin Logon Response
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.1.1.4. KeepAlive

Description: keep alive request to maintain the connection if requests are not sent for a long time

URL: POST /restsdk/webapi/main/keepalive

Message Example:

```
//KeepAliveRequest Object
{}
```

| KeepAliveResponse Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

MessageExample:

```
//KeepAliveResponse
{
  "type" : "keepAlive",
  "errorCode" : 0,
  "errorDetails" : ""
}
```

4.1.1.5. GetServerState

Description: used to get the availability of a media server. This is a Watchdog Command.

Note 1: supported media realm values: TELEPHONY, CALLBACK, WEB_INTERACTION, OPENMEDIA.

Note 2: the values for serverState attribute on the response are the following: UNKNOWN, UNAVAILABLE, PARTIALLY_AVAILABLE, AVAILABLE.

Note 3: the PARTIALLY_AVAILABLE state is returned when the requested media server is AVAILABLE, but the connection state of the Presence server is either UNKNOWN or DISCONNECTED.

URL: POST /restsdk/webapi/main/getserverstate

| GetServerState Request Object | | |
|-------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

| | | |
|--------------|--------|--|
| realm | String | Domain of the contact center for which the state is being requested. See definition of possible values at Realm. |
|--------------|--------|--|

Message Example:

```
//GetServerState Request Object
{
  "realm" : "TELEPHONY",
}
```

| GetServerState Response Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| serverState | String | State of the server. See definition See definition of possible values at ServerState. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//GetServerState Response Object
{
  "serverState" : "AVAILABLE",
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.1.2. Main Commands (old versions)

4.1.2.1. UnregisterApplication (v1)

Note: request kept for compatibility reasons. Applications should use the latest implementation of UnregisterApplication request.

Description: request to unregister the REST SDK application. It requires Authorization header with session token.

Note: When an application is unregistered, it is unsubscribed from all events it previously subscribed and it is logged off from all media. It cannot send requests anymore unless it is registered again.

URL: POST /restsdk/webapi/main/unregisterApplication

| UnregisterApplication Request Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| webhookURL | String | URL which shall be used by the OpenScape Contact Center to send the monitoring events. |
| application | Object | Credentials to be used for application authentication |

Message Example:

```
//unregisterApplication request Object
{
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

"webhookURL" : "https://applicationhostaddress/applicationpath",
"application" : {
  "name" : "client0",
  "token" : "a5e272bcfa964c6dea958b583da4e721703bb2a74bff8533a5818ccaedd71669",
  "busUnitName" : "Company1"
}
}

```

| unregisterApplication Response Object | | |
|---------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| sessionToken | String | Empty |

Message Example

```

//unregisterApplication Response
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
  "sessionToken" : ""
}

```

4.2. Admin

4.2.1. Admin Commands

4.2.1.1. GetUsers

Description: request to query OSCC users on the system.

Note: this request does not require logon. It requires Authorization header with session token.

URL: GET /restsdk/webapi/admin/users

| GetUsers Response Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| users | Object | List of User objects. See the definition of User object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| User Object | | |
|------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Database table unique key of the user. |
| username | String | Name of the user. |
| firstName | String | First name of the user. |
| lastName | String | Last name of the user. |

| | | |
|-------------------------------------|---------|---|
| middleInitial | String | Middle initial of the user. |
| departmentKey | Integer | Key of the department to which the user is associated. |
| acdGroupNumber | String | Group number/Virtual group number to which the user is associated. |
| mediaTypes | List | List of media types to which the user is associated. See the definition of possible values at MediaType . |
| type | String | Type of the user. See the definition of possible values at UserType . |
| agentId | String | Id of the user. |
| multipleContactHandleCapable | Boolean | Identifies if the agent is allowed to handle multiple contacts at a time. |

Message example:

```
//UserResponse Object
{
  "users" :
  [
    {
      "agentKey" : 3,
      "userName" : "UserA",
      "firstName" : "Joe",
      "lastName" : "Miller",
      "middleInitial" : "",
      "departmentKey" : 0,
      "acdGroupNumber" : "0",
      "mediaTypes" : [ //MediaType
        "VOICE",
        "CALLBACK"
      ],
      "type" : "ASSOCIATE_A",
      "agentId" : "100005",
      "multipleContactHandlingCapable" : false
    },
    {
      "agentKey" : 4,
      "userName" : "UserB",
      "firstName" : "Mary",
      "lastName" : "Jane",
      "middleInitial" : "",
      "departmentKey" : 1,
      "acdGroupNumber" : "0",
      "mediaTypes" : [ //MediaType
        "VOICE",
        "CALLBACK"
      ],
      "type" : "ASSOCIATE_A",
      "agentId" : "100006",
      "multipleContactHandlingCapable" : false
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.2. GetQueues

Description: request to query OSCC queues on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/queues

| GetQueues Response Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| queues | Object | List of Queue objects. See the definition of Queue object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| Queue Object | | |
|----------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the queue. |
| name | String | Name of the queue. |
| description | String | Description of the queue. |
| mediaType | String | Media type to which the queue is related. See the definition of possible values at MediaType. |

Message Example:

```
//GetQueues Response Object
{
  "queues" :
  [
    {
      "key" : 7,
      "name" : "Default Voice Queue",
      "description" : "Default Voice Queue",
      "mediaType" : "VOICE" //MediaType
    },
    {
      "key" : 2,
      "name" : "Default Callback Queue",
      "description" : "Default Callback Queue",
      "mediaType" : "CALLBACK" //MediaType
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.3. GetQueues V2

Description: request to query OSCC queues on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/v2/admin/queues

| GetQueues Response Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| queues | Object | List of Queue objects. See the definition of Queue object. |

| | | |
|---------------------|--------|--|
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| Queue Object | | |
|--------------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the queue. |
| name | String | Name of the queue. |
| description | String | Description of the queue. |
| mediaType | String | Media type to which the queue is related. See the definition of possible values at MediaType. |
| queueSteps | Object | List of Queue steps for this queue. See following data Object definition. |

| Queue Object | | |
|-------------------|----------------|--|
| Attribute name | Attribute type | Description |
| stepNumber | Integer | The configured Queue step sequence number. |
| groupKey | Integer | Database table unique key of the Group. |

Message Example:

```
//GetQueues Response Object
{
  "errorCode": "NO_ERROR",
  "errorDetails": "NO_ERROR",
  "queues": [{
    "key": 1,
    "name": "Default Voice Queue",
    "description": "Default voice queue.",
    "mediaType": "VOICE",
    "queueSteps": [{
      "stepNumber": 1,
      "groupKey": 2
    },
    {
      "stepNumber": 2,
      "groupKey": 3
    }
  ]
},
{
  "key": 3,
  "name": "Default Callback Queue",
  "description": "Default callback queue.",
  "mediaType": "CALLBACK",
  "queueSteps": [{
    "stepNumber": 1,
    "groupKey": 1
  }]
}]
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.2.1.4. GetHotStandbyState

Request to query Hot Standby state.

Requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/telephony/hotstandbystate

| GetHotStandbyState Request Object | | |
|-----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| state | String | Hot Standby State of the OSCC node. See the definition of possible values at HotStandbyState. |

Message Example:

```
// GetHotStandbyState Response Object:
{
  "state": "ACTIVE",
  "errorCode": "NO_ERROR",
  "errorDetails": "NO_ERROR"
}
```

4.2.1.5. SetHotStandbyState

Request to set Hot Standby state.

Requires logon and Authorization header with session token.

URL: POST /restsdk/webapi/telephony/hotstandbystate

| SetHotStandbyState Request Object | | |
|-----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| state | String | Set Hot Standby State of the OSCC node. It forces the switchover: the Active node goes to Standby state. Possible value: STANDBY |

Message Example:

```
// SetHotStandbyState Request Object:
{
  "state": "STANDBY"
}
```

| SetHotStandbyState Response Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
// SetHotStandbyState Response Object:
{
  "errorCode" : "NO_ERROR",
}
```

```

    "errorDetails" : "NO_ERROR"
}

```

4.2.1.6. GetGroups

Description: request to query OSCC groups on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/groups

| GetGroups Response Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| groups | Object | List of Group objects. See the definition of Group object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| Group Object | | |
|--------------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the group. |
| name | String | Name of the group. |
| description | String | Description of the group. |

Message Example:

```

//GroupResponse Object
{
  "groups" :
  [
    {
      "key" : 0,
      "name" : "Group1",
      "description" : "Group 1"
    },
    {
      "key" : 1,
      "name" : "Group2",
      "description" : "Group 2"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.2.1.7. GetDepartments

Description: request to query OSCC departments on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/departments

| GetDepartments Response Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| departments | Object | List of Department objects. See the definition of the Department object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| Department Object | | |
|-------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the department. |
| name | String | Name of the department. |
| description | String | Description of the department. |

Message Example:

```
//DepartmentResponse
{
  "departments" :
  [
    {
      "key" : 2,
      "name" : "Service",
      "description" : "Service Department"
    },
    {
      "key" : 1,
      "name" : "Sales",
      "description" : "Sales Department"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.8. GetAggregates

Description: request to query OSCC aggregates on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/aggregates

| GetAggregates Response Object | | |
|-------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| aggregates | Object | List of aggregate objects. See the definition of Aggregate object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

| Aggregate Object | | |
|--------------------|----------------|---|
| Attribute name | Attribute type | Description |
| description | String | Description of the aggregate. |
| key | Integer | Database table unique key of the aggregate. |
| mediaType | String | Media type to which the aggregate is related. See definition of possible values at MediaType. |
| name | String | Name of the aggregate. |

Message Example:

```
//AggregateResponse Object
{
  "aggregates" : [
    {
      "description" : "",
      "key" : 1,
      "mediaType" : "VOICE",
      "name" : "Aggregate 1"
    },
    {
      "description" : "",
      "key" : 2,
      "mediaType" : "VOICE",
      "name" : "Aggregate 2"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.9. GetUnavailableReasons

Description: request to query OSCC unavailable reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/unavailablereasons

GetUnavailableReasons Response Object

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| Attribute name | Attribute type | Description |
|---------------------|----------------|--|
| reasons | Object | List of unavailable reason objects. See the definition of the Reason object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//UnavailableReasonResponse Object
{
  "reasons" :
  [
    {
      "reasonKey" : 5,
      "name" : "Reason 1",
      "description" : ""
    },
    {
      "reasonKey" : 6,
      "name" : "Reason 2",
      "description" : ""
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.10. GetWrapUpReasons

Description: request to query OSCC wrap-up reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/wrapupreasons

| GetWrapUpReasons Response Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| reasons | Object | List of wrap up reason objects. See the definition of the Reason object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//WrapUpReasonResponse Object
{
  "reasons" :
  [
```

```

    {
      "reasonKey" : 5,
      "name" : "Reason 1",
      "description" : "Wrap-up for OpenMedia queue."
    },
    {
      "reasonKey" : 6,
      "name" : "Reason 2",
      "description" : "Wrap-up for Voice queue."
    }
  ]
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

4.2.1.11. GetWorkReasons

Description: request to query OSCC work reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/workreasons

| GetWorkReasons Response Object | | |
|--------------------------------|-----------------|--|
| Attribute name | Attribute type | Description |
| reasons | List of Objects | List of work reason objects. See the definition of the Reason object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```

//WorkReasonResponse Object
{
  "reasons" :
  [
    {
      "reasonKey" : 5,
      "name" : "Automatic",
      "description" : "Automatic work via the communication platform."
    },
    {
      "reasonKey" : 6,
      "name" : "Sales",
      "description" : "Finish sales process"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

4.2.1.12. GetPostProcessingReasons

Description: request to query OSCC Post-processing reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/postprocessingreasons

| GetPostProcessingReasons Response Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| reasons | Object | List of post processing reason objects. See the definition of the Reason object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//PostProcessingReasonResponse Object
{
  "reasons" :
  [
    {
      "reasonKey" : 5,
      "name" : "Automatic",
      "description" : "Automatic post-processing after contact."
    },
    {
      "reasonKey" : 6,
      "name" : "Mandatory",
      "description" : "Mandatory post-processing required."
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.13. GetCallbackRetryReasons

Description: request to query Callback retry reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/callbackretryreasons

| GetCallbackRetryReasons Response Object | | |
|---|----------------|--|
| Attribute name | Attribute type | Description |
| reasons | Object | List of Callback retry reasons. See the definition of the Reason object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//PostCallbackRetryReasonsResponse Object
{
  "reasons" :
  [
    {
```

```

        "description" : "Automatic post-processing after contact.",
        "reasonKey" : 5,
        "name" : "Automatic"
    },
    {
        "description" : "Mandatory post-processing required.",
        "reasonKey" : 6,
        "name" : "Mandatory"
    }
],
"errorCode" : "NO_ERROR",
"errorDetails" : "NO_ERROR"
}

```

4.2.1.14. GetCallbackDeleteReasons

Description: request to query Callback delete reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/ callbackdeletereasons

| GetCallbackDeleteReasons Response Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| reasons | Object | List of Callback delete reasons. See the definition of the Reasons object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```

//PostCallbackDeleteReasonsResponse Object
{
  "reasons" :
  [
    {
      "description" : "Automatic post-processing after contact.",
      "reasonKey" : 5,
      "name" : "Automatic"
    },
    {
      "description" : "Mandatory post-processing required.",
      "reasonKey" : 6,
      "name" : "Mandatory"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

4.2.1.15. GetOpenMediaConnectors

Description: request to query OpenMedia connectors on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/ openmediaconnectors

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| GetOpenMediaConnectors Response Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| connectors | Object | List of configured connectors. See the definition of the Connectors object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//OpenMediaConnectorsResponse Object
{
  "connectors" :
  [
    {
      "connectorKey" : 5,
      "connectorName" : "CompanySystem1"
    },
    {
      "connectorKey" : 6,
      "connectorName" : "CompanySystem2"
    }
  ],
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.1.16. GetOpenMediaDiscardReasons

Description: request to query OpenMedia discard reasons on the system.

Note: It requires logon and Authorization header with session token.

URL: GET /restsdk/webapi/admin/ openmediadiscardreasons

| GetOpenMediaDiscardReasons Response Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| reasons | Object | List of OpenMedia discard reasons. See the definition of the Reasons object. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//OpenMediaDiscardReasonsResponse Object
{
  "reasons" :
  [
    {
      "description" : "Default reason.",
      "reasonKey" : 5,
      "name" : "Default discard reason"
    },
    {
      "description" : "Mandatory post-processing required.",
      "reasonKey" : 6,
      "name" : "Mandatory"
    }
  ]
}
```

```

],
"errorCode" : "NO_ERROR",
"errorDetails" : "NO_ERROR"
}

```

4.2.1.17. StartListenForEvents

Description: request to start listening for Admin server events.

Note: It requires logon and Authorization header with session token. No HTTP body is required to be posted.

URL: POST /restsdk/webapi/admin/startlistenforevents

| StartListenForEvents Response Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```

//StartListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

4.2.1.18. StopListenForEvents

Description: request to stop listening for Admin server events.

Note: It requires logon and Authorization header with session token. No HTTP body is required to be posted.

URL: POST /restsdk/webapi/admin/stoplistenforevents

| StopListenForEvents Response Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

Message Example:

```
//StopListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.2.2. Admin Events

In general, Admin Events have the following structure:

4.2.2.1. OnUserUpdateEvent

Description: event generated when a user is created/updated.

| OnUserUpdateEvent Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserUpdateEvent Data Object | | |
|-------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnUserUpdateEvent Entity Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Database table unique key of the user which has been changed. |
| userName | String | User name of the user. |
| agentId | String | Id of the user which has been changed. |
| firstName | String | First name of the user. |
| lastName | String | Last name of the user. |
| middleInitial | String | Middle initial of the user. |
| departmentKey | Integer | Database table unique key of the department to which the user is associated. |
| acdGroupNumber | String | Group number/Virtual group number to which the user is associated. |
| mediaTypes | List | List of media types to which the user is associated. See the definition of possible values at MediaTypes. |
| type | String | Type of the user. See the definition of possible values at UserType. |
| multipleContactHandlingCapable | Boolean | Identifies if the agent is allowed to handle multiple contacts at a time. |

Message Example:

```
//OnUserUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
```

```

"realm" : "ADMINISTRATION",
"type" : "USER_UPDATED_EVENT",
"data" :
{
  "eventAction" : "ADD",
  "entity" : {
    "agentKey" : 1,
    "userName" : "jsilva",
    "agentId" : "1001",
    "firstName" : "jose",
    "lastName" : "silva",
    "middleInitial" : "c",
    "departmentKey" : 0,
    "acdGroupNumber" : "0",
    "mediaTypes" :
    [
      "OPENMEDIA",
      "WEB_COLLABORATION",
      "EMAIL",
      "CALLBACK",
      "VOICE"
    ],
    "type" : "ASSOCIATE_A",
    "multipleContacthandlingCapable" : false,
  }
}
}
}

```

4.2.2.2. OnQueueUpdateEvent

Description: event generated when queue is created/updated

| OnQueueUpdateEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnQueueUpdateEvent Data Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnQueueUpdateEvent Entity Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Queue which has been changed. |
| name | String | Name of the Queue. |
| description | String | Description of the Queue. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|------------------|--------|---|
| mediaType | String | Media type to which the Queue is related. See the definition of possible values at MediaType. |
|------------------|--------|---|

Message Example:

```
//OnQueueUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "QUEUE_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "key" : 1,
        "name" : "Default Voice Queue",
        "description" : "Default voice queue",
        "mediaType" : "VOICE"
      }
    }
  }
}
```

4.2.2.3. OnGroupUpdateEvent

Description: event generated when group is created/updated

| OnGroupUpdateEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnGroupUpdateEvent Data Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnGroupUpdateEvent Entity Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Group which has been changed. |
| name | String | Name of the Group. |
| description | String | Description of the Group. |

Message Example:

```
//OnGroupUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "GROUP_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "key" : 1,
        "name" : "Default Group",
        "description" : "Default group"
      }
    }
  }
}
```

4.2.2.4. OnDepartmentUpdateEvent

Description: event generated when department is created/updated

| OnDepartmentUpdateEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Data Object | Content of the event. See following data Object definition. |

| OnDepartmentUpdateEvent Data Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnDepartmentUpdateEvent Entity Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Department which has been changed. |
| name | String | Name of the Department. |
| description | String | Description of the Department. |

Message Example:

```
//OnDepartmentUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "type" : "DEPARTMENT_UPDATED_EVENT",
    "data" :
    {
        "eventAction" : "ADD",
        "entity" : {
            "key" : 1,
            "name" : "Sales1",
            "description" : "Sales Department 1"
        }
    }
}
}

```

4.2.2.5. OnAggregateUpdateEvent

Description: event generated when aggregate is created/updated

| OnAggregateUpdateEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnAggregateUpdateEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnAggregateUpdateEvent Entity Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Aggregate which has been changed. |
| name | String | Name of the Aggregate. |
| description | String | Description of the Aggregate. |
| mediaType | String | Media type to which the aggregate is related. See the definition of possible values at MediaTypes. |

Message Example:

```

//OnAggregateUpdateEvent Object
{
    "type" : "EVENT",
    "data" :
    {
        "realm" : "ADMINISTRATION",
        "type" : "AGGREGATE_UPDATED_EVENT",
        "data" :
        {
            "eventAction" : "ADD",
            "entity" : {
                "key" : 1,
                "name" : "Aggregate 1",

```

```

        "description" : "Aggregate description",
        "mediaType" : "VOICE"
    }
}
}
}

```

4.2.2.6. OnPostProcessingReasonUpdateEvent

Description: event generated when post-processing reason is created/updated

| OnPostProcessingReasonUpdateEvent Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnPostProcessingReasonUpdateEvent Data Object | | |
|---|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnPostProcessingReasonUpdateEvent Entity Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Database table unique key of the Post Processing Reason which has been changed. |
| name | String | Name of the Post Processing Reason. |
| description | String | Description of the Post Processing Reason. |

Message Example:

```

//OnPostProcessingReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "POSTPROCESSINGREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Customer data update",
        "description" : "Agent is updating customer data."
      }
    }
  }
}

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

}
}

```

4.2.2.7. OnUnavailableReasonUpdateEvent

Description: event generated when unavailable reason is created/updated

| OnUnavailableReasonUpdateEvent Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUnavailableReasonUpdateEvent Data Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnUnavailableReasonUpdateEvent Entity Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Database table unique key of the Unavailable Reason which has been changed. |
| name | String | Name of the Unavailable Reason. |
| description | String | Description of the Unavailable Reason. |

Message Example:

```

//OnUnavailableReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "UNAVAILABLEREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Lunch break",
        "description" : "Lunch break."
      }
    }
  }
}

```

4.2.2.8. OnWrapUpReasonUpdateEvent

Description: event generated when WrapUp reason is created/updated

| OnWrapUpReasonUpdateEvent Object | | |
|----------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

| | | |
|--------------|--------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnWrapUpReasonUpdateEvent Data Object | | |
|--|-----------------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnWrapUpReasonUpdateEvent Entity Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Database table unique key of the Wrap Up Reason which has been changed. |
| name | String | Name of the Wrap Up Reason. |
| description | String | Description of the Wrap Up Reason. |

Message Example:

```
//OnWrapUpReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "WRAPUPREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Sales registration",
        "description" : "Concluding sales operation."
      }
    }
  }
}
```

4.2.2.9. OnCallbackReasonUpdateEvent

Description: event generated when Callback reason is created/updated

| OnCallbackReasonUpdateEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnCallbackReasonUpdateEvent Data Object | | |
|--|--|--|
|--|--|--|

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| Attribute name | Attribute type | Description |
|----------------|----------------|--|
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnCallbackReasonUpdateEvent Entity Object | | |
|---|----------------|--|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Database table unique key of the Callback Reason which has been changed. |
| name | String | Name of the Callback Reason. |
| description | String | Description of the Callback Reason. |

Message Example (Retry Reason):

```
//OnCallbackReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "CALLBACK_RETRYREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Sales registration",
        "description" : "Concluding sales operation."
      }
    }
  }
}
```

Message Example (Delete Reason):

```
//OnCallbackReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "CALLBACK_DELETEREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "ADD",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Duplicate callback",
        "description" : "Duplicate callback."
      }
    }
  }
}
```

4.2.2.10. OnOpenMediaDiscardReasonUpdateEvent

Description: event generated when OpenMedia Discard reason is created/updated

| OnOpenMediaDiscardReasonUpdateEvent Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnOpenMediaDiscardReasonUpdateEvent Data Object | | |
|---|----------------|--|
| Attribute name | Attribute type | Description |
| eventAction | String | Action which caused the event. See the definition of possible values at EventAction. |
| entity | Entity Object | Object containing the attributes of updated user. |

| OnOpenMediaDiscardReasonUpdateEvent Entity Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Database table unique key of the Wrap Up Reason which has been changed. |
| name | String | Name of the Wrap Up Reason. |
| description | String | Description of the Wrap Up Reason. |

Message Example:

```
//OnOpenMediaDiscardReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "OPENMEDIA_DISCARDREASON_UPDATED_EVENT",
    "data" :
    {
      "eventAction" : "UPDATE",
      "entity" : {
        "reasonKey" : 1,
        "name" : "Sales registration",
        "description" : "Concluding sales operation."
      }
    }
  }
}
```

4.2.2.11. OnDeleteEvent

Description: event generated when an entity is deleted.

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

The following entities are supported: Aggregates, Groups, Departments, Users, Work reasons, Unavailable reasons, Queues, WrapUp reasons, PostProcessing reasons, Callback retry reasons, Callback delete reasons, OpenMedia discard reasons.

| OnDeleteEvent Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Data Object | Object with the keys of the Entities which have been deleted. |

| OnDeleteEvent Data Object | | |
|---------------------------|-----------------|---|
| Attribute name | Attribute type | Description |
| keyList | List of Integer | List with the keys of the Entities which have been deleted. |

Message Example://OnDeleteEvent Object

```
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "USER_DELETED_EVENT",
    "data" : {
      "keyList" : [7]
    }
  }
}
```

4.2.2.12. OnServerConnectedEvent

Description: event triggered when connection to Admin server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```
//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
  }
}
```

```

    {
      "serverName" : "localhost"
    }
  }
}

```

4.2.2.13. OnServerDisconnectedEvent

Description: event triggered when connection to Admin server is lost.

| OnServerDisconnectedEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```

//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : "localhost"
    }
  }
}

```

4.2.3. Admin Events (old versions)

These events are kept for backwards compatibility purposes. These events are only triggered if WebhookAPI version is set to V1 upon registering application.

In general, Admin Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at MessageType |
| data | Object | Content of the message. See definition of this object for each event type. |

4.2.3.1. OnUserUpdateEvent (v1)

Description: event generated when a user is created/updated

| OnUserUpdateEvent Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserUpdateEvent Data Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Database table unique key of the user which has been changed. |
| userName | String | User name of the user. |
| agentId | String | Id of the user which has been changed. |
| firstName | String | First name of the user. |
| lastName | String | Last name of the user. |
| middleInitial | String | Middle initial of the user. |
| departmentKey | Integer | Database table unique key of the department to which the user is associated. |
| acdGroupNumber | String | Group number/Virtual group number to which the user is associated. |
| mediaTypes | List | List of media types to which the user is associated. See the definition of possible values at MediaType. |
| type | String | Type of the user. See the definition of possible values at UserType. |
| multipleContactHandlingCapable | Boolean | Identifies if the agent is allowed to handle multiple contacts at a time. |

Message Example:

```
//OnUserUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "USER_UPDATED_EVENT",
    "data" :
    {
      "agentKey" : 1,
      "userName" : "jsilva",
      "agentId" : "1001",
      "firstName" : "jose",
      "lastName" : "silva",
      "middleInitial" : "c",
      "departmentKey" : 0,
      "acdGroupNumber" : "0",
      "mediaTypes" :
      [
        "OPENMEDIA",
        "WEB_COLLABORATION",
        "EMAIL",
        "CALLBACK",
        "VOICE"
      ],
    },
  },
}
```

```

        "type" : "ASSOCIATE_A",
        "multipleContacthandlingCapable" : false,
    }
}
}

```

4.2.3.2. OnQueueUpdateEvent (v1)

Description: event generated when queue is created/updated

| OnQueueUpdateEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnQueueUpdateEvent Data Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Queue which has been changed. |
| name | String | Name of the Queue. |
| description | String | Description of the Queue. |
| mediaType | String | Media type to which the Queue is related. See the definition of possible values at MediaType. |

Message Example:

```

//OnQueueUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "QUEUE_UPDATED_EVENT",
    "data" :
    {
      "key" : 1,
      "name" : "Default Voice Queue",
      "description" : "Default voice queue",
      "mediaType" : "VOICE"
    }
  }
}
}

```

4.2.3.3. OnGroupUpdateEvent (v1)

Description: event generated when group is created/updated

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| OnGroupUpdateEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnGroupUpdateEvent Data Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Group which has been changed. |
| name | String | Name of the Group. |
| description | String | Description of the Group. |

Message Example:

```
//OnGroupUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "GROUP_UPDATED_EVENT",
    "data" :
    {
      "key" : 1,
      "name" : "Default Group",
      "description" : "Default group"
    }
  }
}
```

4.2.3.4. OnDepartmentUpdateEvent (v1)

Description: event generated when department is created/updated

| OnDepartmentUpdateEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnDepartmentUpdateEvent Data Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| key | Integer | Database table unique key of the Department which has been changed. |
| name | String | Name of the Department. |
| description | String | Description of the Department. |

Message Example:

```
//OnDepartmentUpdateEvent Object
{
```

```

"type" : "EVENT",
"data" :
{
  "realm" : "ADMINISTRATION",
  "type" : "DEPARTMENT_UPDATED_EVENT",
  "data" :
  {
    "key" : 1,
    "name" : "Sales1",
    "description" : "Sales Department 1"
  }
}
}

```

4.2.3.5. OnAggregateUpdateEvent (v1)

Description: event generated when aggregate is created/updated

| OnAggregateUpdateEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnAggregateUpdateEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | Integer | Key of the Aggregate which has been changed. |
| name | String | Name of the Aggregate. |
| description | String | Description of the Aggregate. |
| mediaType | String | Media type to which the aggregate is related. See the definition of possible values at MediaTypes. |

Message Example:

```

//OnAggregateUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "AGGREGATE_UPDATED_EVENT",
    "data" :
    {
      "key" : 1,
      "name" : "Aggregate 1",
      "description" : "Aggregate description",
      "mediaType" : "VOICE"
    }
  }
}

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.2.3.6. OnPostProcessingReasonUpdateEvent (v1)

Description: event generated when post-processing reason is created/updated

| OnPostProcessingReasonUpdateEvent Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnPostProcessingReasonUpdateEvent Data Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Key of the Post Processing Reason which has been changed. |
| name | String | Name of the Post Processing Reason. |
| description | String | Description of the Post Processing Reason. |

Message Example:

```
//OnPostProcessingReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "POSTPROCESSINGREASON_UPDATED_EVENT",
    "data" :
    {
      "reasonKey" : 1,
      "name" : "Customer data update",
      "description" : "Agent is updating customer data."
    }
  }
}
```

4.2.3.7. OnUnavailableReasonUpdateEvent (v1)

Description: event generated when unavailable reason is created/updated

| OnUnavailableReasonUpdateEvent Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUnavailableReasonUpdateEvent Data Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Key of the Unavailable Reason which has been changed. |
| name | String | Name of the Unavailable Reason. |
| description | String | Description of the Unavailable Reason. |

Message Example:

```
//OnUnavailableReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "UNAVAILABLEREASON_UPDATED_EVENT",
    "data" :
    {
      "reasonKey" : 1,
      "name" : "Lunch break",
      "description" : "Lunch break."
    }
  }
}
```

4.2.3.8. OnWrapUpReasonUpdateEvent (v1)

Description: event generated when WrapUp reason is created/updated

| OnWrapUpReasonUpdateEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnWrapUpReasonUpdateEvent Data Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Key of the Wrap Up Reason which has been changed. |
| name | String | Name of the Wrap Up Reason. |
| description | String | Description of the Wrap Up Reason. |

Message Example:

```
//OnWrapUpReasonUpdateEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "WRAPUPREASON_UPDATED_EVENT",
    "data" :
    {
      "reasonKey" : 1,
      "name" : "Sales registration",
      "description" : "Concluding sales operation."
    }
  }
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.2.3.9. OnCallbackReasonUpdateEvent (V1)

Description: event generated when Callback reason is created/updated

| OnCallbackReasonUpdateEvent Object | | |
|------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnCallbackReasonUpdateEvent Data Object | | |
|---|----------------|--|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Key of the Callback Reason which has been changed. |
| name | String | Name of the Callback Reason. |
| description | String | Description of the Callback Reason. |

Message Example (Retry Reason):

```
//OnCallbackReasonUpdateEvent Object
{
  "type": "EVENT",
  "data":
  {
    "realm": "ADMINISTRATION",
    "type": "CALLBACK_RETRYREASON_UPDATED_EVENT",
    "data":
    {
      "reasonKey": 1,
      "name": "Sales registration",
      "description": "Concluding sales operation."
    }
  }
}
```

Message Example (Delete Reason):

```
//OnCallbackReasonUpdateEvent Object
{
  "type": "EVENT",
  "data":
  {
    "realm": "ADMINISTRATION",
    "type": "CALLBACK_DELETEREASON_UPDATED_EVENT",
    "data":
    {
      "reasonKey": 1,
      "name": "Duplicate callback",
      "description": "Duplicate callback."
    }
  }
}
```

4.2.3.10. OnDeleteEvent (v1)

Description: event generated when an entity is deleted.

The following entities are supported: Aggregates, Groups, Departments, Users, Work reasons, Unavailable reasons, Queues, WrapUp reasons, PostProcessing reasons, Callback retry reasons, Callback delete reasons.

| OnUserDeletedEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | List | List with the keys of the Entities which have been deleted. |

Message Example://OnDeleteEvent Object

```
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ADMINISTRATION",
    "type" : "USER_DELETED_EVENT",
    "data" : ["7"]
  }
}
```

4.3. Presence

4.3.1. Presence Commands

In general the response to the Presence Commands has the following format:

| PresenceCommands Response Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.3.1.1. SetRoutingState

Description: request to set the routing (presence) state for an agent.

Note: the reason attribute only applies for UNAVAILABLE and WORK states and it's the reason key for the reason which is being applied. For AVAILABLE state, the attribute value sent is simply ignored. The reason key can be retrieved with the GetUnavailableReasons and GetWorkReasons requests (Admin Control).

URL: POST /restsdk/webapi/presence/setroutingstate

| SetRoutingState Request Object | | |
|--------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-----------------|---------|--|
| state | String | Routing state to which the agent shall be changed. See definition of possible values at RoutingStates. |
| agentId | String | Id of the agent for which the routing state shall be changed. |
| agentKey | Integer | Key of the agent for which the routing state shall be changed. |
| reason | String | Reason for which the routing state is being changed. |

Message Example:

```
//SetRoutingState Request Object
{
  "state" : "AVAILABLE",
  "agentId" : "1000",
  "agentKey" : 3,
  "reason" : 0
}
//SetRoutingState Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}
```

4.3.1.2. GetRoutingState

Description: Request to get the routing state for an agent.

URL: GET /restsdk/webapi/presence/getroutingstate

| GetRoutingState Request Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent for each to return the data. |

Request Example:

```
//GetRoutingStateRequest Object
{
  "agentId" : 3
}
```

| GetRoutingState Response Object | | |
|---------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of agent for which routing state event has been reported. |
| agentKey | Integer | Key of agent for which routing state event has been reported. |
| extension | String | Extension number associated to the agent. |
| loggedOnMediaTypes | List | List of the media types to which the agent is logged on. See definition of possible values at MediaType. |
| presenceState | String | Presence state of the agent. See definition of possible values at PresenceStates. |
| routingState | String | Routing state of the agent. See definition of possible values at RoutingStates. |
| routingStateReasonKey | Integer | Key of a reason associated to the routing state. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Response Example:

```
//GetRoutingStateResponse Object
```

```

{
  "agentId" : "100001",
  "agentKey" : 3,
  "extension" : "554181015002",
  "loggedOnMediaTypes" :
  [
    "VOICE",
    "CALLBACK"
  ],
  "presenceState" : "AWAY",
  "routingState" : "UNAVAILABLE",
  "routingStateReasonKey" : 0,
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}

```

4.3.1.3. RequestPostProcessing

Description: request to set a post-processing reason when an agent enters on post processing state.
 URL: POST /restsdk/webapi/presence/requestpostprocessing

| RequestPostProcessing Request Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| postProcessingReason | Integer | Key of the post processing reason to be applied to the contact. |
| agentId | String | Id of the agent which is handling the contact. |
| agentKey | Integer | Key of the agent which is handling the contact. |
| uniqueCallId | String | Call ID of the contact to which the post processing reason shall be applied. |
| requeueCount | Integer | Number of times the contact has been requeued. |

Message Example:

```

//RequestPostProcessing Request Object
{
  "postProcessingReason" : 0,
  "agentId" : "1000",
  "agentKey" : 3,
  "uniqueCallId" : "1491539316351272",
  "requeueCount" : 0
}

```

Message Example:

```

//RequestPostProcessing Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}

```

4.3.1.4. ExitPostProcessing

Description: request to exit the post-processing state for an agent.
 URL: POST /restsdk/webapi/presence/exitpostprocessing

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| ExitPostProcessing Request Object | | |
|-----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent which is handling the contact. |
| agentKey | Integer | Key of the agent which is handling the contact. |
| uniqueCallId | String | Call ID of the contact which shall exit the post processing state. |
| requeueCount | Integer | Number of times the contact has been requeued. |

Message Example:

```
//ExitPostProcessing Request Object
{
  "agentId" : "1000",
  "agentKey" : 3,
  "uniqueCallId" : "1491539316351272",
  "requeueCount" : 0
}
```

Message Example:

```
//ExitPostProcessing Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}
```

4.3.1.5. SetPrimary

Description: request to set a contact as primary contact. Applies for multiple contact handling.

URL: POST /restsdk/webapi/presence/setprimary

| SetPrimary Request Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent which is handling the contact. |
| agentKey | Integer | Key of the agent which is handling the contact. |
| uniqueCallId | String | Call ID of the contact which shall be set to primary. |
| requeueCount | Integer | Number of times the contact has been requeued. |

Message Example:

```
//SetPrimary Request Object
{
  "agentId" : "1000",
  "agentKey" : 3,
  "uniqueCallId" : "1491539316351272",
  "requeueCount" : 0
}
```

Message Example:

```
//SetPrimary Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}
```

4.3.1.6. CancelMandatoryWrappingUp

Description: request to cancel the mandatory wrap-up for a contact. The agent can then exit post-

processing state without saving the wrap-up reason.

URL: POST /restsdk/webapi/presence/cancelmandatorywrappingup

| CancelMandatoryWrappingUp Request Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent which is handling the contact. |
| agentKey | Integer | Key of the agent which is handling the contact. |
| uniqueCallId | String | Call ID of the contact for which mandatory wrap up shall be canceled.. |
| requeueCount | Integer | Number of times the contact has been requeued. |

Message Example:

```
//CancelMandatoryWrappingUp Request Object
{
  "agentId" : "1000",
  "agentKey" : 3,
  "uniqueCallId" : "1491539316351272",
  "requeueCount" : 0
}
//CancelMandatoryWrappingUp Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}
```

4.3.1.7. SetWrapUpReason

Description: request to set (save) the wrap-up reason(s) for a contact.

URL: POST /restsdk/webapi/presence/setwrapupreason

| SetWrapUpReason Request Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| wrapUpReasons | List | List of reason keys which shall be applied to the contact. |
| queueKey | Integer | Key of the queue which is associated to this contact. |
| agentId | String | Id of the agent which is handling the contact. |
| agentKey | Integer | Key of the agent which is handling the contact. |
| uniqueCallId | String | Call ID of the contact to which the wrap up reasons shall be applied. |
| requeueCount | Integer | Number of times the contact has been requeued. |

Message Example:

```
//SetWrapUpReason Request Object
{
  "wrapUpReasons" : [1],
  "queueKey" : 1,
  "agentId" : "1000",
  "agentKey" : 3,
  "uniqueCallId" : "1491539316351272",
  "requeueCount" : 0
}
//SetWrapUpReason Response Object
{
  "errorCode" : "PRESENCE_ACTION_SUCCEED",
  "errorDetails" : "PRESENCE_ACTION_SUCCEED"
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.3.1.8. StartListenForEvents

Description: request to start listening for Presence events. The resource is the agent key.
URL: POST /restsdk/webapi/presence/startlistenforevents

| StartListenForEvents Request Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | Integer | Key of the agent to start monitoring. Wildcard '*' indicates that the request applies to all agents configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StartListenForEvents Request Object
{
  "resource" : 3
}
//StartListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.3.1.9. StopListenForEvents

Description: request to stop listening for Presence events. The resource is the agent key.
URL: POST /restsdk/webapi/presence/stoplistenforevents

| StopListenForEvents Request Object | | |
|------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| resource | Integer | Key of the agent to stop monitoring. Wildcard '*' indicates that the request applies to all agents configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StopListenForEvents Request Object
{
  "resource" : "3"
}
//StopListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.3.2. Presence Events

In general, Presence Events have the following structure:

| Event Object | | |
|----------------|----------------|-------------|
| Attribute name | Attribute type | Description |

| | | |
|------|--------|--|
| type | String | Type of message. See definition of possible values at MessageType |
| data | Object | Content of the message. See definition of this object for each event type. |

4.3.2.1. OnUserMediaEvent

Description: event triggered when there is a change on media state for a user (e.g. Logon/logoff).

| OnUserMediaEvent Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserMediaEvent Data Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentId | String | Id of agent for which routing state event has been reported. |
| agentKey | Integer | Key of agent for which routing state event has been reported. |
| extension | String | Extension number associated to the agent. |
| mediaType | List | Media type to which the agent is logged on. See definition of possible values at MediaType. |
| mediaState | String | Presence state of the agent. See definition of possible values at MediaState. |
| connectorKey | Integer | Key of the connector for which the agent has logged of for OpenMedia. |

Message Example:

```
//OnUserMediaEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "PRESENCE",
    "type" : "USER_MEDIA_STATE",
    "data" :
    {
      "agentId" : "100001",
      "agentKey" : 3,
      "extension" : "554181015002",
      "mediaType" : "VOICE",
      "mediaState" : "LOGON",
      "connectorKey" : 0
    }
  }
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.3.2.2. OnRoutingStateEvent

Description: event triggered when there is a change on the routing/presence state for a user (e.g. Available/unavailable).

| OnRoutingStateEvent Object | | |
|-----------------------------------|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnRoutingStateEvent Data Object | | |
|--|-----------------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of agent for which routing state event has been reported. |
| agentKey | Integer | Key of agent for which routing state event has been reported. |
| extension | String | Extension number associated to the agent. |
| handlingStates | List | List of Handling State objects for each call on which the agent is involved. See definition of HandlingState object. |
| loggedOnMediaTypes | List | List of the media types to which the agent is logged on. See definition of possible values at MediaType. |
| presenceState | String | Presence state of the agent. See definition of possible values at PresenceStates. |
| routingState | String | Routing state of the agent. See definition of possible values at RoutingStates. |
| routingStateReasonKey | Integer | Key of a reason associated to the routing state. |

Message Example:

```
//OnRoutingStateEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "PRESENCE",
    "type" : "USER_ROUTING_STATE",
    "data" :
    {
      "agentId" : "100001",
      "agentKey" : 3,
      "extension" : "554181015002",
      "handlingStates" :
      [
        {
          "uniqueCallId" : "3567890321",
          "handlingState" : "IDLE",
```

```

        "handlingStateReasonKey" : 0,
        "primary" : true,
        "mediaType" : "VOICE"
    }
],
"loggedOnMediaTypes" :
[
    "VOICE",
    "CALLBACK"
],
"presenceState" : "AWAY",
"routingState" : "UNAVAILABLE",
"routingStateReasonKey" : 0
}
}
}

```

4.3.2.3. OnUserHandlingStateEvent

Description: event triggered when there is a change on the handling state for a user (e.g. Contact is pending/connected). It shows all the contacts the user is currently handling.

| OnUserHandlingStateEvent Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserHandlingStateEvent Data Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of agent for which handling state event has been reported. |
| agentKey | Integer | Key of agent for which handling state event has been reported. |
| handlingStates | List | List of Handling State objects for each call on which the agent is involved. See definition of HandlingState object. |

| HandlingState Object | | |
|------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact. |
| handlingState | Integer | Handling state of the contact. See definition of possible values at HandlingStates. |
| handlingStateReasonKey | Integer | Key of reason associated to the handling state. |
| primary | Boolean | Identifies if this is the primary contact. |
| mediaType | String | Media type related to the contact. |

Message Example:

```

//OnUserHandlingStateEvent Object
{

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

"type" : "EVENT",
"data" : {
  "realm" : "PRESENCE",
  "type" : "USER_HANDLING_STATE",
  "data" :
  {
    "agentId" : "100002",
    "agentKey" : 4,
    "handlingStates" :
    [
      {
        "uniqueCallId" : "3567890321",
        "handlingState" : "RINGING",
        "handlingStateReasonKey" : 4,
        "primary" : true,
        "mediaType" : "VOICE"
      }
    ],
  }
}

```

4.3.2.4. OnUserMediaReadyEvent

Description: event triggered when a media is ready (e.g. Telephony server is available again).

| OnUserMediaReadyEvent Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserMediaReadyEvent Data Object | | |
|-----------------------------------|----------------|----------------------------------|
| Attribute name | Attribute type | Description |
| mediaType | String | Media which is ready to be used. |

Message Example:

```

//OnUserMediaReadyEventObject
{
  "type" : "EVENT",
  "data" : {
    "realm" : "PRESENCE",
    "type" : "USER_MEDIA_READY",
    "data" :
    {
      "mediaType" : "VOICE"
    }
  }
}

```

4.3.2.5. OnUserMediaNotReadyEvent

Description: event triggered when a media is not ready (e.g. Telephony server not available/lost connection).

| OnUserMediaNotReadyEvent Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUserMediaNotReadyEvent Data Object | | |
|--------------------------------------|----------------|--------------------------------------|
| Attribute name | Attribute type | Description |
| mediaType | String | Media which is not ready to be used. |

Message Example:

```
//OnUserMediaNotReadyEventObject
{
  "type" : "EVENT",
  "data" : {
    "realm" : "PRESENCE",
    "type" : "USER_MEDIA_NOTREADY",
    "data" :
    {
      "mediaType" : "VOICE"
    }
  }
}
```

4.3.2.6. OnServerConnected

Description: event triggered when connection to Presence server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
//OnServerConnected Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "PRESENCE",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : "localhost"
    }
  }
}
```

4.3.2.7. OnServerDisconnected

Description: event triggered when connection to Presence server is lost.

| OnServerDisconnectedEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnected Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "PRESENCE",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : "localhost"
    }
  }
}
```

4.4. Routing

4.4.1. Routing Commands

In general the response to the Routing Commands has the following format:

| RoutingCommands Response Object | | |
|---------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

| | | |
|---------------------|--------|--|
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.4.1.1. QueryCall

Description: request to query an enqueued call on the Routing Server..

URL: POST /restsdk/webapi/routing/querycall

| QueryCall Request Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact to be enqueued. |

Message Example:

```
//Enqueue Request Object
{
  "uniqueCallId" : "1491539316351272"
}
```

| QueryCall Response Object | | |
|---------------------------|--------------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| routingCall | RoutingCall Object | Data about the call being routed. |

| RoutingCall Response Object | | |
|--------------------------------|---------------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the call. |
| description | String | Description of the call. |
| contactData | Contact Data Object | List of contact data. |
| mediaType | String | Type of the media. See definition of possible values at MediaType |
| queueKey | Integer | Key of the queue. |
| assignAgentKey | Integer | Key of the agent to which the call was assigned. |
| priority | Integer | Call priority |
| reserveAgentKey | Integer | Key of the agent to which the call is reserver. |
| reserveAgentMaximumTime | Integer | Maximum time the call shall remain reserved to an agent. |
| state | String | Call state. See definition of possible values at SBRCallState |

Message Example:

```
//QueryCallResponse Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO ERROR",
  "routingCall": {
    "uniqueCallId": "9121540480019672",
    "description": "General Call",
  }
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "contactData": [{
      "key": "HPPCSuppInfoAddr",
      "value": "http://localhost:8080"
    }],
    "mediaType": "VOICE",
    "queueKey": 1,
    "assignAgentKey": 0,
    "priority": 20,
    "reserveAgentKey": 0,
    "reserveAgentMaximumTime": 0,
    "state": "QUEUED"
  }
}

```

4.4.1.2. UpdateCall

Description: request to update an enqueued call. Only the following properties can be updated: description, contact data, queueKey and priority.

Note: If the contact is updated via an UpdateCall request and the queueKey attribute is omitted, the contact remains on queueKey: 4. The same is valid if the UpdateCall request is sent with attribute "queueKey": 4. On the other hand, if a different queueKey is sent on UpdateCall request, for example "queueKey": 10, OSCC will enqueue it to queueKey: 10.

URL: POST /restsdk/webapi/routing/updatecall

| UpdateCall Request Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact to be enqueued. |
| description | String | Description for the enqueue command |
| contactData | List | List of contact data which are being associated to the contact |
| queueKey | Integer | Key of the queue involved in the contact |
| priority | Integer | Priority associated to the contact |

Message Example:

```

//Enqueue Request Object
{
  "uniqueCallId" : "1491539316351272",
  "description" : "Enqueue to queue Sales",
  "contactData" : [{
    "key" : "customer",
    "value" : "mss"
  }],
  {
    "key" : "transaction",
    "value" : "sales"
  }],
  "queueKey" : 7,
  "priority" : 1
}

```

4.4.1.3. GetQueueData

Description: request to query queue data.

Note: It requires logon and Authorization header with session token.
 URL: GET /restsdk/webapi/routing/getQueueData

| GetQueueData Request Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| queueKey | Integer | Key of the queue for each to return the data. |

Request Example:
 //GetQueueDataRequest Object

```
{
  "queueKey" : 2
}
```

| GetQueueData Response Object | | |
|------------------------------|------------------|--|
| Attribute name | Attribute type | Description |
| numberOfQueuedCalls | Integer | Number of calls waiting in this queue. |
| queuedCalls | List of Call Ids | List of call ids of the calls waiting in the queue. |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Response Example:
 //GetQueueDataResponse Object

```
{
  "numberOfQueuedCalls" : 5,
  "queuedCalls":
  [
    "2261677699281812",
    "2261677695756788"
  ]
}
```

4.4.1.4. EnqueueCall

Description: Enqueues a call to the Routing Server to be assigned to a user.
 URL: POST /restsdk/webapi/routing/enqueuecall

| EnqueueCall Request Object | | |
|----------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact to be enqueued. |
| description | String | Description for the enqueue command |
| contactData | List | List of contact data which are being associated to the contact |
| mediaType | String | Media type related to the contact |
| queueKey | Integer | Key of the queue involved in the contact |
| priority | Integer | Priority associated to the contact |
| reserveAgentKey | Integer | Agent to be reserved (0 if no agent reservation) |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|--------------------------------|---------|--|
| reserveAgentMaximumTime | Integer | Maximum time the agent shall be reserved (in seconds) |
| automatedTransfer | Boolean | Indicates if the call has been automatically transferred. Used for statistical purposes. |
| source | String | Originator of the call to be enqueued |
| destination | String | Identification of a destination which corresponds to a queue in the Contact Center. |
| queueProcessingDesired | Boolean | Determines if the Queue Processing of the new queue executed (see Note 1) |

Message Example:

```
//EnqueueCall Request Object
{
  "uniqueCallId" : "1491539316351272",
  "description" : "Enqueue to queue Sales",
  "contactData" : [{
    "key" : "customer",
    "value" : "mss"
  }],
  {
    "key" : "transaction",
    "value" : "sales"
  }],
  "mediaType" : "VOICE",
  "queueKey" : 7,
  "priority" : 1,
  "reserveAgentKey" : 0,
  "reserveAgentMaximumTime" : 0,
  "automatedTransfer" : true,
  "source" : "554180911597",
  "destination" : "554181015100"
  "queueProcessingDesired" : true
}
```

Note 1: the queueProcessingDesired attribute is optional. If set to true, the Queue Processing of the new queue will be executed if one of the following conditions are met:

1. The source queue has no Queue Processing configured;
2. The source queue has Queue Processing configured but its treatment is completed/finished before the EnqueueCall request is sent.

Example:

OSCC configured with two Voice Queues, Queue A (source queue) and Queue B (destination queue). A call is routed and enqueued to Queue A, which has no Queue Processing configured (None). A REST SDK application is used to enqueue the call to Queue B, which has Queue Processing configured. If the EnqueueCall request is sent with queueProcessingDesired set to true, the Queue Processing of Queue B will be started as soon as the call is enqueued and no Available agent is found to assign the call.

4.4.1.5. DequeueCall

Description: Dequeues a call from a queue.

URL: POST /restsdk/webapi/routing/dequeuecall

| DequeueCall Request Object | | |
|----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact to be dequeued. |
| abandonedCall | Boolean | Indicates if the call shall be indicated as abandoned |

Message Example:

```
//DequeueCall Request Object
{
  "uniqueCallId" : "1491539316351272",
  "abandonedCall" : true
}
```

4.4.1.6. AddContactData

Description: request to add a contact data to an enqueued contact.

URL: POST /restsdk/webapi/routing/addcontactdata

| AddContactData Request Object | | |
|-------------------------------|----------------|----------------------------|
| Attribute name | Attribute type | Description |
| key | String | Key of the contact data. |
| value | String | Value of the contact data. |
| uniqueCallId | String | Call ID of the contact. |

Message Example:

```
//AddContactData Request Object
{
  "key" : "customer",
  "value" : "mss",
  "uniqueCallId" : "1491539316351272",
}
```

4.4.1.7. RemoveContactData

Description: request to remove a contact data (by key) from an enqueued contact.

URL: POST /restsdk/webapi/routing/removecontactdata

| RemoveContactData Request Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| key | String | Key of the contact data to be removed. |
| uniqueCallId | String | Call ID of the contact. |

Message Example:

```
//RemoveContactData Request Object
{
  "key" : "customer",
  "uniqueCallId" : "1491539316351272"
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.4.1.8. ClearContactData

Description: request to clear (remove all) contact data from an enqueued contact.
URL: POST /restsdk/webapi/routing/clearcontactdata

| ClearContactData Request Object | | |
|---------------------------------|----------------|-------------------------|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact. |

Message Example:

```
//ClearContactData Request Object
{
  "uniqueCallId" : "1491539316351272"
}
```

4.4.1.9. StartListenForEvents

Description: request to start listening for Routing control events.
Note: It requires Admin logon and Authorization header with session token. No HTTP body is required to be posted.

| StartListenForEvents Response Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//StartListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.4.1.10. StopListenForEvents

Description: request to stop listening for Routing control events.
Note: It requires logon and Authorization header with session token. No HTTP body is required to be posted.
URL: POST /restsdk/webapi/routing/stoplisterforevents

| StopListenForEvents Response Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

Message Example:

```
//StopListenForEvents Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR"
}
```

4.4.2. Routing Events

In general, Routing Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at MessageType |
| data | Object | Content of the message. See definition of this object for each event type. |

4.4.2.1. OnAssignCallEvent

Description: event triggered when a contact is assigned to an agent.

| OnAssignCallEvent Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnAssignCallEvent Data Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentExtension | String | Extension number of the agent to which the contact is being assigned. |
| agentKey | Integer | Key of the agent to which the contact is being assigned. |
| uniqueCallId | String | Call ID of the call being assigned. |
| mediaType | String | Media type related to the contact. |

Message Example:

```
//OnAssignCallEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "ASSIGN_CALL_EVENT",
    "data" :
    {
      "agentExtension" : "554181021120",
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "agentKey" : 3,
    "uniqueCallId" : "2491535069604582",
    "mediaType" : "VOICE"
  }
}
}

```

4.4.2.2. OnUnassignCallEvent

Description: event triggered when a contact is unassigned to an agent (e.g. external caller abandoned call).

| OnUnassignCallEvent Object | | |
|----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnUnassignCallEvent Data Object | | |
|---------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent from which the contact is being unassigned. |
| uniqueCallId | String | Call ID of the call being unassigned. |
| mediaType | String | Media type related to the contact. |

Message Example:

```

//OnUnassignCallEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "UNASSIGN_CALL_EVENT",
    "data" :
    {
      "agentKey" : 3,
      "uniqueCallId" : "2491535069604582",
      "mediaType" : "VOICE"
    }
  }
}
}

```

4.4.2.3. OnEnqueueCallEvent

Description: event triggered when a contact is enqueued.

| OnEnqueueCallEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |

| | | |
|-------------|--------|---|
| data | Object | Content of the event. See following data Object definition. |
|-------------|--------|---|

| OnEnqueueCallEvent Data Object | | |
|---------------------------------------|-----------------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the call being dequeued. |
| description | String | Description of the contact. |
| priority | Integer | Priority associated to the contact. |
| queueKey | Integer | Key of the queue associated to this contact. |
| mediaType | String | Media type related to the contact. |

Message Example:

```
//OnEnqueueCallEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "ENQUEUE_CALL_EVENT",
    "data" :
    {
      "uniqueCallId" : "2491535069604582",
      "description" : "General Call",
      "priority" : 20,
      "queueKey" : 1
      "mediaType" : "VOICE"
    }
  }
}
```

4.4.2.4. OnDequeueCallEvent

Description: event triggered when a contact is dequeued.

| OnDequeueCallEvent Object | | |
|----------------------------------|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDequeueCallEvent Data Object | | |
|---------------------------------------|-----------------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the call being dequeued. |
| description | String | Description of the contact. |
| priority | Integer | Priority associated to the contact. |
| queueKey | Integer | Key of the queue associated to this contact. |
| dequeueReason | String | Reason by which the contact has been dequeued. See definition of possible values at DequeueReasons. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|------------------|--------|---|
| mediaType | String | Media type related to the contact. See definition of possible values at MediaType |
|------------------|--------|---|

Message Example:

```
//OnDequeueCallEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "DEQUEUE_CALL_EVENT",
    "data" :
    {
      "uniqueCallId" : "2491535069604582",
      "description" : "General Call",
      "priority" : 20,
      "queueKey" : 1
      "dequeueReason" : "CALLABANDONED",
      "mediaType" : "VOICE"
    }
  }
}
```

4.4.2.5. OnRoutingUpdateInformationEvent

Description: event triggered after the call is enqueued and waiting to be assigned to an agent.

| OnRoutingUpdateInformationEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnRoutingUpdateInformationEvent Data Object | | |
|--|-----------------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID to which contact data is being associated. |
| contactData | List | List of ContactData objects which are being associated to the contact. |
| description | String | Description of the contact. |
| priority | Integer | Priority associated to the contact. |
| queueKey | Integer | Key of the queue involved in the contact. |
| mediaType | String | Media type related to the contact. |

| ContactData Object | | |
|---------------------------|-----------------------|--|
| Attribute name | Attribute type | Description |
| key | String | Label which identifies the contact data. |

| | | |
|--------------|--------|------------------------------|
| value | String | Content of the contact data. |
|--------------|--------|------------------------------|

Message Example:

```
//OnRoutingUpdateInformationEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "ROUTING_INFORMATION_UPDATED_EVENT",
    "data" :
    {
      "uniqueCallId" : "2491535069604582",
      "contactData" :
      [
        {
          "key" : "key0",
          "value" : "value0"
        },
        {
          "key" : "__HPPC_SuppInfoAddress",
          "value" : "http://localhost:8080"
        }
      ]
      "description" : "General Call",
      "priority" : 20,
      "queueKey" : 1
      "mediaType" : "VOICE"
    }
  }
}
```

4.4.2.6. OnTimeoutCallEvent

Description: event triggered when a contact times out (e.g. no agent is available to handle the call).

| OnTimeoutCallEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnTimeoutCallEvent Data Object | | |
|--------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the call which has been timed out. |
| telephoneNumber | String | Extension number of where the call has been transferred to (the time out extension). |
| mediaType | String | Media type corresponding to the event. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

Message Example:

```
//OnTimeoutCallEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "TIMEOUT_CALL_EVENT",
    "data" :
    {
      "uniqueCallId" : "2491535069604582",
      "telephoneNumber" : "1234",
      "mediaType" : "VOICE"
    }
  }
}
```

4.4.2.7. OnServerConnected

Description: event triggered when connection to Routing server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```
//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : " 6002@10.80.2.206"
    }
  }
}
```

4.4.2.8. OnServerDisconnected

Description: event triggered when connection to Routing server is lost.

| OnServerDisconnectedEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "ROUTING",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : " 6002@10.80.2.206"
    }
  }
}
```

4.5. Telephony

4.5.1. Telephony Commands

In general the response to the Telephony Commands has the following format:

| PresenceCommands Response Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.5.1.1. Logon

Description: request to logon an agent on Voice media.

URL: POST /restsdk/webapi/v2/telephony/logon

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| Logon Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent which shall be logged on. |
| extension | String | Extension number which shall be associated to the agent. |

Message Example:

```
//Logon Object
{
  "agentKey" : 3,
  "extension" : "554181015002"
}
```

4.5.1.2. Logoff

Description: request to logoff an agent from Voice media.

URL: POST /restsdk/webapi/v2/telephony/logoff

| Logoff Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | String | Key of the agent which shall be logged off. |

Message Example:

```
//Logoff Object
{
  "agentKey" : 3
}
```

4.5.1.3. Dial

Description: request to dial a number.

URL: POST /restsdk/webapi/telephony/dial

| Dial Request Object | | |
|------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the call originator. |
| to | String | Extension number of the call destination. This is the number to be dialed. |
| numberToDisplay | String | Number to be displayed to the call destination. |
| nameToDisplay | String | Name to be displayed to the call destination. |

Message Example:

```
//Dial Object
{
  "from" : "554181015002",
  "to" : "0498972231466",
  "numberToDisplay" : "554181015002",
  "nameToDisplay" : "Agent 1"
},
```

4.5.1.4. Answer

Description: request to answer a phone call on the extension.

URL: POST /restsdk/webapi/telephony/answer

| Answer Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number on which the call shall be answered. |

Message Example:

```
//Answer Object
{
  "from" : "554181015002"
},
```

4.5.1.5. Disconnect

Description: request to disconnect the extension from the active call.

URL: POST /restsdk/webapi/telephony/disconnect

| Disconnect Request Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number for which the call shall be disconnected. |
| workflowDisconnected | Boolean | Indicates if the call was disconnected via workflow. Used for statistical purposes. |

Message Example:

```
//Disconnect Object
{
  "from" : "554181015002",
  "workflowDisconnected" : false
},
```

4.5.1.6. Consult

Description: request to consult another extension.

URL: POST /restsdk/webapi/telephony/consult

| Consult Request Object | | |
|------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the consulting party. |
| to | String | Extension number of the consulted party. |
| uniqueCallId | String | Call ID of the call leg to be put on consultation hold. |

Message Example:

```
//Consult Object
{
  "from" : "554181015002",
  "to" : "554181015003",
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
"uniqueCallId" : "1491539316351272"  
},
```

4.5.1.7. Hold

Description: request to hold a call.

URL: POST /restsdk/webapi/telephony/hold

| Hold Request Object | | |
|---------------------|----------------|--|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the holding party. |
| uniqueCallId | String | Call ID of the call leg to be put on hold. |

Message Example:

```
//Hold Object  
{  
  "from" : "554181015002",           //this is the holding party.  
  "uniqueCallId" : "1491539316351272" //Call Id to be held.  
},
```

4.5.1.8. Retrieve

Description: request to retrieve a held call.

URL: POST /restsdk/webapi/telephony/retrieve

| Retrieve Request Object | | |
|-------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the holding party. |
| uniqueCallId | String | Call ID of the call leg to be retrieved. |

Message Example:

```
//Retrieve Object  
{  
  "from" : "554181015002",  
  "uniqueCallId" : "1491539316351272"  
},
```

4.5.1.9. Reconnect

Description: request to reconnect a held call, when consulting another extension.

URL: POST /restsdk/webapi/telephony/reconnect

| Reconnect Request Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the consulting party. |
| uniqueCallId | String | Call ID of the call leg which is on consultation hold and shall be reconnected. |

Message Example:

```
//Reconnect Object
{
  "from" : "554181015002",
  "uniqueCallId" : "1491539316351272"
},
```

4.5.1.10. Conference

Description: request to create a conference.

URL: POST /restsdk/webapi/telephony/conference

| Conference Request Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the consulting party. |
| uniqueCallId | String | Call ID of the call leg which on consultation hold. |

Message Example:

```
//Conference Object
{
  "from" : "554181015002",
  "uniqueCallId" : "1491539316351272"
},
```

4.5.1.11. Transfer

Description: request to transfer a call, after a consult.

URL: POST /restsdk/webapi/telephony/transfer

| Transfer Request Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the consulting party. |
| uniqueCallId | String | Call ID of the call leg which on consultation hold. |

Message Example:

```
//Transfer Object
{
  "from" : "554181015002",
  "uniqueCallId" : "1491539316351272"
}
```

4.5.1.12. SingleStepTransfer

Description: request to perform a single step transfer.

URL: POST /restsdk/webapi/telephony/singlesteptransfer

| SingleStepTransfer Request Object | | |
|-----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the transferring party. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-------------------------|---------|---|
| to | String | Extension number of the destination of the transfer. |
| uniqueCallId | String | Call ID of the active call. |
| workflowTransfer | Boolean | Indicates if the call was transferred via workflow. Used for statistical purposes. |
| networkTransfer | Boolean | Indicates if the call will be transferred from Desktop (ONS) to the Preferred Device (OND). |

Message Example:

```
//SingleStepTransfer Object
{
  "from" : "554181015002",
  "to" : "554181015003",
  "uniqueCallId" : "1491539316351272",
  "workflowTransfer" : false,
  "networkTransfer" : true
}
```

4.5.1.13. TransferToVoiceMail

Description: request to transfer to voice mail.

URL: POST /restsdk/webapi/telephony/transfertovoiceemail

| TransferToVoiceMail Request Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the transferring party. |
| to | String | Extension number of the destination of the transfer. |
| uniqueCallId | String | Call ID of the active call. |

Message Example:

```
//TransferToVoiceMail Object
{
  "from" : "554181015002",
  "to" : "554181015003",
  "uniqueCallId" : "1491539316351272"
}
```

4.5.1.14. Divert

Description: The Divert method transfers a call from a queue to a user's extension. To do this, they must pass the extension to which they want to divert the call.

URL: POST /restsdk/webapi/telephony/divert

| Divert Request Object | | |
|-----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| from | String | Extension number of the ringing party |
| to | String | Extension number of the destination of the divert. |
| uniqueCallId | String | Call ID of the active call. |

Message Example:

```
//Divert Request Object
{
  "from" : "554181015002",
  "to" : "554181015003",
  "uniqueCallId" : "1491539316351272",
}
```

4.5.1.15. SetUserPreferredDevice

Description: request to set the preferred device for an extension.

URL: POST /restsdk/webapi/telephony/setuserpreferreddevice

| SetUserPreferredDevice Request Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent for which Preferred Device shall be removed. |
| deviceid | String | Extension number which is associated to the agent. |
| forwardDestination | String | Destination of the Preferred Device. |

Message Example:

```
//SetUserPreferredDevice Object
{
  "agentKey" : 3,
  "deviceid" : "554181015002",
  "forwardDestination" : "554180911597"
}
```

4.5.1.16. RemoveUserPreferredDevice

Description: request to remove the preferred device from an extension.

URL: POST /restsdk/webapi/telephony/removeuserpreferreddevice

| RemoveUserPreferredDevice Request Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent for which Preferred Device shall be removed. |
| deviceid | String | Extension number which is associated to the agent. |

Message Example:

```
//RemoveUserPreferredDevice Object
{
  "agentKey" : 3,
  "deviceid" : "554181015002"
}
```

4.5.1.17. UpdateContactData

Description: request to update the contact data of a telephony contact.

URL: POST /restsdk/webapi/telephony/updatecontactdata

| UpdateContactData Request Object | | |
|----------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|---------------------|----------------------|--|
| uniqueCallId | String | Call Id of the Telephony contact for which the content shall be added. |
| contactData | List of Contact Data | The contact data to be update on a Telephony contact. |

Message Example:

```
//UpdateContactData Object
{
  "uniqueCallId": "W869020181026170830001",
  "contactData": [{
    "key": "key0",
    "value": "value0"
  }, {
    "key": "key1",
    "value": "value1"
  }]
}
```

4.5.1.18. QueryLine

Description: request to query line state.

URL: POST /restsdk/webapi/v2/telephony/queryline

| QueryLine Request Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| extension | String | Extension for which data is being queried. |

Message Example:

```
//QueryLine Request Object
{
  "extension" : "554133416000"
}
```

| QueryLine Response Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| agentId | String | Id of the agent which is associated to this extension. |
| uniqueCallId | String | Call ID which is active for this extension. |
| agentKey | Integer | Key of the agent which is associated to this extension. |
| teamKey | Integer | Key of the team to which this extension is associated. |
| firstCallId | String | First Call ID which is associated to this extension. |
| secondCallId | String | Second Call ID which is associated to this extension. |
| resourceType | String | Type of resource from Telephony realm perspective. See definition of possible values at LineResourceType. |
| status | String | Status of the extension. See definition of possible values at LineState. |
| prevStatus | String | Previous status of the extension. See definition of possible values at LineState. |
| type | String | Type of the device which corresponds to this extension. See definition of possible values at Type. |
| stateEnteredAt | String | Time at which the extension entered at the current state. |
| busUnitKey | Integer | Key of tenant to which this extension is associated. |
| associatedCallbackUserId | String | Id of the agent logged on Callback media, which is associated to this extension. |

| | | |
|----------------------------------|---------|---|
| associatedCallbackUserKey | Integer | Key of the agent logged on Callback media, which is associated to this extension. |
|----------------------------------|---------|---|

Message Example:

```
//QueryLine Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO ERROR",
  "agentId" : "1000",
  "uniqueCallId" : "5701539803885842",
  "agentKey" : 4,
  "teamKey" : 1,
  "firstCallId" : "FF00010000000BD8A8D5B69E36901",
  "secondCallId" : "FF00010000000BD8A8D5B69E45634",
  "resourceType" : "AGENTEXTENSION",
  "status" : "CONSULTING",
  "prevStatus" : "RINGING",
  "type" : "UNKNOWN_TYPE",
  "stateEnteredAt" : "2018-10-17T19:18:10Z",
  "busUnitKey" : "1",
}
```

4.5.1.19. QueryCall

Description: request to query call state.

URL: POST /restsdk/webapi/telephony/querycall

| QueryCall Request Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID for which data is being queried. |

Message Example:

```
//QueryCall Object
{
  "uniqueCallId" : "5701539803885842"
}
```

| QueryCall Response Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| contactType | String | Type of the contact. See definition of possible values at ContactType. |
| type | String | Type of the call. See definition of possible values at CallType. |
| state | String | State of the call. See definition of possible values at CallState. |
| origDNIS | String | Original destination number. |
| origQueueDNIS | String | Extension number of the original queue. |
| origANI | String | Extension number of initial call originator. |
| routingANI | String | ANI which was used for routing. |
| routingDNIS | String | DNIS which was used for routing. |
| acdGroupNumber | String | Group number/Virtual group number. |
| origACDQ | String | Queue to which the call has been originally queued. |
| origCallId | String | Initial Call ID. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|---------------------------|---------|--|
| origCallingParty | Object | Data about the call which originated the call. See the definition of the Party object. |
| origAnsweringParty | Object | Data about the party which originally answered the call. See the definition of the Party object. |
| origAnsweringAgent | Object | Data about the agent which originally answered the call. See the definition of the Party object. |
| initiator | Object | Data about the party which has just initiated voice service. See the definition of the Party object. |
| targetParty | Object | Data about the party which is the target of the call. See the definition of the Party object. |
| numIvrVisits | Integer | Number of times the call went through the IVR. |
| strFrom | String | Extension number which was reported on Screen Pop API. |
| divertDestination | String | Extension number of the divert destination. |
| busUnitKey | Integer | Key of tenant for which the call is being handled. |
| queueKey | Integer | Key of the queue the contact has been routed to. |

Message Example:

```
//QueryCallResponse Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO ERROR",
  "contactType" : "ROUTED_VOICE",
  "type" : "INT2ACD",
  "state" : "CONNECTED",
  "origDNIS" : "554181015100",
  "origQueueDNIS" : "554181015001",
  "origANI" : "554180911597",
  "routingANI" : "554180911597",
  "routingDNIS" : "554181015100",
  "acdGroupNumber" : "554181015001",
  "origACDQ" : "554181015001",
  "origCallId" : "0300010000000000BD8A8D5B69E36901",
  "origCallingParty" :
  {
    "agentKey": 0,
    "device": "554180911597",
    "type": "EXTERNAL"
  },
  "origAnsweringParty" :
  {
    "agentKey": 3,
    "device": "554181015004",
    "type": "AGENT"
  },
  "origAnsweringAgent" :
  {
    "agentKey": 3,
    "device": "554181015004",
    "type": "AGENT"
  },
  "initiator" :
  {
```

```

    "agentKey": 0,
    "device": "554180911597",
    "type": "EXTERNAL"
  },
  "targetParty" :
  {
    "agentKey": 0,
    "device": "554181015100",
    "type": "UNKNOWN"
  },
  "numIvrVisits" : 1
  "strFrom" : "",
  "divertDestination" : "554181015004",
  "busUnitKey" : 1,

  "strFrom" : "",
  "divertDestination" : "554181015004",
  "busUnitKey" : 1,
  "queueKey" : 1
}

```

4.5.1.20. StartListenForEvents

Description: request to start listening for Telephony server events. The resource is the extension number.

Note: if '*' is passed, all the subscribers configured for the tenant in the OpenScape Contact Center will be monitored.

URL: POST /restsdk/webapi/telephony/startlistenforevents

| StartListenForEvents Request Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Extension number of the station to be monitored. Wildcard "*" indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```

//StartListenForEvents Request Object
{
  "resource" : "554181015002"
}

```

4.5.1.21. StopListenForEvents

Description: request to stop listening for Telephony server events. The resource is the extension number.

URL: POST /restsdk/webapi/telephony/stoplissenforevents

| StopListenForEvents Request Object | | |
|------------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-----------------|--------|--|
| resource | String | Extension number of the station to be monitored. Wildcard "*" indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |
|-----------------|--------|--|

Message Example:

```
//StopListenForEvents Request Object  
{  
  "resource" : "554181015002"  
}
```

4.5.2. Telephony Events

In general, Telephony Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at <code>MessageType</code> |
| data | Object | Content of the message. See definition of this object for each event type. |

4.5.2.1. OnDeliveredEvent

Description: event triggered when a call is delivered.

| OnDeliveredEvent Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at <code>Realm</code> . |
| type | String | Identification of the event. See definition of possible values at <code>EventType</code> |
| data | Object | Content of the event. See following data Object definition. |

| OnDeliveredEvent Data Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at <code>MediaType</code> . |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at <code>LCSType</code> . |
| contactType | String | Type of contact. See definition See definition of possible values at <code>ContactType</code> . |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at <code>EventCause</code> . |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| deliveredToParty | Object | Data about the party which is being alerted. See the definition of <code>Party Object</code> . |
| fromParty | Object | Data about current source party. See the definition of <code>Party Object</code> . |
| toParty | Object | Data about current destination party. See the definition of <code>Party Object</code> . |
| heldParty | Object | Data about current held party. See the definition of <code>Party Object</code> . |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|----------------------|--------|--|
| redirectParty | Object | Data about the party which has last forwarded the call. See the definition of Party Object. |
| sipCallId | String | SIP Call Identifier from the original call. Need communication platform configuration (only OpenScape Voice). See the note below for more information. |

Note: You must enable the "Enable Private Data Presentation - V8" parameter on the communication platform (OpenScape Voice).

Message Example:

```
//OnDeliveredEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "DELIVERED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554183021932",
      "uniqueCallId": "2171710349467052",
      "requeueCount": 0,
      "lcsType": "ALERTING",
      "contactType": "ROUTED_VOICE",
      "normalCause": "DISTRIBUTED",
      "originalFrom": "554181021779",
      "originalTo": "554183022930",
      "deliveredToParty": {
        "agentKey": 50,
        "device": "554183021932",
        "type": "AGENT"
      },
      "fromParty": {
        "agentKey": 0,
        "device": "554181021779",
        "type": "EXTERNAL"
      },
      "toParty": {
        "agentKey": 0,
        "device": "554183022930",
        "type": "AGENT"
      },
      "heldParty": {
        "agentKey": 0,
        "device": "",
        "type": "UNKNOWN"
      },
      "redirectParty": {
        "agentKey": -1,
        "device": "",
        "type": "INTERNAL"
      }
    }
  }
}
```

```

    },
    "contactData": [],
    "sipCallId": "SEC11-c66ffd50-c7effd50-1-CgqLKT9Lw1J4",
  }
}
}

```

4.5.2.2. OnDisconnectedEvent

Description: event triggered when one of the call parties disconnects.

| OnDisconnectedEvent Object | | |
|----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnDisconnectedEvent Data Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been queued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| disconnectedParty | Object | Data about the party which has been disconnected. See the definition of Party Object. |
| reason | String | Reason for which the call has been disconnected. See definition of possible values at DisconnectReasons. |

Message Example:

```

//OnDisconnectedEvent Object{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "DISCONNECTED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "uniqueCallId": "1111535044018952",
    "sequenceNumber": 0,
    "lcsType": "CONNECTED",
    "contactType": "ROUTED_VOICE",
    "normalCause": "MULTIPLE_ALERTING",
    "originalFrom": "554181021119",
    "originalTo": "554181022110",
    "disconnectedParty": {
      "agentKey": 0,
      "device": "554181021119",
      "type": "AGENT"
    },
    "reason": "UNDEFINED"
  }
}

```

4.5.2.3. OnQueuedEvent

Description: event triggered when a call is queued.

| OnQueuedEvent Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnQueuedEvent Data Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| fromParty | Object | Data about current source party. See the definition of Party Object. |
| toParty | Object | Data about current destination party. See the definition of Party Object. |
| queuedParty | Object | Data about the queue party. See the definition of Party Object. |

Message Example:

```

//OnQueuedEvent Object
{
  "type" : "EVENT",

```

```

"data" :
{
  "realm" : "TELEPHONY",
  "type" : "QUEUED_EVENT",
  "data" :
  {
    "mediaType": "VOICE",
    "resource": "554181021110",
    "uniqueCallId": "3341535057392202",
    "sequenceNumber": 0,
    "lcsType": "QUEUED",
    "contactType": "ROUTED_VOICE",
    "normalCause": "TIMEOUT",
    "originalFrom": "554181021119",
    "originalTo": "554181022110",
    "fromParty": {
      "agentKey": -1,
      "device": "",
      "type": "UNKNOWN"
    },
    "toParty": {
      "agentKey": -1,
      "device": "",
      "type": "UNKNOWN"
    },
    "queuedParty": {
      "agentKey": 0,
      "device": "554181021110",
      "type": "QUEUE"
    }
  }
}
}

```

4.5.2.4. OnEstablishedEvent

Description: event triggered when a call is answered.

| OnQueuedEvent Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnQueuedEvent Data Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-----------------------|---------|---|
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been queued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| fromParty | Object | Data about current source party. See the definition of Party Object. |
| toParty | Object | Data about current destination party. See the definition of Party Object. |
| redirectParty | Object | Data about the party which has last forwarded the call. See the definition of Party Object. |

Message Example:

```
//OnEstablishedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "ESTABLISHED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "1081535045429592",
      "sequenceNumber": 0,
      "lcsType": "CONNECTED",
      "contactType": "ROUTED_VOICE",
      "normalCause": "INVALID_NUMBER_FORMAT",
      "originalFrom": "554181021119",
      "originalTo": "554181022110",
      "fromParty": {
        "agentKey": 0,
        "device": "554181021119",
        "type": "AGENT"
      },
      "toParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      },
      "redirectParty": {
        "agentKey": -1,
        "device": "",
        "type": "INTERNAL"
      }
    }
  }
}
```

```

}
}

```

4.5.2.5. OnDivertedEvent

Description: event triggered when a call is diverted.

| OnDivertedEvent Object | | |
|------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnDivertedEvent Data Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| divertedParty | Object | Data about the party which has been diverted to a new destination. See the definition of Party Object. |
| divertingParty | Object | Data about the party has diverted the call to a new destination. See the definition of Party Object. |
| destinationParty | Object | Data about the party to which the call has been diverted. See the definition of Party Object. |

Message Example:

```

//OnDivertedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "DIVERTED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021110",
      "uniqueCallId": "5261535055499272",

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

"sequenceNumber": 0,
"lcsType": "NULL",
"contactType": "ROUTED_VOICE",
"normalCause": "INVALID_NUMBER_FORMAT",
"originalFrom": "554181021119",
"originalTo": "554181022110",
"divertedParty": {
  "agentKey": 0,
  "device": "554181021119",
  "type": "AGENT"
},
"divertingParty": {
  "agentKey": 0,
  "device": "554181021110",
  "type": "RCG"
},
"destinationParty": {
  "agentKey": 3,
  "device": "554181021113",
  "type": "AGENT"
},
}
}
}
}

```

4.5.2.6. OnHeldEvent

Description: event triggered when a call is held.

| OnHeldEvent Object | | |
|--------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnHeldEvent Data Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |

| | | |
|---------------------|--------|---|
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| heldParty | Object | Data about the party which has been put on hold. See the definition of Party Object. |
| holdingParty | Object | Data about the party which has put the other party on hold. See the definition of Party Object. |

Message Example:

```
//OnHeldEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "HELD_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "2831535059550752",
      "sequenceNumber": 0,
      "lcsType": "HOLD",
      "contactType": "ROUTED_VOICE",
      "normalCause": "CSTA_SINGLE_STEP_TRANSFER",
      "originalFrom": "554181021119",
      "originalTo": "554181022110",
      "heldParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      },
      "holdingParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      }
    }
  }
}
```

4.5.2.7. OnRetrievedEvent

Description: event triggered when a held call is retrieved.

| OnRetrievedEvent Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-------------|--------|---|
| data | Object | Content of the event. See following data Object definition. |
|-------------|--------|---|

| OnRetrievedEvent Data Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been queued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| heldParty | Object | Data about the party which was on hold and has just been retrieved. See the definition of Party Object. |
| retrievingParty | Object | Data about the party which retrieved the call from hold. See the definition of Party Object. |

Message Example:

```
//OnRetrievedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "RETRIEVED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "4841535060746862",
      "sequenceNumber": 0,
      "lcsType": "CONNECTED",
      "contactType": "ROUTED_VOICE",
      "normalCause": "CSTA_SINGLE_STEP_TRANSFER",
      "originalFrom": "554181021119",
      "originalTo": "554181022110",
      "heldParty": {
        "agentKey": 0,
        "device": "554181021119",
        "type": "AGENT"
      },
      "retrievingParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      }
    }
  }
}
```

4.5.2.8. OnConferencedEvent

Description: event triggered when a conference is created.

| OnConferencedEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnConferencedEvent Data Object | | |
|--------------------------------|-----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| invitedParty | Object | Data about the party which was added to the conference call. See the definition of Party Object. |
| invitingParty | Object | Data about the party which added a new member to the conference call. See the definition of Party Object. |
| conferenceParties | List of Objects | List of the parties which are participating in the conference call. |

Message Example:

```
//OnConferencedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "CONFERENCED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "4821535053654902",
      "sequenceNumber": 0,

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-----------------------|---------|---|
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| fromParty | Object | Data about the current source party. See the definition of Party Object. |
| toParty | Object | Data about the current destination party. See the definition of Party Object. |
| failedParty | Object | Data about the party on which the call has failed. See the definition of Party Object. |

Message Example:

```
//OnFailedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "FAILED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "7631535062233862",
      "sequenceNumber": -1,
      "lcsType": "CONNECTED",
      "contactType": "DIRECT_INTERNAL_VOICE",
      "normalCause": "OVERFLOW",
      "originalFrom": "554181021113",
      "originalTo": "554181021119",
      "fromParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      },
      "toParty": {
        "agentKey": 0,
        "device": "554181021119",
        "type": "AGENT"
      },
      "failedParty": {
        "agentKey": 0,
        "device": "554181021119",

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "type": "AGENT"
  }
}
}
}

```

4.5.2.10. OnOriginatedEvent

Description: event triggered when dialing to another extension.

| OnOriginatedEvent Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnOriginatedEvent Data Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| referenceCallId | String | FUTURE – Call ID of Callback Calls. |
| fromParty | Object | Data about the current source party. See the definition of Party Object. |
| toParty | Object | Data about the current destination party. See the definition of Party Object. |

Message Example:

```

//OnOriginatedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "ORIGINATED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "4331535062940702",
      "sequenceNumber": -1,
    }
  }
}

```

```

    "lcsType": "CONNECTED",
    "contactType": "NONE",
    "normalCause": "CONSULTATION",
    "originalFrom": "554181021113",
    "originalTo": "554181021119",
    "referenceCallId": "",
    "fromParty": {
      "agentKey": 3,
      "device": "554181021113",
      "type": "AGENT"
    },
    "toParty": {
      "agentKey": 0,
      "device": "554181021119",
      "type": "AGENT"
    }
  }
}
}
}

```

4.5.2.11. OnServiceInitiatedEvent

Description: event triggered when a phone goes offhook.

| OnServiceInitiatedEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServiceInitiatedEvent Data Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| Consult | Boolean | Consultation call? |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-----------------------|--------|--|
| initiatedParty | Object | Data about the party which went offhook. See the definition of Party Object. |
|-----------------------|--------|--|

Message Example:

```
//OnServiceInitiatedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "SERVICE_INITIATED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "1341535063665572",
      "sequenceNumber": -1,
      "lcsType": "INITIATE",
      "contactType": "NONE",
      "normalCause": "CONSULTATION",
      "originalFrom": "554181021113",
      "originalTo": "",
      "consult": false,
      "initiatedParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      }
    }
  }
}
```

4.5.2.12. OnTransferredEvent

Description: event triggered when a call is transferred.

| OnTransferredEvent Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnTransferredEvent Data Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. See definition of possible values at MediaType. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |

| | | |
|-------------------------|--------|---|
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| fromParty | Object | Data about the transferring party. See the definition of Party Object. |
| toParty | Object | Data about the transferred-to party. See the definition of Party Object. |
| transferredParty | Object | Data about the transferred party. See the definition of Party Object. |
| redirectParty | Object | Data about the last party from which the call was forwarded. See the definition of Party Object. |

Message Example:

```
//OnTransferredEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "TRANSFERRED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "4291535065409342",
      "sequenceNumber": 0,
      "lcsType": "NULL",
      "contactType": "ROUTED_VOICE",
      "normalCause": "NETWORK_NOT_OBTAINABLE",
      "originalFrom": "554181021119",
      "originalTo": "554181022110",
      "fromParty": {
        "agentKey": 3,
        "device": "554181021113",
        "type": "AGENT"
      },
      "toParty": {
        "agentKey": 5,
        "device": "554181021114",
        "type": "AGENT"
      },
      "transferredParty": {
        "agentKey": 0,
        "device": "554181021119",
        "type": "AGENT"
      },
    },
  },
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "redirectParty": {
      "agentKey": -1,
      "device": "",
      "type": "INTERNAL"
    }
  }
}
}

```

4.5.2.13. OnNetworkReachedEvent

Description: event triggered when seizing a trunk for an external call

| OnNetworkReachedEvent Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnNetworkReachedEvent Data Object | | |
|-----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requeued. |
| lcsType | String | Local Connection State of the device. See definition of possible values at LCSType. |
| contactType | String | Type of contact. See definition See definition of possible values at ContactType. |
| normalCause | String | Cause for which a change in the device state led to the generation of the event. See definition of possible values at EventCause. |
| originalFrom | String | Extension number of the original source of this call. |
| originalTo | String | Extension number of the original destination of this call. |
| fromParty | Object | Data about the current source party. See the definition of Party Object. |
| toParty | Object | Data about the current destination party. See the definition of Party Object. |

Message Example:

```

//OnNetworkReachedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "NETWORKREACHED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",

```

```

"resource": "554180911612",
"uniqueCallId": "2491535069604582",
"sequenceNumber": -1,
"lcsType": "CONNECTED",
"contactType": "DIRECT_OUTGOING_VOICE",
"normalCause": "CSTA_SINGLE_STEP_TRANSFER",
"originalFrom": "554180911612",
"originalTo": "554181021120",
"fromParty": {
  "agentKey": 0,
  "device": "554181021120",
  "type": "EXTERNAL"
},
"toParty":{
  "agentKey": 0,
  "device": "554181021120",
  "type": "EXTERNAL"
}
}
}
}

```

4.5.2.14. OnServicesEnabled

Description: event triggered for almost all telephony actions to indicate which services are possible in that state.

| OnServiceEnabled Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServicesEnabled Data Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Extension number of device for which the event is being reported. |
| uniqueCallId | String | Call ID related to the event is being reported. |
| sequenceNumber | Integer | Number of times this contact has been requested. |
| answer | Boolean | Telephony Answer request. |
| available | Boolean | Presence Available request. |
| conference | Boolean | Telephony Conference request. |
| consult | Boolean | Telephony Consult request. |
| dial | Boolean | Telephony Dial request. |
| disconnect | Boolean | Telephony Disconnect request. |
| divert | Boolean | Telephony Divert request. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|--------------------|---------|-------------------------------|
| hold | Boolean | Telephony Hold request. |
| logoff | Boolean | Telephony Logoff request. |
| logon | Boolean | Telephony Logon request. |
| reconnect | Boolean | Telephony Reconnect request. |
| retrieve | Boolean | Telephony Retrieve request. |
| transfer | Boolean | Telephony Transfer request. |
| unavailable | Boolean | Presence Unavailable request. |
| work | Boolean | Presence Work request. |

Message Example:

```
//OnServicesEnabled Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "SERVICE_ENABLED_EVENT",
    "data" :
    {
      "mediaType": "VOICE",
      "resource": "554181021113",
      "uniqueCallId": "",
      "requeueCount": 0,
      "answer": false,
      "available": false,
      "conference": false,
      "consult": false,
      "dial": true,
      "disconnect": false,
      "divert": false,
      "hold": false,
      "logoff": true,
      "logon": false,
      "reconnect": false,
      "retrieve": false,
      "transfer": false,
      "unavailable": true,
      "work": true
    }
  }
}
```

4.5.2.15. OnServerConnectedEvent

Description: event triggered when connection to Telephony server is established.

| OnServerConnectedEvent Object | | |
|--------------------------------------|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |

| | | |
|-------------|--------|---|
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|---|-----------------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```
//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "TELEPHONY",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6001:10.81.3.116"
    }
  }
}
```

4.5.2.16. OnServerDisconnectedEvent

Description: event triggered when connection to Telephony server is lost.

| OnServerDisconnectedEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "realm" : "TELEPHONY ",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
        "serverName" : "6001:10.81.3.116"
    }
}
}

```

4.5.2.17. HotStandby_Event

Description: event to inform that the OSCC node entered the Active or Standby mode.

| HotStandby Event Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| data Object | | |
|------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | Integer | Media type for which the event is being reported. See definition of possible values at MediaType. |
| state | Integer | Hot Standby State of the OSCC node. See the definition of possible values at HotStandbyState. |

```

// HOTSTANDBY_EVENT object:
{
    "type": "EVENT",
    "data": {
        "realm" : "TELEPHONY",
        "type" : " HOTSTANDBY_EVENT ",
        "data" : {
            "mediaType": "VOICE",
            "state": "ACTIVE"
        }
    }
}

```

4.5.3. Telephony Common Objects

| Party Object |
|--------------|
|--------------|

| Attribute name | Attribute type | Description |
|-----------------|----------------|---|
| agentKey | Integer | Agent key of the party. It contains value '0' if not associated to an agent. |
| device | String | Extension number of the party. |
| type | String | Device type of the party. See definition See definition of possible values at PartyTypes. |

4.5.4. Telephony Commands (old versions)

Note: request kept for compatibility reasons. Applications should use the latest implementation of the Telephony Commands.

4.5.4.1. Logon (v1)

Description: request to logon an agent on Voice media.

URL: POST /restsdk/webapi/telephony/logon

| Logon Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent which shall be logged on. |
| extension | String | Extension number which shall be associated to the agent. |

Message Example:

```
//Logon Object
{
  "agentID" : "1000",
  "extension" : "554181015002"
}
```

4.5.4.2. Logoff (v1)

Description: request to logoff an agent from Voice media.

URL: POST /restsdk/webapi/telephony/logoff

| Logoff Request Object | | |
|-----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentId | String | Id of the agent which shall be logged off. |

Message Example:

```
//Logoff Object
{
  "agentId" : "1000"
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.5.4.3. QueryLine (v1)

Description: request to query line state.

URL: POST /restsdk/webapi/telephony/queryline

| QueryLine Request Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| extension | String | Extension for which data is being queried. |

Message Example:

```
//QueryLine Request Object
{
  "extension" : "554133416000"
}
```

| QueryLine Response Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| agentId | String | Id of the agent which is associated to this extension. |
| uniqueCallId | String | Call ID which is active for this extension. |
| agentKey | Integer | Key of the agent which is associated to this extension. |
| teamKey | Integer | Key of the team to which this extension is associated. |
| firstCallId | String | First Call ID which is associated to this extension. |
| secondCallId | String | Second Call ID which is associated to this extension. |
| resourceType | String | Type of resource from Telephony realm perspective. See definition of possible values at LineResourceType. |
| adminResourceType | String | Type of resource from Admin realm perspective. See definition of possible values at LineResourceTypes. |
| status | String | Status of the extension. See definition of possible values at LineState. |
| prevStatus | String | Previous status of the extension. See definition of possible values at LineState. |
| type | String | Type of the device which corresponds to this extension. See definition of possible values at Type. |
| stateEnteredAt | String | Time at which the extension entered at the current state. |
| busUnitKey | Integer | Key of tenant to which this extension is associated. |

Message Example:

```
//QueryLine Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO ERROR",
  "agentId" : "1000",
  "uniqueCallId" : "5701539803885842",
  "agentKey" : 4,
  "teamKey" : 1,
  "firstCallId" : "FF00010000000BD8A8D5B69E36901",
  "secondCallId" : "FF00010000000BD8A8D5B69E45634",
  "resourceType" : "AGENTEXTENSION",
  "adminResourceType" : "AGENTEXTENSION",
  "status" : "CONSULTING",
  "prevStatus" : "RINGING",
  "type" : "UNKNOWN TYPE",
  "stateEnteredAt" : "2018-10-17T19:18:10Z",
}
```

```
"busUnitKey" : "1",
}
```

4.6. Callback

4.6.1. Callback Commands

All requests require logon on Admin and an Authorization header with the session token.

In general the response to the Callback Commands has the following format:

| Callback Commands Response Object | | |
|-----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.6.1.1. Logon

Description: request to logon an agent on Callback media.

URL: POST /restsdk/webapi/callback/logon

| Logon Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent which shall be logged on. |
| extension | String | Extension number which shall be associated to the agent. |

Message Example:

```
//Logon Object
{
  "agentKey" : 5,
  "extension" : "554181015002"
}
```

4.6.1.2. Logoff

Description: request to logoff an agent from Callback media.

URL: POST /restsdk/webapi/callback/logoff

| Logoff Request Object | | |
|-----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent which shall be logged off. |

Message Example:

```
//Logoff Object
{
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
"agentKey" : 5
}
```

4.6.1.3. Accept

Description: request to accept the callback delivered to the agent.

URL: POST /restsdk/webapi/callback/accept

| Accept Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent for which callback shall be accepted. |

Message Example:

```
///Accept Object
{
  "agentKey" : 5
}
```

4.6.1.4. Complete

Description: request to complete the callback handled by the agent.

URL: POST /restsdk/webapi/callback/complete

| Complete Request Object | | |
|-------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent for which callback shall be completed. |
| successful | Boolean | Indicate if the callback has been successfully completed. |
| retryDelay | Integer | The retryDelay unit is minutes. For retryDelay = 0, the callback is set to retry now. For retryDelay >= 1, the callback is set to retry later with the specified phoneNumber. |
| retryReasonKey | Integer | Key of the reason for which the callback shall be retried. |
| phoneNumber | String | Phone number to which the callback shall be retried. |
| maxReached | Boolean | The maxReached flag is used to set callback result reason as maximum retries reached. |

Message Example:

```
//Complete Object
{
  "agentKey": 3,
  "successful": true,
  "retryDelay": 0,
  "retryReasonKey": 0,
  "phoneNumber": "554180811093",
  "maxReached": false
}
```

4.6.1.5. Create

Description: request to create a callback.

URL: POST /restsdk/webapi/callback/create

| Create Request Object | | |
|------------------------|--------------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent for which callback shall be created. |
| name | String | Name of callback to be created. |
| queueKey | Integer | Key of the queue for which the callback shall be created. |
| description | String | Text with more details about the callback; |
| priority | Integer | Priority which will be set to the created callback; |
| reserveAgentKey | Integer | Key of the agent to which the callback shall be reserved. If no reservation to agent, value shall be set to 0. |
| schedule | Schedule Object | The start and end of the time interval in which the callback shall be executed and the phone number to be dialed. |
| contactData | ContactData Object | List of key value pairs for attributes of this callback. |

Message Example:

```
//Create Object
{
  "agentKey": 3,
  "name": "sdkname",
  "queueKey": 3,
  "description": "sdkdesc",
  "priority": 20,
  "reserveAgentKey": 0,
  "schedule": [{
    "startTime": "2019-01-25T10:04:42-02:00",
    "endTime": "2019-01-25T12:37:59-02:00",
    "phoneNumber": "551138172345"
  }],
  "contactData": [{
    "key": "key0",
    "value": "value0"
  }, {
    "key": "key1",
    "value": "value1"
  }]
}
```

4.6.1.6. Delete

Description: request to delete the callback which was delivered to an agent.

URL: POST /restsdk/webapi/callback/delete

| Delete Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent for which the callback shall be deleted. |
| reasonKey | Integer | Key of the reason to delete the callback. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

Message Example:

```
//Delete Object
{
  "agentKey": 3,
  "reasonKey": 6
}
```

4.6.1.7. QueryNewCallbacks

Description: request to query new callbacks (i.e. Callbacks with status = 0 on Callback Server). Since this request is asynchronous, the query result comes as an event of type NEW_CALLBACKS_LIST_EVENT. It's required that the application is listening on Callback events, on any agentKey (or all keys with wildcard *).

URL: POST /restsdk/webapi/callback/querynewcallbacks

| QueryNewCallbacks Request Object | | |
|----------------------------------|------------------|---|
| Attribute name | Attribute type | Description |
| origin | String | Determines the type of callback to be queried. See definition of possible values at CallbackOrigin. |
| fromTime | String | Begin of the time interval for the query. |
| toTime | String | End of the time interval for the query. |
| queueKeys | List of Integers | List of keys of the queues for which the callback shall be queried. |

Message Example:

```
//QueryNewCallbacks Object
{
  "origin": "ORIGIN_DESKTOP",
  "fromTime": "2019-01-25T10:05:42-02:00",
  "toTime": "2019-01-25T12:37:59-02:00",
  "queueKeys": [1, 3, 5]
}
```

4.6.1.8. Update

Description: request to update a callback. It's possible to update an active callback, or a callback which was not delivered to an agent yet (it's still being processed on database). If an active callback is being updated, the start time of the first active schedule cannot be changed.

URL: POST /restsdk/webapi/callback/update

| Update Request Object | | |
|------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent for which callback shall be updated. |
| uniqueCallId | String | Call ID of the callback to be updated. |
| name | String | Name of the callback to be updated. |
| queueKey | Integer | Key of the queue for which the callback shall be updated. |
| description | String | Text with more details about the callback; |
| priority | Integer | Priority which will be set to the created callback; |
| reserveAgentKey | Integer | Key of the agent to which the callback shall be reserved. If no reservation to agent, value shall be set to 0. |

| | | |
|-------------------------|--------------------|---|
| reserveAgentTime | Integer | Time in seconds for which the agent will be reserved for the callback. |
| schedule | Schedule Object | The start and end of the time interval in which the callback shall be executed and the phone number to be dialed. |
| contactData | ContactData Object | List of key value pairs for attributes of this callback. |
| retryTime | String | Time when the callback shall be retried. |
| reasonKey | Integer | Key of the reason for which the callback shall be retried. |
| status | String | Status of the callback. See definition of possible values at CallbackStatus. |

Message Example:

```
//Update Object
{
  "agentKey": 3,
  "uniqueCallId": "C7041543247160029"
  "name": "sdkname",
  "queueKey": 3,
  "description": "sdkdesc",
  "priority": 20,
  "reserveAgentKey": 0,
  "reserveAgentTime": 0,
  "schedule": [{
    "startTime": "2019-01-25T10:04:42-02:00",
    "endTime": "2019-01-25T12:37:59-02:00",
    "phoneNumber": "551138172345"
  }],
  "contactData": [{
    "key": "key0",
    "value": "value0"
  }, {
    "key": "key1",
    "value": "value1"
  }]
  "retryTime": "2019-01-25T17:04:42-02:00",
  "reasonKey": 12,
  "status": "CALLBACKSTATUS_NEW"
}
```

4.6.1.9. StartListenForEvents

Description: request to start listening for Callback server events. The resource is the user key.

Note: if '*' is passed, all the subscribers configured for the tenant in the OpenScape Contact Center will be monitored.

URL: POST /restsdk/webapi/callback/startlistenforevents

| StartListenForEvents Request Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard '*' indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

Message Example:

```
//StartListenForEvents Request Object
{
  "resource" : "3"
}
```

4.6.1.10. StopListenForEvents

Description: request to stop listening for Callback server events. The resource is the user key.

URL: POST /restsdk/webapi/callback/stoplistenforevents

| StopListenForEvents Request Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard "*" indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScope Contact Center. |

Message Example:

```
//StopListenForEvents Request Object
{
  "resource" : "3"
}
```

4.6.2. Callback Events

In general, Callback Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at MessageType |
| data | Object | Content of the message. See definition of this object for each event type. |

4.6.2.1. OnDeliveredCallbackEvent

Description: event triggered when a callback is delivered to an agent.

| OnDeliveredCallbackEvent Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnDeliveredCallbackEvent Data Object | | |
|--------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |

| | | |
|---------------------|--------------------|---|
| resource | String | Key of the agent to which the callback was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| name | String | Name of the callback. |
| description | String | Description of the callback. |
| schedules | Schedules Object | List of schedules for that agent. |
| contactData | ContactData Object | List of contact data key values. |

Message Example:

```
// OnDeliveredCallbackEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "CALLBACK",
    "type": "DELIVERED_CALLBACK_EVENT",
    "data": {
      "mediaType": "CALLBACK",
      "resource": "3",
      "uniqueCallId": "C8511543249806039",
      "requeueCount": 0,
      "name": "sdkname",
      "description": "sdkdesc",
      "schedules": [{
        "startTime": "2018-11-26T15:55:57Z",
        "endTime": "2018-11-26T18:21:43Z",
        "phoneNumber": "1119",
        "status": "ACTIVE"
      }],
      "contactData": [{
        "key": "key0",
        "value": "value0"
      }, {
        "key": "key1",
        "value": "value1"
      }]
    }
  }
}
```

4.6.2.2. OnDivertedCallbackEvent

Description: event triggered when a callback is deleted by an agent.

| OnDivertedCallbackEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-------------|--------|---|
| data | Object | Content of the event. See following data Object definition. |
|-------------|--------|---|

| OnDivertedCallbackEvent Data Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the callback was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| reasonKey | Integer | Key of the reason the agent used for deleting the callback. |

Message Example:

```
// OnDivertedCallbackEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "CALLBACK",
    "type": "DIVERTED_CALLBACK_EVENT",
    "data": {
      "mediaType": "CALLBACK",
      "resource": "3",
      "uniqueCallId": "C8511543249806039",
      "requeueCount": 1,
      "reasonKey": 6
    }
  }
}
```

4.6.2.3. OnMakeCallFailedCallbackEvent

Description: event triggered when it's not possible to make a callback call (e.g. Accept request sent but agent's extension is busy).

| OnMakeCallFailedCallbackEvent Object | | |
|--------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnMakeCallFailedCallbackEvent Data Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the callback was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |

Message Example:

```
// OnMakeCallFailedCallbackEvent Object
{
```

```

    "type": "EVENT",
    "data": {
      "realm": "CALLBACK",
      "type": "MAKECALLFAILED_CALLBACK_EVENT",
      "data": {
        "mediaType": "CALLBACK",
        "resource": "3",
        "uniqueCallId": "C8511543249806039",
        "requeueCount": 1
      }
    }
  }
}

```

4.6.2.4. OnServerConnected

Description: event triggered when connection to Callback server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```

//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "CALLBACK",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6007:10.81.3.116"
    }
  }
}

```

4.6.2.5. OnServerDisconnected

Description: event triggered when connection to Callback server is lost.

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| OnServerDisconnectedEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|---------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "CALLBACK",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6007:10.81.3.116"
    }
  }
}
```

4.6.3. Callback Common Objects

4.6.3.1. Schedule Object

| Schedule Object | | |
|-----------------|----------------|---|
| Attribute name | Attribute type | Description |
| startTime | String | Start of the time interval of the callback. |
| endTime | String | End of the time interval of the callback. |
| phoneNumber | String | Phone number which shall be callback back. |

4.6.3.2. Schedules Object

| Schedules Object | | |
|------------------|----------------|--|
| Attribute name | Attribute type | Description |
| List of: | | |
| startTime | String | Start of the time interval of the callback. |
| endTime | String | End of the time interval of the callback. |
| phoneNumber | String | Phone number which shall be callback back. |
| status | String | Status of the scheduled callback. See definition of possible values at CallbackScheduleStatus. |

4.6.3.3. ContactData Object

| ContactData Object | | |
|--------------------|----------------|-------------------------------------|
| Attribute name | Attribute type | Description |
| List of: | | |
| key | String | Identification of the contact data. |
| value | String | Content of the contact data. |

4.7. Web Collaboration

4.7.1. Web Collaboration Commands

All requests require that the application is logged on Admin and an Authorization header with the session token.

In general the response to the Web Collaboration Commands has the following format:

| Web Collaboration Commands Response Object | | |
|--|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.7.1.1. Logon

Description: request to logon an agent on Web Collaboration media.

URL: POST /restsdk/webapi/webcollaboration/logon

| Logon Request Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent which shall be logged on. |

Message Example:

```
//Logon Object
{
  "agentKey" : 5
}
```

4.7.1.2. Logoff

Description: request to logoff an agent from Web Collaboration media.

URL: POST /restsdk/webapi/webcollaboration/logoff

| Logoff Request Object |
|-----------------------|
|-----------------------|

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| Attribute name | Attribute type | Description |
|-----------------|----------------|--|
| agentKey | Integer | Key number of the agent which shall be logged off. |

Message Example:

```
//Logoff Object
{
  "agentKey" : 5
}
```

4.7.1.3. Accept

Description: request to accept a Web Collaboration session/conference invite delivered to the agent.
URL: POST /restsdk/webapi/webcollaboration/accept

| Accept Request Object | | |
|-----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent which shall accept the WebCollaboration session/conference invite. |
| uniqueCallId | String | Call Id of the Web Collaboration session/conference invite to be accepted. |

Message Example:

```
//Accept Object
{
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.4. Disconnect

Description: request to disconnect an agent from a Web Collaboration session.
URL: POST /restsdk/webapi/webcollaboration/disconnect

| Disconnect Request Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent for which the Web Collaboration session shall be disconnected. |
| uniqueCallId | String | Call Id of the Web Collaboration session to be disconnected. |

Message Example:

```
//Disconnect Object
{
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.5. InviteAgent

Description: request to invite an agent to join a Web Collaboration session.

URL: POST /restsdk/webapi/webcollaboration/inviteagent

| InviteAgent Request Object | | |
|----------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| invitedAgentKey | Integer | Key number of the agent who shall be invited to join the Web Collaboration session. |
| agentKey | Integer | Key number of the agent who shall be inviting the other agent to join the Web Collaboration session. |
| uniqueCallId | String | Call Id of the Web Collaboration session. |

Message Example:

```
//InviteAgent Object
{
  "invitedAgentKey" : 9,
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.6. DeclineInvite

Description: request to decline an invite to join a Web Collaboration session.

URL: POST /restsdk/webapi/webcollaboration/declineinvite

| DeclineInvite Request Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| invitedAgentKey | Integer | Key number of the agent who shall decline the invite to join the Web Collaboration session. |
| agentKey | Integer | Key number of the agent who had sent the invite which shall be declined. |
| uniqueCallId | String | Call Id of the Web Collaboration session. |

Message Example:

```
//DeclineInvite Object
{
  "invitedAgentKey" : 9,
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.7. CallMe

Description: request to send a call me to the customer. The customer can then reply with a phone number

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

to be called by the agent.

URL: POST /restsdk/webapi/webcollaboration/callme

| CallMe Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key number of the agent who is starting the Call Me function. |
| uniqueCallId | String | Call Id of the Web Collaboration session for which the Call Me function shall be started. |

Message Example:

```
//CallMe Object
{
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.8. RequeueToQueue

Description: request to requeue a Web Collaboration session to another queue.

URL: POST /restsdk/webapi/webcollaboration/requeuetoqueue

| RequeueToQueue Request Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| queueKey | Integer | Key number of the queue to which the Web Collaboration session shall be requeued. |
| agentKey | Integer | Key number of the agent who is handling this Web Collaboration session. |
| uniqueCallId | String | Call Id of the Web Collaboration session which shall be requeued. |

Message Example:

```
//RequeueToQueue Object
{
  "queueKey" : 8,
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.9. RequeueToAgent

Description: request to requeue a Web Collaboration session to another agent.

URL: POST /restsdk/webapi/webcollaboration/requeuetoagent

| RequeueToAgent Request Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| toAgentKey | Integer | Key number of the agent to which the Web Collaboration session shall be requeued. |
| priority | Integer | Priority for the requeued Web Collaboration session. |
| agentKey | Integer | Key number of the agent who is handling this Web Collaboration session. |

| | | |
|---------------------|--------|--|
| uniqueCallId | String | Call Id of the Web Collaboration session which shall be requested. |
|---------------------|--------|--|

Message Example:

```
//RequeueToAgent Object
{
  "toAgentKey" : 8,
  "priority" : 1,
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.10. AddContent

Description: request to add content to a Web Collaboration session.

URL: POST /restsdk/webapi/webcollaboration/addcontent

| AddContent Request Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| content | String | The content to be added on the behalf of the agent to a Web Collaboration session. |
| agentKey | Integer | Key number of the agent on whose behalf the content shall be added. |
| uniqueCallId | String | Call Id of the Web Collaboration session for which the content shall be added. |

Message Example:

```
//AddContent Object
{
  "content" : "How are you doing?",
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.11. UpdateContactData

Description: request to update the contact data of a Web Collaboration session.

URL: POST /restsdk/webapi/webcollaboration/updatecontactdata

| UpdateContactData Request Object | | |
|----------------------------------|----------------------|--|
| Attribute name | Attribute type | Description |
| contactData | List of Contact Data | The contact data to be update on a Web Collaboration session. |
| agentKey | Integer | Key number of the agent on whose behalf the content shall be added. |
| uniqueCallId | String | Call Id of the Web Collaboration session for which the content shall be added. |

Message Example:

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
//UpdateContactData Object
{
  "contactData": [{
    "key": "key0",
    "value": "value0"
  }, {
    "key": "key1",
    "value": "value1"
  }],
  "agentKey" : 5,
  "uniqueCallId": "W869020181026170830001"
}
```

4.7.1.12. StartListenForEvents

Description: request to start listening for Web Collaboration media events. The resource is the user key.
 Note: if '*' is passed, all the subscribers configured for the tenant in the OpenScape Contact Center will be monitored.

URL: POST /restsdk/webapi/webcollaboration/startlistenforevents

| StartListenForEvents Request Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard "*" indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StartListenForEvents Request Object
{
  "resource" : "3"
}
```

4.7.1.13. StopListenForEvents

Description: request to stop listening for Web Collaboration events. The resource is the user key.

URL: POST /restsdk/webapi/webcollaboration/stoplifenforevents

| StopListenForEvents Request Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard "*" indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StopListenForEvents Request Object
{
  "resource" : "3"
}
```

4.7.2. Web Collaboration Events

In general, Web Collaboration Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at <code>MessageType</code> |
| data | Object | Content of the message. See definition of this object for each event type. |

4.7.2.1. OnDeliveredWebChatEvent

Description: event triggered when a Web Collaboration session is delivered to an agent.

| OnDeliveredWebChatEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at <code>Realm</code> . |
| type | String | Identification of the event. See definition of possible values at <code>EventType</code> . |
| data | Object | Content of the event. See following data Object definition. |

| OnDeliveredWebChatEvent Data Object | | |
|-------------------------------------|--------------------|--|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at <code>MediaType</code> . |
| resource | String | Key of the agent to which the Web Collaboration was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| source | String | Content of the source field of the Web Collaboration request. |
| destination | String | Content of the destination field of the Web Collaboration request. |
| invitingAgentKey | Integer | Key of the agent who is inviting to join a Web Collaboration session. This field is only used if an agent is inviting another agent to join a Web Collaboration session. |
| deliveredReason | String | Reason for the delivery of the Web Collaboration session. See definition of possible values at <code>WebCollaborationDeliveredReason</code> . |
| contactData | ContactData Object | List of key value pairs of Contact Data. |
| chatContent | ChatContent Object | List of formatted content items. |

Message Example:

```
// OnDeliveredWebChatEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "DELIVERED_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "resource": "3",
    "uniqueCallId": "W869020181027100055005",
    "requeueCount": 0,
    "source": "sourceweb",
    "destination": "destweb",
    "invitingAgentKey": 0,
    "deliveredReason": "NORMAL_ASSIGNMENT",
    "contactData": [{
      "key": "Key1",
      "value": "val1"
    }, {
      "key": "Key2",
      "value": "val2"
    }, {
      "key": "Key3",
      "value": "val3"
    }, {
      "key": "__HPPC_UserLanguage",
      "value": "1"
    }
  ],
  "chatContent": [{
    "chatCommitter": "CUSTOMER",
    "content": "<TABLE width='95%' border='0' cellspacing='0' cellpadding='2'><TR><TD width='2%' valign='top'><IMG SRC='images/customericon.gif' WIDTH='16' HEIGHT='16'/></TD><TD width='98%'><FONT face=Tahoma size=2><FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2>11/27/2018</FONT>, <FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2>10:00 AM</FONT> <FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2><STRONG>Name</STRONG></FONT><STRONG> says</STRONG></FONT></TD></TR><TR><TD>&nbsp;</TD><TD valign='top'><FONT face=Tahoma size=2>Can you tell me about...</FONT></TD></TR></TABLE>"
  }, {
    "chatCommitter": "SYSTEM",
    "content": "<TABLE width='95%' border='0' cellspacing='0' cellpadding='2'><TR><TD width='2%' valign='top'><IMG SRC='images/systemicon.gif' WIDTH='16' HEIGHT='16'/></TD><TD width='98%'><FONT face=Tahoma size=2><FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2>11/27/2018</FONT>, <FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2>10:00 AM</FONT> <FONT contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma size=2><STRONG><FONT face=Tahoma size=2>System</FONT></STRONG></FONT><STRONG> says</STRONG></FONT></TD></TR><TR><TD>&nbsp;</TD><TD valign='top'><FONT face=Tahoma size=2>Welcome to the contact center, powered by OpenScape Contact Center.&nbsp;<br>Please hold while we connect you to an agent.</FONT></TD></TR></TABLE>"
  }
  ]
}

```

4.7.2.2. OnDivertedWebChatEvent

Description: event triggered when an agent declines an invite to a Web Collaboration session.

| OnDivertedWebChatEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDivertedWebChatEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent who had sent the invitation to join a Web Collaboration session. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| refusingAgentKey | Integer | Key of the agent who refused the invitation to join a Web Collaboration session. |
| divertReason | String | Reason for the refuse of the Web Collaboration session. See definition of possible values at WebCollaborationDivertReason. |

Message Example:

```
// OnDivertedWebChatEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "DIVERTED_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0,
      "refusingAgentKey": 4,
      "divertReason": "INVITATION_REJECTED"
    }
  }
}
```

4.7.2.3. OnContentWebChatEvent

Description: event triggered when a content is added to a Web Collaboration session.

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| OnContentWebChatEvent Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnContentWebChatEvent Data Object | | |
|-----------------------------------|--------------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent added the content to the Web Collaboration session. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| chatContent | ChatContent Object | List of formatted content items. |

Message Example:

```
// OnContentWebChatEvent Object
```

```
{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "CONTENT_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0,
      "chatContent": [{
        "chatCommitter": "AGENT",
        "content": "<TABLE width='95%' border='0' cellpadding='0' cellspacing='0'>
          <TR><TD width='2%' valign='top'><IMG SRC='images/agenticon.gif'
            WIDTH='16' HEIGHT='16'/></TD><TD width='98%'><FONT face=Tahoma size=2><FONT
            contentEditable=false style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma
            size=2>11/27/2018</FONT>, <FONT contentEditable=false style=\"BACKGROUND-COLOR:
            #ffffff\" tabIndex=-1 face=Tahoma size=2>10:17 AM</FONT> <FONT contentEditable=false
            style=\"BACKGROUND-COLOR: #ffffff\" tabIndex=-1 face=Tahoma
            size=2><STRONG>agent</STRONG></FONT><STRONG>
            says</STRONG></FONT></TD></TR><TR><TD>&nbsp;</TD><TD valign='top'>hi <img
            src=\"images/angry.gif\"></TD></TR></TABLE>"
      ]
    }
  }
}
```

4.7.2.4. OnDisconnectedWebChatEvent

Description: event triggered when participant disconnects from a Web Collaboration session.

| OnDisconnectedWebChatEvent Object | | |
|-----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDisconnectedWebChatEvent Data Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent who disconnected the Web Collaboration session. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| disconnectedAgentKey | Integer | Key of the agent who disconnected from the Web Collaboration session. |
| disconnectReason | String | Reason for the disconnection of the Web Collaboration session. See definition of possible values at WebCollaborationDisconnectReason. |

Message Example:

```
// OnDisconnectedWebChatEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "DISCONNECTED_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0,
      "disconnectedAgentKey": 0,
      "disconnectReason": "NORMAL_DISCONNECT"
    }
  }
}
```

4.7.2.5. OnEstablishedWebChatEvent

Description: event triggered when a Web Collaboration session is established with an agent.

| OnEstablishedWebChatEvent Object | | |
|----------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|--------------|--------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnEstablishedWebChatEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent who accepted the invitation to join the Web Collaboration session. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |

Message Example:

```
// OnEstablishedWebChatEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "ESTABLISHED_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0
    }
  }
}
```

4.7.2.6. OnConferencedWebChatEvent

Description: event triggered when a Web Collaboration session becomes a conference (with more than 2 participants).

| OnConferencedWebChatEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnConferencedWebChatEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent who joined the Web Collaboration conference session. |

| | | |
|-----------------------|---------|--|
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| joinedAgentKey | Integer | Key of the agent who joined the Web Collaboration conference session. |
| numberOfAgents | Integer | Number of the agents who are participating in the Web Collaboration session. |

Message Example:

```
// OnConferencedWebChatEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "CONFERENCED_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0,
      "joinedAgentKey": 3,
      "numberOfAgents": 2
    }
  }
}
```

4.7.2.7. OnCallMeAnswerWebChatEvent

Description: event triggered when a customer answers to a CallMe request.

| OnCallMeAnswerWebChatEvent Object | | |
|-----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnCallMeAnswerWebChatEvent Data Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent who sent the Call Me request to the customer. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| phoneNumber | String | Phone number to be used to call the customer. |

Message Example:

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
// OnCallMeAnswerWebChatEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "WEB_INTERACTION",
    "type": "CALL_ME_ANSWER_WEB_CHAT_EVENT",
    "data": {
      "mediaType": "WEB_COLLABORATION",
      "resource": "3",
      "uniqueCallId": "W869020181027100055005",
      "requeueCount": 0,
      "phoneNumber": "+55(41)80911597"
    }
  }
}
}
```

4.7.2.8. OnServerConnectedEvent

Description: event triggered when connection to WebInteraction server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```
//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "WEB_INTERACTION",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6020:10.81.3.116"
    }
  }
}
}
```

4.7.2.9. OnServerDisconnectedEvent

Description: event triggered when connection to WebInteraction server is lost.

| OnServerDisconnectedEvent Object | | |
|----------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

| | | |
|--------------|--------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "WEB_INTERACTION",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6020:10.81.3.116"
    }
  }
}
```

4.7.3. Web Collaboration Common Objects

4.7.3.1. ChatContent Object

| ChatContent Object | | |
|---------------------------|-----------------------|---|
| Attribute name | Attribute type | Description |
| chatCommitter | String | Identification of the party which added the content. See definition of possible values at WebCollaborationChatCommitter enum. |
| content | String | Formatted content. |

4.7.3.2. ContactData Object

| ContactData Object | | |
|---------------------------|-----------------------|-------------------------------------|
| Attribute name | Attribute type | Description |
| List of: | | |
| key | String | Identification of the contact data. |
| value | String | Content of the contact data. |

4.8. OpenMedia

4.8.1. OpenMedia Commands

All requests require that the application is logged on Admin and an Authorization header with the session token.

In general the response to the OpenMedia Commands has the following format:

| OpenMedia Commands Response Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.8.1.1. Logon

Description: request to logon an agent on an OpenMedia connector.

URL: POST /restsdk/webapi/openmedia/logon

| Logon Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| connectorKey | Integer | Key number of the connector to which the agent shall be logged on. |
| agentKey | Integer | Key number of the agent which shall be logged on. |

Message Example:

```
//Logon Object
{
  "connectorKey" : 5,
  "agentKey" : 5
}
```

4.8.1.2. Logoff

Description: request to logoff an agent from an OpenMedia connector.

URL: POST /restsdk/webapi/openmedia/logoff

| Logoff Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| connectorKey | Integer | Key number of the connector to which the agent shall be logged off. |
| agentKey | Integer | Key number of the agent which shall be logged off. |

Message Example:

```
//Logoff Object
{
  "connectorKey" : 5,
  "agentKey" : 5
}
```

4.8.1.3. Accept

Description: request to accept an OpenMedia session delivered to the agent.
URL: POST /restsdk/webapi/openmedia/accept

| Accept Request Object | | |
|-----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call Id of the OpenMedia session to be accepted. |

Message Example:

```
//Accept Object
{
  "uniqueCallId": "OB869020181026170830001"
}
```

4.8.1.4. Disconnect

Description: request to disconnect an agent from an OpenMedia session.
URL: POST /restsdk/webapi/openmedia/disconnect

| Disconnect Request Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call Id of the OpenMedia session to be disconnected. |

Message Example:

```
//Disconnect Object
{
  "uniqueCallId": "OB869020181026170830001"
}
```

4.8.1.5. QueryEligibleUsers

Description: request to query logged on agents on the specified connector.
URL: POST /restsdk/webapi/openmedia/queryeligibleusers

| QueryEligibleUsersRequest Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| connectorKey | Integer | Key of the connector for which the users shall be queried. |

Message Example:

```
//QueryEligibleUsersRequest Object
{
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
"connectorKey" : 1
}
```

| QueryEligibleUsersResponse Object | | |
|-----------------------------------|-----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| agentKeys | List of Integer | List of keys of the agents who are eligible for the passed connector. |

Message Example:

```
//QueryEligibleUsersResponse Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
  "agentKeys" : [3]
}
```

4.8.1.6. Reply

Description: request to reply an OpenMedia contact.

URL: POST /restsdk/webapi/openmedia/reply

| Reply Request Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| connectorName | String | Name of the connector |
| replyTo | String | OPTIONAL - Refers to the inReplyTo id on the objectToBePublished which is sent to the connector. If the replyTo attribute is missing or empty, OpenMedia Server will use the last published id as the "inReplyTo id". |
| content | String | Content of the reply message. |
| uniqueCallId | String | Call Id of the OpenMedia session to be replied. |

Message Example:

```
//Reply Object
{
  "connectorName": " CustomerSystem ",
  "replyTo": "ID456454343_4567890",
  "content": "How can I help you?",
  "uniqueCallId": "OB869020181026170830001"
}
```

4.8.1.7. Defer

Description: request to defer an OpenMedia contact. The contact must be in Established state (i.e. Accepted by an agent) in order to be deferred. The REST SDK allows to defer both Real-Time and Non

Real-Time OpenMedia contacts.
URL: POST /restsdk/webapi/openmedia/defer

| Defer Request Object | | |
|----------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | String | Key of the agent who is deferring the OpenMedia contact. |
| connectorKey | String | Key of the connector which originated the contact. |
| draftMessage | String | OPTIONAL - Content of the draft message. |
| uniqueCallId | String | Call Id of the OpenMedia session to be deferred. |

Message Example:

```
//Defer Object
{
  "agentKey": 3,
  "connectorKey": 1
  "draftMessage": "How can I help you?",
  "uniqueCallId": "OB869020181026170830001"
}
```

4.8.1.8. Resume

Description: request to resume a deferred OpenMedia contact.
URL: POST /restsdk/webapi/openmedia/resume

| Resume Request Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call Id of the OpenMedia session to be resumed. |

Message Example:

```
//Resume Object
{
  "uniqueCallId": "OB869020181026170830001"
}
```

4.8.1.9. RequeueToQueue

Description: request to requeue an OpenMedia contact to another queue.
URL: POST /restsdk/webapi/openmedia/requeue-to-queue

| RequeueToQueue Request Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| queueKey | Integer | Key number of the queue to which the OpenMedia session shall be requeued. |
| priority | Integer | Key number of the agent who is handling this OpenMedia session. |
| draftMessage | String | OPTIONAL - Content of the draft message. |
| uniqueCallId | String | Call Id of the OpenMedia session which shall be requeued. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

Message Example:

```
//RequeueToQueue Object
{
  "queueKey" : 8,
  "priority" : 20,
  "draftMessage": "How can I help you?",
  "uniqueCallId": "0869020181026170830001"
}
```

4.8.1.10. RequeueToAgent

Description: request to requeue an OpenMedia contact to another agent.

URL: POST /restsdk/webapi/openmedia/requeueToAgent

| RequeueToAgent Request Object | | |
|-------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| toAgentKey | Integer | Key number of the agent to which the OpenMedia session shall be requeued. |
| priority | Integer | Priority for the requeued OpenMedia session. |
| draftMessage | String | OPTIONAL - Content of the draft message. |
| uniqueCallId | String | Call Id of the OpenMedia session which shall be requeued. |

Message Example:

```
//RequeueToAgent Object
{
  "toAgentKey" : 8,
  "priority" : 1,
  "draftMessage": "How can I help you?",
  "uniqueCallId": "0869020181026170830001"
}
```

4.8.1.11. Discard

Description: request to discard an OpenMedia contact. It is possible to discard both Real-Time and Non Real-Time OpenMedia contacts.

URL: POST /restsdk/webapi/openmedia/discard

| Discard Request Object | | |
|------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| reasonKey | Integer | Key number of the reason for which the OpenMedia contact has been discarded. |
| uniqueCallId | String | Call Id of the OpenMedia session which shall be requeued. |

Message Example:

```
//Discard Object
{
  "reasonKey" : 8,
```

```
"uniqueCallId": "0869020181026170830001"
}
```

4.8.1.12. QueryDeferredMessages

Description: request to query deferred OpenMedia messages/contacts.
 URL: POST /restsdk/webapi/openmedia/querydeferredmessages

| QueryDeferredMessages Request Object | | |
|--------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| agentKey | Integer | Key of the agent for which the deferred messages shall be queried. |

Message Example:

```
//QueryDeferredMessages Request Object
{
  "connectorKey" : 1
}
```

| QueryDeferredMessages Response Object | | |
|---------------------------------------|---------------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| deferredList | DeferredList Object | List of contacts which are deferred for this agent. |

Message Example:

```
// QueryDeferredMessages Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
  "agentKeys" : [{
    "uniqueCallId": "0869020181026170830001",
    "queueKey" : 5,
    "connectorKey" : 1,
    "connectorName": "CustomerSystem",
    "arrivalTime": "2019-09-19T14:17:56Z",
    "deferTime" : "2019-09-19T14:18:45Z",
    "from" : "John Smith",
    "to": "Sales"
  }]
}
```

4.8.1.13. GetStream

Description: request to get the stream of an OpenMedia contact. Since this request is asynchronous, the result comes as an event of type STREAM_RESPONSE_OPENMEDIA_EVENT. Thus, it's required OpenMedia event listening on the AgentKey related to the agent who requested the stream (which is probably handling the contact).

URL: POST /restsdk/webapi/openmedia/getstream

| GetStream Request Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call Id of the OpenMedia contact for which the stream shall be collected. |

Message Example:

```
//GetStream Object
{
  "uniqueCallId": "0869020181026170830001"
}
```

4.8.1.14. StartListenForEvents

Description: request to start listening for OpenMedia events. The resource is the user key.

Note: if '*' is passed, all the subscribers configured for the tenant in the OpenScape Contact Center will be monitored.

URL: POST /restsdk/webapi/openmedia/startlistenforevents

| StartListenForEvents Request Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard '*' indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StartListenForEvents Request Object
{
  "resource" : "3"
}
```

4.8.1.15. StopListenForEvents

Description: request to stop listening for OpenMedia events. The resource is the user key.

URL: POST /restsdk/webapi/openmedia/stoplistenforevents

| StopListenForEvents Request Object | | |
|------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| resource | String | Key of the user to be monitored. Wildcard '*' indicates that the request applies to all extension numbers configured for the corresponding tenant in the OpenScape Contact Center. |

Message Example:

```
//StopListenForEvents Request Object
{
  "resource" : "3"
}
```

4.8.2. OpenMedia Events

In general, OpenMedia Events have the following structure:

| Event Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| type | String | Type of message. See definition of possible values at <code>MessageType</code> |
| data | Object | Content of the message. See definition of this object for each event type. |

4.8.2.1. OnDeliveredOpenMediaEvent

Description: event triggered when a OpenMedia contact is delivered to an agent.

| OnDeliveredOpenMediaEvent Object | | |
|----------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at <code>Realm</code> . |
| type | String | Identification of the event. See definition of possible values at <code>EventType</code> . |
| data | Object | Content of the event. See following data Object definition. |

| OnDeliveredOpenMediaEvent Data Object | | |
|---------------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at <code>MediaType</code> . |
| resource | String | Key of the agent to which the OpenMedia contact was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| conversationId | String | Conversation ID of the OpenMedia contact. |
| interactionId | String | Interaction ID of the OpenMedia message in the contact. |
| connectorKey | Integer | Key of the OpenMedia connector which originated the contact. |
| connectorName | String | Name of the OpenMedia connector which originated the contact. |
| realTime | Boolean | Indicates if the contact is real time or non real time. |
| draftMessage | String | Message typed by the agent so far. |
| autoSuggestMessage | String | Suggested message. |
| contactData | ContactData Object | List of contact data |
| openMediaContent | OpenMediaContent Object | Content of the initial message. |

Message Example:

```
// OnDeliveredOpenMediaEvent Object
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "DELIVERED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "conversationId" : "OAF0DEC5C0300",
      "interactionId" : "OAF0DEC5C0300",
      "connectorKey": 1,
      "connectorName": "CompanySystem",
      "realTime": false,
      "draftMessage": "",
      "autoSuggestMessage": "Thank you for your message!",
      "contactData": [{
        "key": "Key1",
        "value": "val1"
      }, {
        "key": "Key2",
        "value": "val2"
      }, {
        "key": "Key3",
        "value": "val3"
      }, {
        "key": "___HPPC_UserLanguage",
        "value": "1"
      }
    ],
    "openMediaContent" : {
      "id" : "703545976517482_703546026517477",
      "sourceName" : "John Smith",
      "time" : "2019-05-27T19:17:53Z",
      "content" : "fafasfasfasd",
      "commiter" : "CUSTOMER",
      "title" : "Sales Testing",
      "destinationName" : "aaa",
      "attachments" : [{
        "type" : "imagem",
        "content" : "jpg image",
        "url" : "http://evoque:8080/Circuit.jpg"
      }, {
        "type" : "image/jpg",
        "content" : "jpg image",
        "url" : "https://cdn.voxasdad-
cdn.com/uploads/chorus_image/image/57914095/Royal_Guard_set_cover.1512774916.jpg?file=
as0id1=1d=cd=csda=vermiverm=21d,dx912xwq"
      }
    ]
  }
}
}
}

```

4.8.2.2. OnDisconnectedOpenMediaEvent

Description: event triggered when disconnecting from an OpenMedia contact.

| OnDisconnectedOpenMediaEvent Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDisconnectedOpenMediaEvent Data Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent from which the OpenMedia contact was disconnected. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| discardReasonKey | Integer | Key of the reason for which the OpenMedia session was discarded. |
| disconnectReason | String | Reason for disconnection. See definition of possible values at OpenMediaDisconnectReason enum. |

Message Example:

```
// OnDisconnectedOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "DISCONNECTED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "discardReasonKey" : 1,
      "disconnectReason" : "AGENTREPLIED"
    }
  }
}
```

4.8.2.3. OnDivertedOpenMediaEvent

Description: event triggered when an OpenMedia contact is diverted (i.e. Delivered to an agent but returns to queue).

A31003-S22C0-R102-02-7620, 02/2026

OpenScale Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| OnDivertedOpenMediaEvent Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDivertedOpenMediaEvent Data Object | | |
|--------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being diverted. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the OpenMedia contact was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| divertReason | String | Reason for diversion. See definition of possible values at OpenMediaDivertReason enum. |

Message Example:

```
// OnDivertedOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "DIVERTED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "divertReason": "RNA"
    }
  }
}
```

4.8.2.4. OnEstablishedOpenMediaEvent

Description: event triggered when an OpenMedia contact is established.

| OnEstablishedOpenMediaEvent Object | | |
|------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnEstablishedOpenMediaEvent Data Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |

| | | |
|---------------------|---------|--|
| resource | String | Key of the agent to which the OpenMedia contact was established. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |

Message Example:

```
// OnEstablishedOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "ESTABLISHED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0
    }
  }
}
```

4.8.2.5. OnDeferredOpenMediaEvent

Description: event triggered when an OpenMedia contact is deferred.

| OnDeferredOpenMediaEvent Object | | |
|---------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnDeferredOpenMediaEvent Data Object | | |
|--------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the OpenMedia contact was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| deferReason | String | Reason for deferring. See definition of possible values at OpenMediaDeferReason enum. |

Message Example:

```
// OnDeferredOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "realm": "OPENMEDIA",
    "type": "DEFERRED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "deferReason": "AGENTDEFER"
    }
  }
}

```

4.8.2.6. OnResumedOpenMediaEvent

Description: event triggered when an OpenMedia contact is resumed.

| OnResumedOpenMediaEvent Object | | |
|--------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnResumedOpenMediaEvent Data Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the OpenMedia contact was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| deferReason | String | Reason for resuming. See definition of possible values at OpenMediaResumeReason enum. |
| draftMessage | String | Draft message by agent. |

Message Example:

```

// OnResumedOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "RESUMED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "deferReason": "DEFERRESUMED"
      "draftMessage": "draft msg by agent"
    }
  }
}

```

4.8.2.7. OnTransferredOpenMediaEvent

Description: event triggered when an OpenMedia contact is requeued (either to a queue or to another agent).

| OnTransferredOpenMediaEvent Object | | |
|------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnTransferredOpenMediaEvent Data Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent to which the OpenMedia contact was delivered. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| toAgentKey | Integer | Key of the agent to which the OpenMedia contact was requeued (only if reserved for agent). |
| transferReason | String | Reason for transferring. See definition of possible values at OpenMediaTransferReason enum. |
| transferTarget | String | Target of transfer. See definition of possible values at OpenMediaTransferTarget enum. |

Message Example:

```
// OnTransferredOpenMediaEvent Object
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "TRANSFERRED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "toAgentKey": 0,
      "transferReason": "NORMAL",
      "transferTarget": "QUEUE"
    }
  }
}
```

4.8.2.8. OnContentAddedOpenMediaEvent

Description: event triggered when customer sends/adds content to an OpenMedia (Realtime contact).

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

The event is also triggered after a requeue, providing the messages exchanged between the previous agent and the customer.

| OnContentAddedOpenMediaEvent Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| OnContentAddedOpenMediaEvent Data Object | | |
|--|-------------------------|---|
| Attribute name | Attribute type | Description |
| mediaType | String | Media type for which the event is being reported. See definition of possible values at MediaType. |
| resource | String | Key of the agent for which the content was added. |
| uniqueCallId | String | Call ID related to the event that is being reported. |
| requeueCount | Integer | Number of times this contact has been requeued. |
| openMediaContent | OpenMediaContent Object | Added content. |

Message Example:

```
// OnContentAddedOpenMediaEvent Object

{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "CONTENT_ADDED_OPENMEDIA_EVENT",
    "data": {
      "mediaType": "OPENMEDIA",
      "resource": "3",
      "uniqueCallId": "0869020181027100055005",
      "requeueCount": 0,
      "openMediaContent" : {
        "id" : "703545976517482_703546026517477",
        "sourceName" : "John Smith",
        "time" : "2019-05-27T19:17:53Z",
        "content" : "fafasfasfasd",
        "committer" : "AGENT",
        "title" : "Sales Testing",
        "destinationName" : "John Smith",
        "attachments" : []
      }
    }
  }
}
```

4.8.2.9. StreamResponseOpenMediaEvent

Description: event triggered as a response to the GetStream request.

| StreamResponseOpenMediaEvent Object | | |
|-------------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| StreamResponseOpenMediaEvent Data Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| connectorKey | Integer | Media type for which the event is being reported. |
| stream | Stream Object | Key of the agent for which the content was added. |

Message Example:

```
// StreamResponseOpenMediaEvent Object
```

```
{
  "type": "EVENT",
  "data": {
    "realm": "OPENMEDIA",
    "type": "STREAM_RESPONSE_OPENMEDIA_EVENT",
    "data": {
      "connectorKey": 1,
      "stream" : {
        "id" : "703545976517482_703546026517400",
        "sourceName" : "John Smith",
        "time" : "2019-05-27T19:17:53Z",
        "content" : "Message 1: this is the original complaint.",
        "commiter" : "CUSTOMER",
      }, {
        "id" : "703545976517482_703546026517501",
        "sourceName" : "Martin Jones",
        "time" : "2019-05-27T19:17:58Z",
        "content" : "Message 2: this is the response from the agent.",
        "commiter" : "AGENT",
      }
    ]
  }
}
```

4.8.2.10. OnServerConnected

Description: event triggered when connection to OpenMedia server is established.

| OnServerConnectedEvent Object | | |
|-------------------------------|----------------|-------------|
| Attribute name | Attribute type | Description |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|--------------|--------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerConnectedEvent Data Object | | |
|---|-----------------------|--|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been connected. |

Message Example:

```
//OnServerConnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "OPENMEDIA",
    "type" : "SERVER_CONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6007:10.81.3.116"
    }
  }
}
```

4.8.2.11. OnServerDisconnected

Description: event triggered when connection to OpenMedia server is lost.

| OnServerDisconnectedEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "OPENMEDIA",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {

```

```

    "serverName" : "6007:10.81.3.116"
  }
}
}

```

4.8.3. OpenMedia Common Objects

4.8.3.1. DeferredList Object

| DeferredList Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| List of: | | |
| uniqueCallId | String | Call ID of the OpenMedia contact |
| queueKey | Integer | Key of the queue. |
| connectorKey | Integer | Key of the connector which originated the OpenMedia contact. |
| connectorName | String | Name of the connector which originated the OpenMedia contact. |
| arrivalTime | String | Time the OpenMedia contact was received. |
| deferTime | String | Time the OpenMedia contact was deferred. |
| from | String | Originator of the initial message. |
| to | String | Destination of the initial message. |

4.8.3.2. OpenMediaContent Object

| OpenMediaContent Object | | |
|-------------------------|--------------------|---|
| Attribute name | Attribute type | Description |
| id | String | ID of the content |
| sourceName | String | Name of the content originator |
| time | String | Time the content was created. |
| content | String | Content of posted message. |
| commiter | String | Identification of the commiter of the message. See definition of possible values at OpenMediaCommitter. |
| title | String | Title of the content. |
| destinationName | String | Destination of the initial message. |
| attachments | Attachments Object | List of attachments |

4.8.3.3. Attachments Object

| Attachments Object | | |
|--------------------|----------------|----------------------------|
| Attribute name | Attribute type | Description |
| List of: | | |
| type | String | Type of the attachment. |
| content | String | Content of the attachment. |
| url | String | Attachment location. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

4.8.3.4. Stream Object

| Stream Object | | |
|----------------|----------------|--|
| Attribute name | Attribute type | Description |
| List of: | | |
| id | String | Message id. |
| sourceName | String | Name of the message originator. |
| time | String | Time the message was created. |
| content | String | Content of the message. |
| committer | String | Identification of the committer of the message. See definition of possible values at OpenMediaCommitter. |

4.9. Real-Time Statistics

4.9.1. Real-Time Statistics Commands

All requests require that the application is logged on Admin and an Authorization header with the session token.

In general the response to the Real-Time Statistics Commands has the following format:

| RealTime Commands Response Object | | |
|-----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |

4.9.1.1. StartQuery

Description: request to start a query on RealTime Statistics. A maximum number of five (5) queries of each type can run at the same time per REST SDK application. There are 13 types of queries, therefore one REST SDK application may have up to 65 RealTime queries running at the same time. If the query is successfully started on RealTime Server, the queryId is returned on response with a value greater than zero.

The types of query are: User Real-Time, Queue Real-Time, Group Real-Time, Aggregate Real-Time, Contact Real-Time, Callback Real-Time, User Cumulative, Queue Cumulative, Group Cumulative, Aggregate Cumulative, User Wrapup Reason Cumulative, Queue Wrapup Reason Cumulative, Aggregate Wrapup Reason Cumulative.

If the user which was used to perform the Admin Logon on REST SDK application is not a Master user (Admin logon), this user must have permission to monitor the requested entities (resources) which are provided on "keyList" attribute. This can be configured on Manager (Edit user -> Monitor tab).

The "fromTime" attribute is mandatory when starting cumulative queries, and it must be on ISO 8601 format. It has no effect on realtime queries. The format allowed for "fromTime" attribute is yyyy-mm-ddThh:mm:ssZ (UTC) or yyyy-mm-ddThh:mm:ss±hh:mm (with offset).

The "keyList" list attribute is mandatory. If the same key appears multiple times on the "keyList", it will be considered only once. For example: "keyList": [3, 4, 5, 3, 3, 4, 5, 7] will be considered simply as "keyList": [3, 4, 5, 7].

Since the "keyList" attribute is a list of Integers, the use of wildcard (*) is not possible. For example, it's not allowed to use: "keyList": [*] or even "keyList": "".

URL: POST /restsdk/webapi/realtime/startquery

| StartQuery Request Object | | |
|---------------------------|------------------|---|
| Attribute name | Attribute type | Description |
| queryType | String | Identification of the committer of the message. See definition of possible values at RealTimeQueryType. |
| keyList | List of Integers | List of the keys of the elements of the corresponding queried type. |
| fromTime | String | Start time for the cumulative statistics data. |

Message Examples:

```
//StartQuery Object
{
  "queryType" : "USER_REALTIME",
  "keyList" : [2,3,5]
}

//StartQuery Object (cumulative query)
{
  "queryType" : "USER_CUMULATIVE",
  "keyList" : [5],
  "fromTime" : "2019-09-02T11:00:00Z",
}
```

| StartQuery Response Object | | |
|----------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| errorCode | String | Determines if the request was successfully handled by the server. |
| errorDetails | String | In case of error, it provides a more detailed description of the cause of the error. |
| queryId | Integer | Identifies the query. This parameter will be present in the real-time statistics events. |

Response Example:

```
//StartQuery Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
  "queryId" : 26
}
```

4.9.1.2. StopQuery

Description: request to stop a query on RealTime Server. The application can only stop queries started by itself, i.e. It cannot stop queries started by other SDK applications or OSCC clients. If the application unregisters or its session token expires, all queries started by this application will be automatically stopped.

URL: POST /restsdk/webapi/realtime/stopquery

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| StopQuery Request Object | | |
|--------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query to be stopped. |

Message Examples:

```
//StopQuery Object
{
  "queryId" : 26
}
```

Response Examples:

```
//StopQuery Response Object
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "NO_ERROR",
}

//StopQuery Response Object (stop failed)
{
  "errorCode" : "NO_ERROR",
  "errorDetails" : "StopRealTimeQuery - Application is not a valid listener for
queryId [26]",
}
```

4.9.2. Real Time Statistics Events

When starting a RealTime Server query, the SDK Application receives a response with the queryId associated to the started query. Then, it periodically receives events with the query results.

Events are posted on the Webhook provided on application register request. Unless the application stops the query or unregisters (either by request or by timeout), the REST SDK service will keep posting the events associated to that query on the provided Webhook. The events will bring the associated queryId and a list of monitored elements. Each monitored resource will have its own element on the list if the logged REST SDK user (which started the query) has permission to monitor it. Otherwise, the results for the said resource will not be included on the "elements" list.

The "timeInterval" attribute on cumulative queries will always be on UTC time, even if "fromTime" on the associated StartQuery request was on local time (with offset). A quarter of an hour is considered one interval, or a "timeInterval".

The first event of a cumulative query (soon after starting the query) will report statistics for the current/latest and past intervals, i.e. all statistics gathered since the provided time ("fromTime") for the cumulative period. Then, the following events correspond only to the current interval, if data is available. If not, data for the previous interval is considered. The only exceptions for this are Wrap-up reason cumulative events, which bring data only for the current interval (once the first event with current/latest and past intervals is sent).

All statistics times are measured in seconds.

In general, Real Time Statistics Events have the following structure:

| Event Object |
|--------------|
|--------------|

| Attribute name | Attribute type | Description |
|----------------|----------------|--|
| type | String | Type of message. See definition of possible values at <code>MessageType</code> |
| data | Object | Content of the message. See definition of this object for each event type. |

4.9.2.1. UserRealTimeEvent

Description: event triggered when UserRealTime information is available. The monitored resource is the `userKey`

| UserRealTimeEvent Object | | |
|--------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at <code>Realm</code> . |
| type | String | Identification of the event. See definition of possible values at <code>EventType</code> . |
| data | Object | Content of the event. See following data Object definition. |

| UserRealTimeEvent Data Object | | |
|-------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported.. |

| Elements Object | | |
|------------------------------|-------------------------|--|
| Attribute name | Attribute type | Description |
| userKey | Integer | Key of the user. |
| extension | String | Telephone extension that the user is logged on to. |
| presenceState | String | Presence state of the user. See definition of possible values at <code>PresenceStates</code> enum. |
| timeInPresenceState | Integer | Amount of time that the user has been in the current presence state. |
| routingState | String | Routing state of the user. See definition of possible values at <code>RoutingStates</code> enum. |
| timeInRoutingState | Integer | Amount of time that the user has been in the current routing state. |
| routingStateReasonKey | Integer | Key of the Unavailable reason or Work reason that the user selected. |
| minUnusedCapacity | Integer | The maximum number of contacts (including direct contacts) that the user can accept before reaching their configured capacity. |
| maxUnusedCapacity | Integer | The minimum number of contacts (including direct contacts) that the user can accept before reaching their configured capacity. |
| contacts | List of Contacts Object | List of the contacts the user is handling. |

| Contacts Object | | |
|---------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| uniqueCallId | String | Call ID of the contact. |
| description | String | Description of the contact. |
| associatedQueueKey | Integer | Key of the queue this contact is associated to. |
| requeueCount | Integer | Indicates how many times this contact has been requeued. |
| contactType | String | Type of the contact. See definition of possible values at <code>ContactType</code> enum. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|----------------------------|---------|---|
| handlingState | String | State of the user while handling a contact. See definition of possible values at HandlingStates enum. |
| handlingStateReason | Integer | Key of the reason for which the user is in this handling state. |
| primaryContact | Boolean | Indicates if this is the primary contact. |
| userHandlingTime | Integer | Indicates how long the user is handling this contact. |
| activeContactTime | Integer | Indicates how long the contact is active for this user. |
| timeInHandlingState | Integer | Indicates how long the user is in this handling state. |

Message Example:

```
// UserRealTimeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "USER_REALTIME_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "userKey" : 3,
        "extension" : "554181021112",
        "presenceState" : "ACTIVE",
        "timeInPresenceState" : 7,
        "routingState" : "AVAILABLE",
        "timeInRoutingState" : 12,
        "routingStateReasonKey" : 0,
        "minUnusedCapacity" : 0,
        "maxUnusedCapacity" : 0,
        "contacts" : [ {
          "uniqueCallId" : "6141567464070452",
          "description" : "General Call",
          "associatedQueueKey" : 1,
          "requeueCount" : 0,
          "contactType" : "ROUTED_VOICE",
          "handlingState" : "CONNECTED",
          "handlingStateReason" : 0,
          "primaryContact" : true,
          "userHandlingTime" : 5,
          "activeContactTime" : 5,
          "timeInHandlingState" : 5
        } ]
      } ]
    } ]
  }
}
```

4.9.2.2. QueueRealTimeEvent

Description: event triggered when QueueRealTime information is available. The monitored resource is the queueKey

QueueRealTimeEvent Object

| Attribute name | Attribute type | Description |
|----------------|----------------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| QueueRealTimeEvent Data Object | | |
|--------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported.. |

| Elements Object | | |
|---------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| abandonedRate | Float | Weighted percentage of the last 24 contacts routed to the queue that were abandoned. |
| avgAbandonedWaitTime | Float | Average amount of time that contacts waited in the queue before being abandoned, based on the last 10 contacts that were abandoned. |
| avgAnsweredWaitTime | Float | Average amount of time that contacts waited in the queue before being answered, based on the last 10 contacts that were abandoned. |
| queuedContacts | Integer | Number of contacts that are waiting in the queue. |
| overflowedContacts | Integer | Number of contacts waiting in the queue that have overflowed. |
| oldestContactWaitTime | Integer | Amount of time that the oldest contact has been waiting in the queue. |
| estimatedAnsweredWaitTime | Integer | Estimated amount of time that contacts will spend in the queue before being routed to a user. |
| estimatedServiceLevel | Float | Estimated service level of the queue. |
| serviceLevel | Float | Current service level, calculated based on the last 24 contacts routed to the queue. |
| queueKey | Integer | Key of the queue for which this event has been generated. |

Message Example:

```
// QueueRealTimeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "QUEUE_REALTIME_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "abandonedRate" : 10.8,
        "avgAbandonedWaitTime" : 8.0,
        "avgAnsweredWaitTime" : 20.0,
        "queuedContacts" : 1,
        "overflowedContacts" : 0,
        "oldestContactWaitTime" : 4,
        "estimatedAnsweredWaitTime" : 20,
        "estimatedServiceLevel" : 71.2,
        "serviceLevel" : 56.8,

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide


```

"type" : "EVENT",
"data" : {
  "realm" : "REALTIME",
  "type" : "AGGREGATE_REALTIME_EVENT",
  "data" : {
    "queryId" : 28,
    "elements" : [ {
      "abandonedRate" : 10.8,
      "avgAbandonedWaitTime" : 8.0,
      "avgAnsweredWaitTime" : 20.0,
      "queuedContacts" : 1,
      "overflowedContacts" : 0,
      "oldestContactWaitTime" : 4,
      "estimatedAnsweredWaitTime" : 20,
      "estimatedServiceLevel" : 71.2,
      "serviceLevel" : 56.8,
      "aggregateKey" : 1
    } ]
  }
}
}

```

4.9.2.5. ContactRealTimeEvent

Description: event triggered when ContactRealTime information is available, i.e. Contact is queued or being handled by an agent. The monitored resource is the queueKey

| ContactRealTimeEvent Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| ContactRealTimeEvent Data Object | | |
|----------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|-----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| destination | String | Destination to which the contact was sent. |
| uniqueCallId | String | Call Id of the contact. |
| source | String | Source where the contact was generated. |
| contactState | String | Current state of the contact. See definition of possible values at ContactState enum. |
| description | String | Description of the contact. |
| qualifyingAgentsCount | Integer | Number of agents eligible to receive a given call. |
| queueKey | Integer | Database table unique key of the queue entity associated with this contact. |
| timeInState | Integer | Amount of time that the contact has been in its current state. |
| totalWaitTime | Integer | Amount of time that the contact has been waiting in the system. |

| | | |
|------------------------|---------|----------------------------------|
| mediaType | String | Media type of the contact. |
| currentPriority | Integer | Current priority of the contact. |

Message Example:

```
// ContactRealTimeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "CONTACT_REALTIME_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "destination" : "554181022110",
        "uniqueCallId" : "6051567528596712",
        "source" : "554181021119",
        "contactState" : "QUEUED",
        "description" : "General Call",
        "qualifyingAgentsCount" : 2,
        "queueKey" : 1,
        "timeInState" : 1,
        "totalWaitTime" : 1,
        "mediaType" : "VOICE",
        "currentPriority" : 20
      } ]
    }
  }
}
```

4.9.2.6. CallbackRealTimeEvent

Description: event triggered when CallbackRealTime information is available, i.e. Callback is scheduled or being handled by an agent. The monitored resource is the queueKey

| CallbackRealTimeEvent Object | | |
|------------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| CallbackRealTimeEvent Data Object | | |
|-----------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object |
|-----------------|
|-----------------|

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| Attribute name | Attribute type | Description |
|---------------------|----------------|--|
| queueKey | Integer | Database table unique key of the queue. |
| uniqueCallId | String | Call Id of the callback in the system. |
| customerName | String | Name of the customer who is to be called back. |
| description | String | Description associated with the callback. |
| origin | String | Origin of the callback. See definition of possible values at CallbackOrigin enum. |
| state | Integer | Current state of the callback. See definition of possible values at ContactState enum. |
| timeInState | Integer | Amount of time that the callback has been in this state. |
| attemptCount | Integer | Number of callback attempts made. |

Message Example:

```
// CallbackRealTimeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "CALLBACK_REALTIME_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "queueKey" : 1,
        "uniqueCallId" : "C8771567527295009",
        "customerName" : "cb",
        "description" : "desc",
        "origin" : "ORIGIN_DESKTOP",
        "state" : "SCHEDULED",
        "timeInState" : 15,
        "attemptCount" : 1
      } ]
    }
  }
}
```

4.9.2.7. UserCumulativeEvent

Description: event triggered when UserCumulative information is available, usually while the monitored user is logged on a media. The monitored resource is the userKey.

| UserCumulativeEvent Object | | |
|----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| UserCumulativeEvent Data Object | | |
|---------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|----------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |
| userKey | Integer | Database table unique key of the user. |
| utilization | Float | Percentage of the user's logged-on time that was spent handling contacts. |
| offered | Integer | Number of offered and direct contacts that were offered to the user. |
| requeued | Integer | Number of routed contacts that the user requeued. |
| abandonedWhileRinging | Integer | Number of routed contacts which were abandoned while being offered to the user. |
| handled | Integer | Number of routed and direct contacts which were handled by the user. |
| unhandledRouted | Integer | Number of routed contacts that the user transferred directly without requeuing. |
| undeliveredRouted | Integer | Number of routed contacts that were assigned to the user but were not delivered to the user's extension. |
| disconnectedRoutedCalls | Integer | Number of routed contacts that were handled by the user and completed without being transferred or requeued. |
| routedTransferred | Integer | Number of routed contacts that the user transferred directly without requeuing. |
| routedHeld | Integer | Number of routed calls and callbacks that the user placed on hold. |
| routedConsulted | Integer | Number of routed contacts that were consulted out by the user. If the user consulted out more than once during a single contact, the contact is counted only once. |
| totalIdleTime | Integer | Amount of time the user spent in Idle presence state. |
| totalAwayTime | Integer | Amount of time the user spent in Away presence state. |
| totalBusyTime | Integer | Amount of time the user spent in Busy presence state. |
| totalLogonTime | Integer | Amount of time the user spent logged on. |
| totalRoutedTalkTime | Integer | Amount of time the user spent in Talking handling state. |
| totalOtherTime | Integer | Amount of time the user spent in Other handling state. |
| totalRoutedHoldTime | Integer | Amount of time the user spent in Hold handling state. |
| totalPendingTime | Integer | Amount of time the user spent in Pending handling state. |
| totalPostProcessingTime | Integer | Amount of time the user spent in Post-processing handling state. |
| ringingTime | Integer | Total amount of time that the user's extension was ringing for routed or direct contacts (incoming) or listening to the ringing of a dialed extension (outgoing). |
| handlingTime | Integer | Amount of time that the user spent handling routed and direct contacts. |
| maximumRoutedHandlingTime | Integer | Maximum amount of time spent handling a routed contact. |

Message Example:

```
// UserCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "USER_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    "timeInterval" : "2019-09-03T17:15:00Z",
    "userKey" : 3,
    "utilization" : 99.3,
    "offered" : 1,
    "requeue" : 0,
    "abandonedWhileRinging" : 0,
    "handled" : 1,
    "unhandledRouted" : 0,
    "undeliveredRouted" : 0,
    "disconnectedRoutedCalls" : 1,
    "routedTransferred" : 0,
    "routedHeld" : 0,
    "routedConsulted" : 0,
    "totalIdleTime" : 407,
    "totalAwayTime" : 0,
    "totalBusyTime" : 0,
    "totalLogonTime" : 444,
    "totalRoutedTalkTime" : 34,
    "totalOtherTime" : 2,
    "totalRoutedHoldTime" : 0,
    "totalPendingTime" : 2,
    "totalPostProcessingTime" : 0,
    "ringingTime" : 2,
    "handlingTime" : 34,
    "maximumRoutedHandlingTime" : 34
  } ]
}
}
}

```

4.9.2.8. QueueCumulativeEvent

Description: event triggered when QueueCumulative information is available, usually when contacts were enqueued on the monitored queue. The monitored resource is the queueKey.

| QueueCumulativeEvent Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| QueueCumulativeEvent Data Object | | |
|----------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|-----------------|----------------|---|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |

| | | |
|-----------------------------|---------|---|
| receivedContacts | Integer | Number of contacts that were received in the queue. |
| answeredContacts | Float | Number of contacts routed to the queue that were answered. |
| abandonedContacts | Integer | Number of contacts that were abandoned while waiting in the queue or while being offered to the user. |
| redirectedOutOfScope | Integer | Number of contacts received in the queue that were redirected. |
| serviceLevel | Integer | Percentage of contacts routed to the queue that were answered within the site-defined or queue-defined service level. |
| abandonedRate | Integer | Percentage of contacts routed to the queue that were abandoned before being answered. |
| averageWaitTime | Integer | Average amount of time that contacts waited in the queue before being answered, abandoned or redirected. |
| maximumWaitTime | Integer | Maximum amount of time that a contact waited in the queue before being answered, abandoned or redirected. |
| queueKey | Integer | Database table unique key of the queue. |

Message Example:

```
// QueueCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "QUEUE_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "receivedContacts" : 1,
        "answeredContacts" : 0,
        "abandonedContacts" : 1,
        "redirectedOutOfScope" : 0,
        "serviceLevel" : 100.0,
        "abandonedRate" : 100.0,
        "averageWaitTime" : 28.0,
        "maximumWaitTime" : 28,
        "queueKey" : 1
      } ]
    }
  }
}
```

4.9.2.9. GroupCumulativeEvent

Description: event triggered when GroupCumulative information is available, usually while users are logged on a media on the monitored group. The monitored resource is the groupKey.

| GroupCumulativeEvent Object | | |
|-----------------------------|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| | | |
|-------------|--------|--|
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| GroupCumulativeEvent Data Object | | |
|----------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|-------------------------------------|----------------|--|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |
| groupKey | Integer | Database table unique key of the group |
| callsReceived | Integer | Number of contacts that were received by the group. |
| callsOffered | Integer | Number of contacts that were offered to the group. |
| consultOut | Integer | Number of contacts associated with the group that were consulted out by the first answering user. |
| transferOut | Integer | Number of contacts associated with the group that were transferred by the first answering user. |
| receivedHereOfferedElsewhere | Integer | Number of routed contacts that were received in the group, which is the primary group configured to handle these contacts but were offered to another group. |

Message Example:

```
// GroupCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "GROUP_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "timeInterval" : "2019-09-03T18:15:00Z",
        "groupKey" : 1,
        "callsReceived" : 3,
        "callsOffered" : 1,
        "consultOut" : 0,
        "transferOut" : 0,
        "receivedHereOfferedElsewhere" : 0
      } ]
    }
  }
}
```

4.9.2.10. AggregateCumulativeEvent

Description: event triggered when AggregateCumulative information is available, usually when contacts were enqueued on a queue of the monitored aggregate. The monitored resource is the aggregateKey.

| AggregateCumulativeEvent Object |
|---------------------------------|
|---------------------------------|

| Attribute name | Attribute type | Description |
|----------------|----------------|---|
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| AggregateCumulativeEvent Data Object | | |
|--------------------------------------|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|----------------------|----------------|---|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |
| receivedContacts | Integer | Number of contacts that were received in the aggregate. |
| answeredContacts | Float | Number of contacts routed to the aggregate that were answered. |
| abandonedContacts | Integer | Number of contacts that were abandoned while waiting in the aggregate or while being offered to the user. |
| redirectedOutOfScope | Integer | Number of contacts received in the aggregate that were redirected. |
| serviceLevel | Integer | Percentage of contacts routed to the aggregate that were answered within the site-defined or queue-defined service level. |
| abandonedRate | Integer | Percentage of contacts routed to the aggregate that were abandoned before being answered. |
| averageWaitTime | Integer | Average amount of time that contacts waited in the aggregate before being answered, abandoned or redirected. |
| maximumWaitTime | Integer | Maximum amount of time that a contact waited in the aggregate before being answered, abandoned or redirected. |
| aggregateKey | Integer | Database table unique key of the aggregate. |

Message Example:

```
// AggregateCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "AGGREGATE_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "receivedContacts" : 3,
        "answeredContacts" : 1,
        "abandonedContacts" : 2,
        "redirectedOutOfScope" : 0,
        "serviceLevel" : 100.0,
        "abandonedRate" : 66.7,
        "averageWaitTime" : 9.0,
        "maximumWaitTime" : 17,
        "aggregateKey" : 1
      }
    ]
  }
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```

    } ]
  }
}

```

4.9.2.11. UserWrapUpReasonCumulativeEvent

Description: event triggered when UserWrapUpReasonCumulative information is available, usually when the monitored user saves one or more Wrap-up reasons. The monitored resource is the userKey.

| UserWrapUpReasonCumulativeEvent Object | | |
|--|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| UserWrapUpReasonCumulativeEvent Data Object | | |
|---|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|-----------------|----------------|---|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |
| wrapUpReasonKey | Integer | Database table unique key of the wrapup reason. |
| count | Integer | Number of objects UserWrapUpReasonCumulativeElement. |
| userKey | Integer | Database table unique key of a queue. |

Message Example:

```

// UserWrapUpReasonCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "USER_WRAPUPREASON_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "wrapUpReasonKey" : 1,
        "count" : 4,
        "userKey" : 4,
      }, {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "wrapUpReasonKey" : 2,
        "count" : 2,
        "userKey" : 4,
      } ]
    }
  }
}

```

4.9.2.12. QueueWrapUpReasonCumulativeEvent

Description: event triggered when QueueWrapUpReasonCumulative information is available, usually when Wrap-up reason is saved on a contact which was enqueued on the monitored queue. The monitored resource is the queueKey.

| QueueWrapUpReasonCumulativeEvent Object | | |
|---|----------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType. |
| data | Object | Content of the event. See following data Object definition. |

| QueueWrapUpReasonCumulativeEvent Data Object | | |
|--|-------------------------|---|
| Attribute name | Attribute type | Description |
| queryId | Integer | Identification of the query for which this event is being reported. |
| elements | List of Elements Object | List of the elements which are being reported. |

| Elements Object | | |
|-----------------|----------------|---|
| Attribute name | Attribute type | Description |
| timeInterval | String | Time range that specifies the start of the 15-minute period to which it refers. |
| wrapUpReasonKey | Integer | Database table unique key of the wrapup reason. |
| count | Integer | Number of objects QueueWrapUpReasonCumulativeElement. |
| queueKey | Integer | Database table unique key of a queue. |

Message Example:

```
// QueueWrapUpReasonCumulativeEvent Object
{
  "type" : "EVENT",
  "data" : {
    "realm" : "REALTIME",
    "type" : "QUEUE_WRAPUPREASON_CUMULATIVE_EVENT",
    "data" : {
      "queryId" : 28,
      "elements" : [ {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "wrapUpReasonKey" : 1,
        "count" : 4,
        "queueKey" : 4,
      }, {
        "timeInterval" : "2019-09-03T17:45:00Z",
        "wrapUpReasonKey" : 2,
      }
    ]
  }
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

| OnServerDisconnectedEvent Object | | |
|---|-----------------------|---|
| Attribute name | Attribute type | Description |
| realm | String | Domain of the contact center for which the event is being reported. See definition of possible values at Realm. |
| type | String | Identification of the event. See definition of possible values at EventType |
| data | Object | Content of the event. See following data Object definition. |

| OnServerDisconnectedEvent Data Object | | |
|--|-----------------------|---|
| Attribute name | Attribute type | Description |
| serverName | String | Name of the server which has been disconnected. |

Message Example:

```
//OnServerDisconnectedEvent Object
{
  "type" : "EVENT",
  "data" :
  {
    "realm" : "REALTIME",
    "type" : "SERVER_DISCONNECTED_EVENT",
    "data" :
    {
      "serverName" : "6007:10.81.3.116"
    }
  }
}
```

5. Definitions

CallbackOrigin

```
{  
ORIGIN_NONE,  
ORIGIN_IVR,  
ORIGIN_DESKTOP,  
ORIGIN_WEBCOLLABORATION,  
ORIGIN_ABANDONED,  
ORIGIN_OUTBOUND,  
ORIGIN_SDK,  
ORIGIN_FLOW,  
ORIGIN_ALL,  
ORIGIN_VIRTUALAGENT  
}
```

CallbackResultType

```
{  
SUCCESS,  
RETRY,  
DELETED,  
MAXRESULTTYPE  
}
```

CallbackScheduleStatus

```
{  
UNDEFINED,  
EXPIRED,  
ACTIVE,  
FUTURE  
}
```

CallbackStatus

```
{  
CALLBACKSTATUS_NEW,  
CALLBACKSTATUS_RETRY,  
CALLBACKSTATUS_SUSPENDED,  
CALLBACKSTATUS_SCHEDULED,  
CALLBACKSTATUS_ENQUEUED,  
CALLBACKSTATUS_OFFERED,  
CALLBACKSTATUS_ACCEPTED,  
CALLBACKSTATUS_FAILED,  
CALLBACKSTATUS_CALLING,  
CALLBACKSTATUS_CONNECTED,  
CALLBACKSTATUS_DISCONNECTED,  
CALLBACKSTATUS_COMPLETED,  
CALLBACKSTATUS_EXPIRED,  
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
CALLBACKSTATUS_MAXRETRY,  
CALLBACKSTATUS_TIMEOUT,  
CALLBACKSTATUS_DELETED,  
CALLBACKSTATUS_RECOVERING,  
CALLBACKSTATUS_UNKNOWN,  
CALLBACKSTATUS_INVALID  
}
```

CallState

```
{  
START,  
CALLING,  
QUEUED,  
CONNECTED,  
CONSULTING,  
CONFERENCING,  
HOLDING,  
FINISHED,  
NOCALLSTATE  
}
```

CallType

```
{  
EXT2ACD,  
INT2ACD,  
EXT2INT,  
INT2INT,  
INT2EXT,  
CONFERENCE,  
NOVALUE,  
UNKNOWN  
}
```

ContactState

```
{  
INVALIDSTATE,  
PROCESSING,  
QUEUED,  
PENDING,  
RESERVED,  
HANDLED,  
DEFERRED,  
EXTERNALEMAILCONSULT,  
MEDIASUSPENDED,  
UNANSWERED,  
SCHEDULED,  
IVRSUSPENDED,  
NETWORKSUSPENDED,  
POSTPROCESSING  
}
```

ContactType

```
{  
NONE,  
ROUTED_VOICE,  
DIRECT_INCOMING_VOICE,  
DIRECT_OUTGOING_VOICE,  
DIRECT_INTERNAL_VOICE,  
ROUTED_CALLBACK,  
ROUTED_EMAIL,  
DIRECT_OUTGOING_EMAIL,  
ROUTED_WEBCHAT,  
UNKNOWN_VOICE,  
ROUTED_OPENMEDIA,  
DIRECT_OUTGOING_OPENMEDIA,  
CONTACT_TYPE_MAX  
}
```

DeliveredReasons

```
{  
UNDEFINED,  
INITIAL_ARRIVAL,  
NORMAL,  
REQUEUED,  
CONFERENCED  
}
```

DequeueReasons

```
{  
NONE,  
REQUESTFROMWEBSERVER,  
REQUESTFROMEMAILSERVER,  
WEBCOLLABORATIONCONNECTFAILED,  
SYSTEMERROR,  
CALLANSWERED,  
CALLABANDONED,  
CALLTIMEDOUT,  
WORKFLOWTRANSFER  
}
```

DisconnectReasons

```
{  
UNDEFINED(0),  
AGENT_REPLIED(1),  
AUTO_RESPONDED(2),  
DISCARDED(3),  
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
TIMED_OUT(4),
CRITICAL_SERVER_DOWN(5),
TRANSFERRED_OUT(6),
NORMAL(101),
FAILED_TO_START_WORKFLOW(102),
ABANDONED_IN_WORKFLOW(103),
ABANDONED_IN_QUEUE(104),
TIMED_OUT_IN_QUEUE(105),
ABANDONED_WHILE_PENDING(106),
BROWSER_TIMED_OUT(108),
AGENT_DELETED(110),
WORKFLOW_DISCONNECT(111),
SHUTTING_DOWN(112),
SESSION_EXPIRED(114)
}
```

DivertReasons

```
{
UNDEFINED(0),
DEFER_TAKE_BACK(1),
NO_ANSWER(2),
ROUTING_TIMED_OUT(3),
EXTERNAL_CONSULT_REPLY(4),
EXTERNAL_CONSULT_TAKE_BACK(5),
SYSTEM_ROUTED(101),
INVITATION_REJECTED(102),
INVITATION_TIMED_OUT(103),
ABANDONED_WHILE_PENDING(105),
DISCONNECTED_WHILE_PENDING(106)
}
```

ErrorCode

```
{
NO_ERROR(0),
GENERAL_ERROR(1),
ALREADY_REGISTERED_ON(2),
CLIENT_NAME_NOT_FOUND(3),
AUTH_STATEMENT_NOT_VALID(4),
NOT_READY(5),
NOT_ENABLED(6),
CLIENT_TOKEN_NOT_FOUND(7),
APPLICATION_NOT_REGISTERED(8),
WRONG_API_REQUEST(9),
PARAMETER_LENGTH_TOO_LONG(10),
WRONG_DATE_FORMAT(11),
INVALID_BUSINESS_UNIT_NAME(12),
EMPTY_PARAMETER(13),
INVALID_CHARACTERS(14),
NEGATIVE_PARAMETER(15),
}
```

```
PRESENCE_ACTION_SUCCEED(16),
PRESENCE_ACTION_FAILED(17),
TELEPHONY_INVALID_EXTENSION(18),
TELEPHONY_RESOURCEBUSY(19),
TELEPHONY_RESOURCEERROR(20),
TELEPHONY_OUTOFSERVICE(21),
TELEPHONY_LINEBUSY(22),
TELEPHONY_UNMONITOREDEXTENSION(23),
TELEPHONY_REQUESTTIMEOUT(24),
TELEPHONY_CSTA_CAP_NOT_SUPPORTED(25),
TELEPHONY_CAP_DISCONNECT_NOT_SUPPORTED(26),
TELEPHONY_CAP_DEFLECT_NOT_SUPPORTED(27),
TELEPHONY_INCOMPATIBLE_OBJECT(28),
TELEPHONY_VALIDATIONCALLBACKFAILED(29),
TELEPHONY_GENERIC_FRAMEWORK_ERROR(30),
TELEPHONY_FW_ERROR_INVALID_SERVER_NAME(31),
TELEPHONY_STATEERROR(32),
TELEPHONY_EXCEEDLIMIT(33),
TELEPHONY_TOOMANYAGENTS(34),
TELEPHONY_VALIDATIONFAILED(35),
TELEPHONY_NETWORKBUSY(36),
TELEPHONY_SERVERNOTREADY(37),
ADMIN_QUERYUSER_FAILED(50),
ADMIN_INVALID_BUSSINESUNIT_TO_LOGON(51),
ADMIN_INVALID_CREDENTIALS_TO_LOGON(52),
NO_LICENSE_AVAILABLE(60)
CALLBACK_ERROR(80),
CALLBACK_INVALIDEXT(81),
CALLBACK_ACCEPT_FAILED(82),
CALLBACK_COMPLETE_FAILED(83),
CALLBACK_DELETE_FAILED(84),
WEB_INTERACTION_ERROR(100),
OPENMEDIA_ERROR(120),
REALTIME_ERROR(140)
}
```

EventAction

```
{
UNKNOWN,
ADD,
UPDATE
}
```

EventCause

```
{
NULL(0),
ACTIVE_MONITOR(1),
ALTERNATE(2),
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

BUSY(3),
CALLBACK(4),
CALL_CANCELLED(5),
CALL_FORWARD_ALWAYS(6),
CALL_FORWARD_BUSY(7),
CALL_FORWARD_NO_ANSWER(8),
CALL_FORWARD(9),
CALL_NOT_ANSWERED(10),
CALL_PICKUP(11),
CAMP_ON(12),
DEST_NOT_OBTAINABLE(13),
DO_NOT_DISTURB(14),
INCOMPATIBLE_DESTINATION(15),
INVALID_ACCOUNT_CODE(16),
KEY_CONFERENCE(17),
LOCKOUT(18),
MAINTENANCE(19),
NETWORK_CONGESTION(20),
NETWORK_NOT_OBTAINABLE(21),
NEW_CALL(22),
NO_AVAILABLE_AGENTS(23),
OVERRIDE(24),
PARK(25),
OVERFLOW(26),
RECALL(27),
REDIRECTED(28),
REORDER_TONE(29),
RESOURCE_NOT_AVAILABLE(30),
SILENT_MONITOR(31),
TRANSFER(32),
TRUNK_BUSY(33),
VOICE_UNIT_INITIATOR(34),
BLOCKED(35),
CHARACTER_COUNT_REACHED(36),
CONSULTATION(37),
DISTRIBUTED(38),
DTMF_DIGIT_DETECTED(39),
DURATION_EXCEEDED(40),
END_OF_MESSAGE_DETECTED(41),
ENTERING_DISTRIBUTION(42),
FORCED_PAUSE(43),
MAKE_CALL(44),
MESSAGE_SIZE_EXCEEDED(45),
NETWORK_SIGNAL(46),
NEXT_MESSAGE(47),
NORMAL_CLEARING(48),
NO_SPEECH_DETECTED(49),
NUMBER_CHANGED(50),
CSTA_SINGLE_STEP_CONFERENCE(51),
CSTA_SINGLE_STEP_TRANSFER(52),
SPEECH_DETECTED(53),
SWITCHING_FUNCTION_TERMINATED(54),

TERMINATION_CHARACTER_RECEIVED(55),
TIMEOUT(56),
ACD_BUSY(57),
ACD_FORWARD(58),
ACD_SATURATED(59),
ALERT_TIME_EXPIRED(60),
AUTO_WORK(61),
CAMP_ON_TRUNKS(62),
CONFERENCE(63),
DEST_DETECTED(64),
DEST_OUT_OF_ORDER(65),
DISTRIBUTION_DELAY(66),
FORCED_TRANSITION(67),
INTRUDE(68),
INVALID_NUMBER_FORMAT(69),
JOIN_CALL(70),
KEY_OPERATION_IN_USE(71),
MAKE_PREDICTIVE_CALL(72),
MESSAGE_DURATION_EXCEEDED(73),
MULTIPLE_ALERTING(74),
MULTIPLE_QUEUING(75),
NETWORK_DIALING(76),
NETWORK_OUT_OF_ORDER(77),
NORMAL(78),
NOT_AVAILABLE_BEARER_SERVICE(79),
NOT_SUPPORTED_BEARER_SERVICE(80),
NUMBER_UNALLOCATED(81),
QUEUE_CLEARED(82),
REMAINS_IN_QUEUE(83),
RESERVED(84),
SELECTED_TRUNK_BUSY(85),
SUSPEND(86),
UNAUTHORIZED_BEARER_SERVICE(87),
CSTA_SOFT_HOLD(95),
CSTA_HARD_HOLD(96),
CSTA_LINE_HOLD(97),
BACKGROUND_HOLD(98),
EXCLUSIVE_HOLD(99),
RECALL_FORWARDED(100),
RECALL_BUSY(101),
RECALL_NO_ANSWER(102),
RECALL_RESOURCES_NOT_AVAILABLE(103),
BUSY_OVERFLOW(104),
CALENDAR_OVERFLOW(105),
CAPACITY_OVERFLOW(106),
PATH_REPLACEMENT(107),
QUEUE_TIME_OVERFLOW(108),
UNKNOWN_OVERFLOW(109)
}

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

EventType

```
{
  USER_HANDLING_STATE,
  USER_ROUTING_STATE,
  USER_MEDIA_NOTREADY,
  USER_MEDIA_READY,
  USER_MEDIA_STATE,
  // Telephony
  DELIVERED_EVENT,
  DISCONNECTED_EVENT,
  HOLD_EVENT,
  CONSULT_EVENT,
  QUEUED_EVENT,
  ESTABLISHED_EVENT,
  DIVERTED_EVENT,
  HELD_EVENT,
  RETRIEVED_EVENT,
  CONFERENCED_EVENT,
  FAILED_EVENT,
  SERVER_CONNECTED_EVENT,
  SERVER_DISCONNECTED_EVENT,
  ORIGINATED_EVENT,
  SERVICE_INITIATED_EVENT,
  TRANSFERRED_EVENT,
  PROCESS_TRANSFERRING_EVENT,
  PROCESS_TRANSFERRED_EVENT,
  NETWORKREACHED_EVENT,
  SERVICES_ENABLED_EVENT,
  // Admin
  AGGREGATE_UPDATED_EVENT,
  DEPARTMENT_UPDATED_EVENT,
  GROUP_UPDATED_EVENT,
  POSTPROCESSINGREASON_UPDATED_EVENT,
  QUEUE_UPDATED_EVENT,
  UNAVAILBLEREASON_UPDATED_EVENT,
  WORKREASON_UPDATED_EVENT,
  WRAPUPREASON_UPDATED_EVENT,
  USER_UPDATED_EVENT,
  AGGREGATE_DELETED_EVENT,
  DEPARTMENT_DELETED_EVENT,
  GROUP_DELETED_EVENT,
  POSTPROCESSINGREASON_DELETED_EVENT,
  QUEUE_DELETED_EVENT,
  UNAVAILBLEREASON_DELETED_EVENT,
  WORKREASON_DELETED_EVENT,
  WRAPUPREASON_DELETED_EVENT,
  USER_DELETED_EVENT,
  // Routing
  ASSIGN_CALL_EVENT,
  UNASSIGN_CALL_EVENT,
```

```

ENQUEUE_CALL_EVENT,
DEQUEUE_CALL_EVENT,
ROUTING_INFORMATION_UPDATED_EVENT,
TIMEOUT_CALL_EVENT
// Callback
DELIVERED_CALLBACK_EVENT,
MAKECALLFAILED_CALLBACK_EVENT,
DIVERTED_CALLBACK_EVENT,
NEW_CALLBACKS_LIST_EVENT,
// Callback/Admin
CALLBACK_RETRYREASON_UPDATED_EVENT,
CALLBACK_RETRYREASON_DELETED_EVENT,
CALLBACK_DELETEREASON_UPDATED_EVENT,
CALLBACK_DELETEREASON_DELETED_EVENT,
// WebInteraction
DIVERTED_WEB_CHAT_EVENT,
DELIVERED_WEB_CHAT_EVENT,
ESTABLISHED_WEB_CHAT_EVENT,
CONFERENCED_WEB_CHAT_EVENT,
DISCONNECTED_WEB_CHAT_EVENT,
CONTENT_WEB_CHAT_EVENT,
CALL_ME_ANSWER_WEB_CHAT_EVENT
// OpenMedia/Admin
OPENMEDIA_DISCARDREASON_UPDATED_EVENT,
OPENMEDIA_DISCARDREASON_DELETED_EVENT,
// OpenMedia
DELIVERED_OPENMEDIA_EVENT,
DISCONNECTED_OPENMEDIA_EVENT,
DIVERTED_OPENMEDIA_EVENT,
ESTABLISHED_OPENMEDIA_EVENT,
DEFERRED_OPENMEDIA_EVENT,
RESUMED_OPENMEDIA_EVENT,
TRANSFERRED_OPENMEDIA_EVENT,
CONTENT_ADDED_OPENMEDIA_EVENT,
STREAM_RESPONSE_OPENMEDIA_EVENT
}

```

HandlingStates

```

{
NONE,
PENDING,
DIALING,
BUSY,
RINGING,
CONNECTED,
QUEUED,
ONHOLD,
CONSULTING,

```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
PROCESSING,  
POSTPROCESSING,  
UNKNOWN  
}
```

HoldReasons

```
{  
UNDEFINED,  
AGENT_DEFER,  
AUTO_DEFER,  
EXTERNAL_CONSULT  
}
```

LCSType

```
{  
NULL,  
INITIATE,  
ALERTING,  
CONNECTED,  
HOLD,  
QUEUED,  
FAIL  
}
```

LineResourceType

```
{  
AGENTEXTENSION,  
IVREXTENSION,  
AGENTACD,  
AGENTRCG,  
REQUEUE,  
BASICACD,  
BASICRCG,  
TRANSFERACD,  
BOUNCEACD,  
BOUNCERCG,  
NETWORKTRANSITNUMBER,  
IVRACD,  
IVRRCG,  
IVRTRUNKID,  
UNKNOWN,  
UNMONEXTENSION,  
UNMONTRUNK,  
UNMONACD,  
UNMONRCG,  
TRUNKGROUP,  
MONITOREDTRUNK,  
IVRTRANSITNUMBER,  
NORESOURCETYPE,  
ROUTINGERRORNUMBER,  
}
```

```
ROUTINGTRANSFERNUMBER,  
SERVICENUMBER,  
TRANSITIONHUNTGROUP  
}
```

LineResourceTypes

```
{  
AGENTEXTENSION,  
IVREXTENSION,  
ACDGROUP,  
BASICRCG,  
REQUEUE,  
BASICACDGROUP,  
TRANSFERACDGROUP,  
LBACDGROUP,  
LBRCCGROUP,  
NETWORKTRANSITNUMBER,  
IVRACDGROUP,  
IVRRCG,  
IVRTRUNKID,  
AGENTRCG,  
TRUNKGROUP,  
TELEPHONYSOURCE,  
EMAILSOURCE,  
CHATSOURCE,  
TELDESTINATION,  
TELEXTERNALDESTINATION,  
EMAILDESTINATION,  
CHATDESTINATION,  
CALLDIRECTORINTERACTIVEEXTENSION,  
CALLDIRECTORANNOUNCEMENTEXTENSION,  
IVRWFEXTENSION,  
IVRTRANSITNUMBER,  
QUEUE,  
OPENMEDIASOURCE,  
MAXRESOURCETYPES  
UNKNOWN,  
ROUTINGERRORNUMBER,  
ROUTINGTRANSFERNUMBER,  
SERVICENUMBER,  
TRANSITIONHUNTGROUP  
}
```

LineState

```
{  
IDLE,  
DIALING,  
BUSY,  
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
RINGING,  
CONNECTED,  
QUEUED,  
ONHOLD,  
CONSULTING,  
OUTOFSERVICE,  
UNKNOWN  
}
```

LineType

```
{  
ANALOG,  
DIGITAL,  
OTHER,  
UNKNOWNTYPE  
}
```

MediaState

```
{  
LOGOFF,  
LOGON,  
AVAILABLE,  
DO_NOT_DISTURB,  
UNKNOWN  
}
```

MediaType

```
{  
NONE,  
VOICE,  
CALLBACK,  
EMAIL,  
WEB_COLLABORATION,  
OPENMEDIA,  
MAXMEDIUM  
}
```

MessageType

```
{  
EVENT,  
REQUEST  
}
```

OpenMediaCommitter

```
{  
UNKNOWN,  
CUSTOMER,  
}
```

```
AGENT
}
```

OpenMediaDeferReason

```
{
  UNDEFINED,
  AGENTDEFER,
  AUTODEFER,
  EXTERNALCONSULT
}
```

OpenMediaDisconnectReason

```
{
  UNDEFINED,
  AGENTREPLIED,
  AUTORESPONDED,
  DISCARDED,
  TIMEDOUT,
  CRITICALSERVERDOWN,
  TRANSFERREDOUT,
  SENT
}
```

OpenMediaDivertReason

```
{
  UNDEFINED,
  DEFERTAKEBACK,
  RNA,
  ROUTINGSERVERTIMEOUT,
  EXTERNALCONSULTREPLY,
  EXTERNALCONSULTTAKEBACK
}
```

OpenMediaResumeReason

```
{
  UNDEFINED,
  DEFERRESUMED,
  EXTERNALCONSULTRESUMED,
  RECOVERY
}
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

OpenMediaTransferReason

```
{  
UNDEFINED,  
NORMAL,  
MONITOR  
}
```

OpenMediaTransferTarget

```
{  
UNDEFINED,  
RESERVEFORAGENT,  
QUEUE  
}
```

PartyTypes

```
{  
UNKNOWN,  
EXTERNAL,  
INTERNAL,  
AGENT,  
TRUNK,  
RCG,  
QUEUE,  
IVR  
}
```

PresenceStates

```
{  
IDLE,  
AWAY,  
BUSY,  
ACTIVE,  
LOGGEDOFF,  
UNKNOWN  
}
```

Realm

```
{  
ADMINISTRATION,  
PRESENCE,  
TELEPHONY,  
REALTIME,  
STATISTIC,  
CALLBACK,  
ROUTING,  
WEB_INTERACTION,  
OPENMEDIA
```

```
}
```

RealTimeQueryType

```
{  
  USER_REALTIME,  
  QUEUE_REALTIME,  
  GROUP_REALTIME,  
  AGGREGATE_REALTIME,  
  CONTACT_REALTIME,  
  CALLBACK_REALTIME,  
  USER_CUMULATIVE,  
  QUEUE_CUMULATIVE,  
  GROUP_CUMULATIVE,  
  AGGREGATE_CUMULATIVE,  
  USER_WRAPUP_REASON_CUMULATIVE,  
  QUEUE_WRAPUP_REASON_CUMULATIVE,  
  AGGREGATE_WRAPUP_REASON_CUMULATIVE  
}
```

RoutingStates

```
{  
  AVAILABLE,  
  UNAVAILABLE,  
  WORK,  
  LOGGEDOFF,  
  UNKNOWN  
}
```

SBRCallState

```
{  
  ABANDONED,  
  ANSWERED,  
  DEQUEUED,  
  HOLDING,  
  ICAQUEUED,  
  NONE,  
  ORPHANED,  
  PENDING,  
  QUEUED,  
  SUSPENDED,  
  TIMEDOUT,  
  QUEUEDETERMINATION,  
  QUEUEDPAUSEASSIGNMENT,  
  NETWORKSUSPENDED  
}
```

ServerConnectionState

```
{
```

A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide

```
UNKNOWN,  
DISCONNECTED,  
CONNECTED  
}
```

ServerState

```
{  
UNKNOWN,  
UNAVAILABLE,  
PARTIALLY_AVAILABLE,  
AVAILABLE  
}
```

UnavailableReasonType

```
{  
UNAVAILABLE_TYPE,  
WORK_TYPE,  
UNKNOWN  
}
```

UnavailableReasonType

```
{  
UNAVAILABLE_TYPE,  
WORK_TYPE,  
UNKNOWN  
}
```

UserType

```
{  
ASSOCIATE_A,  
SUPERVISOR,  
ADMINISTRATOR,  
MASTER,  
SERVICE,  
ASSOCIATE_E,  
BASIC,  
CRM,  
MAXUSERTYPE  
}
```

WebCollaborationChatCommitter

```
{  
CUSTOMER,  
AGENT,  
SYSTEM  
}
```

WebCollaborationDeliveredReason

```
{  
NONE,  
INITIAL_ARRIVAL,  
NORMAL_ASSIGNMENT,  
REQUEUE_ASSIGNMENT,  
CONFERENCE  
}
```

WebCollaborationDisconnectReason

```
{  
UNDEFINED,  
NORMAL_DISCONNECT,  
FAILED_TO_START_WORKFLOW,  
ABANDONED_IN_WORKFLOW,  
ABANDONED_IN_QUEUE,  
TIMEDOUT_IN_QUEUE,  
ABANDONED_WHILE_PENDING,  
TRANSFERRED_OUT_OF_HPPC,  
BROWSER_TIMEOUT,  
MANAGER_DELETE_AGENT,  
WORKFLOW_DISCONNECT,  
SHUTTING_DOWN,  
SESSION_EXPIRED,  
ADMIN_DOWN,  
WATCHDOG_DOWN,  
FEATURE_DISABLED  
}
```

WebCollaborationDivertReason

```
{  
UNDEFINED,  
HPPCR,  
INVITATION_REJECTED,  
INVITATION_TIMEOUT,  
UNANSWERED,  
ABANDONED_WHILE_PENDING,  
DISCONNECT_WHILE_PENDING  
}
```

HotStandbyState

```
{  
UNKNOWN,  
ACTIVE,  
STANDBY  
}
```


A31003-S22C0-R102-02-7620, 02/2026

OpenScape Contact Center Enterprise V12, REST SDK Framework, Programming Guide


6. Scenarios with High Availability

In a High Availability scenario the REST SDK application can be connected to a redundant OSCC. In this scenario, the Application Server instance(s) must be deployed in a separate machine from the OSCC nodes. A redundant system can also have redundant Application Server instances to provide the REST SDK web service. Finally, the OSCC can also be connected to a redundant Communication Platform like OSV.

This is the recommended architecture:




Alternative architecture – Each Application Server will point to one of the OSCC nodes, which means that each Application Server will be tied to one of the OSCC nodes – this is not recommended because if the Application Server which is connected to the active OSCC node fails, there is no way to enforce the OSCC to switchover to the other node.




6.1. Redundant OpenScope Voice

The OSV provides High Availability in an Active-Active approach. The OSCC connects to OSV via CSTA and the determination of the node preference is performed via DNS SRV. This means that the OSCC is normally connected to one of the OSV nodes. If the OSV node to which the OSCC is connected to fails, the OSCC will connect to the other OSV node. This process shall be transparent to the connection between the REST SDK Application and Application Server.

In normal conditions, the OSCC Active and OSCC Standby nodes are pointing to OSV 1 node.



If the OSV 1 node fails, both OSCC nodes will re-connect to OSV 2.



The CSTA connection between OSCC and OSV should switch from OSV 1 node to OSV 2 node in two situations:

- There network between OSCC and OSV 1 node has a problem.
- The OSV 1 node is out of service.

In case of a switchover from OSV 1 node to OSV 2 node, the following consequences will be noticed:

A31003-S22C0-R102-02-7620, 02/2026

OpenScope Contact Center Enterprise V12, REST SDK Framework, Programming Guide

- The connection between the REST SDK Application and the Application Server remains unchanged.
- The connection between the Application Server and OSCC remains unchanged.
- The calls which are in queue are disconnected by OSV – this only happens if the OSV fails and it does not happen in the case of network failure. A Dequeue Call Routing Event shall be reported for each disconnected queued call.

Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the list of Call IDs for each queue with GetQueueData.

- The agents are logged off – this is indicated by a User Media Not Ready Presence Event for Voice which is sent when the switchover of the OSV nodes happens.


Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the agent state by sending a GetRoutingState request for each agent.

- The Real Time Statistics are not impacted.


6.2. Redundant OSCC

The OSCC High Availability implementation is based on the Windows Cluster feature. The Windows Cluster provides a unique IP Address which will point to the active OSCC node. It is recommended that each Application Server will point to the Cluster IP address, what means that each Application Server shall connect to the active OSCC node – this is the recommended architecture, since the redundancy of the Application Server is independent from the redundancy of the OSCC.

In normal conditions, the Application Server(s) is(are) pointing to the Cluster IP address assigned to the active OSCC 1 node.



If a switchover is executed in OSCC, the Cluster IP is assigned to the new active OSCC 2 node.



When a switchover occurs in the OSCC, the following situations are verified in the system:

- The Application Server temporarily loses the connection to OSCC. The Application Server keeps trying to connect to OSCC by pointing to the IP address of the OSCC Cluster. When the switchover is completed the Application Server is automatically connected to the new active OSCC.
- The REST SDK Application remains connected to the Application Server.
- The event monitoring (started via ListenForEvents commands) is kept by the Application Server and is not affected by the OSCC switchover.
- The agents are logged off.

Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the agent state by sending a GetRoutingState request for each agent.

- During the switchover process, a SERVER_DISCONNECTED_EVENT is reported for the Telephony Server, for the Presence Server, for the Routing Server, for the Callback Server, for the Web Collaboration Server and for the OpenMedia Server. The Presence server also reports a USER_MEDIA_NOTREADY for each of the monitored media. These events shall be used by the REST SDK Application to indicate that a switchover happened.
- When the new active OSCC node gets back in service, the REST SDK application will start receiving a SERVER_CONNECTED_EVENT for each of the OSCC services.
- When a SERVER_CONNECTED_EVENT for the Presence Server is received by the REST SDK application, it shall start logging on the agents back.
- For each of the calls which were in queue during the switchover process, the REST SDK application will receive:
 - A Telephony QUEUED event.
 - A Routing ENQUEUE_CALL event and
 - A Routing ROUTING_INFORMATION_UPDATED event.


Note: the queued calls are recovered with minimal data and information like Calling Party Number are not recovered.

Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the list of Call IDs for each queue with GetQueueData.

- The Real Time Statistics are lost and must be restarted.

Note 1: Currently, it is not possible to get the routing status of the agents. We recommend re-defining the agent logon and routing status after a recovery situation happens.


Note 2: Currently, it is not possible to get the call id of the calls waiting in the queue. We recommend getting statistical data about the queue with the Real Time Statistics and waiting for the calls to be handled.




6.3. Redundant Application Server

The Application Server can be deployed in a Hot Standby approach, which means that only one Application Server will be running at a time. In this scenario, the REST SDK Application must manage the connection to the active Application Server node. As soon as the REST SDK Application detects that the Application Server is not accessible, it shall start working with the new active Application Server node.

In normal conditions, the REST SDK Application must be registered to both the Application Servers nodes. The REST SDK Application must choose one of the Application Server nodes to be the active node. In the example below the Application Server 1 was chosen to be the active node.



If the REST SDK Application identifies that the active Application Server 1 fails, it shall start working with the Application Server 2 which becomes the active node.



If the REST SDK Application cannot access the Application Server, the reason can be:

- There is a network problem between the REST SDK Application and the Application Server.
- The Application Server is out of service.

The problem can be detected by any not responded REST SDK request which is sent by the REST SDK Application.

The REST SDK may try to register to the former standby Application Server but the registration may fail if the previously used connection was not disconnected in the OSCC yet. The OSCC may take up to 180 seconds (3 minutes) to detect that the connection to the Application Server was lost. Two approaches are possible to reconnect via the former standby Application Server:

- The REST SDK Application tries to register to the same Application Id as was used before. It can take up to 3 minutes to release this application in the OSCC.
- The REST SDK Application uses a second Application Id to connect to the second Application Server. This approach requires a second REST SDK license.

Independent of the approach to reconnect the REST SDK Application to the servers, the REST SDK Application is impacted by:

- The event monitoring (started via ListenForEvents commands) is lost for all server/media and must be re-sent by the REST SDK Application.
- The agents remain logged on and the Routing State also remains the same as before the problem with the Application Server.

Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the agent state by sending a GetRoutingState request for each agent.

- The ongoing contacts are not impacted.

Starting with OpenScape Contact Center V11R1 FR6, it is recommended to get the list of Call IDs for each queue with GetQueueData.

- The Real Time Statistics are lost and must be restarted.

6.4. Redundant REST SDK Application

The definition of a redundant REST SDK Application is out of the scope of this document.

A session token which was generated for an instance of the REST SDK Application shall not be used by another instance of the REST SDK Application. However, the only REST SDK command which matches the originator of a command to the session token is the Keep Alive. This means that if an instance of a REST SDK Application is registered and it fails, another instance of the REST SDK Application could re-use the session token, except for the Keep Alive messages. The REST SDK events which are sent to the REST SDK Application via the webhook must be distributed to a pre-defined IP address by for example using a Load Balancer.

