

Installation Sprachanalyse-Software von EML Windows-Version 1.4



Installationsanleitung für Systembetreiber

13.11.2019

Originalanleitung

Produktlinie neo, Version 6.x

Die beschriebenen Funktionen können mit folgenden ASC-Produkten verwendet werden:

EVOIPneo

EVOLUTIONneo / XXL / eco

EVOflex (länderspezifisch)

Im Partnerbereich unserer Webseite <http://www.asctechnologies.com> finden Sie immer die aktuellsten technischen Dokumente und Produktaktualisierungen.

Copyright © 2019 ASC Technologies AG. Alle Rechte vorbehalten.

Windows ist ein eingetragenes Markenzeichen der Microsoft Corporation. VMware® ist ein eingetragenes Markenzeichen von VMware, Inc. Alle anderen hier erwähnten Marken und Produktnamen sind das Eigentum ihrer jeweiligen Inhaber.

Inhaltsverzeichnis

1	Allgemeine Hinweise	4
2	Einleitung	5
3	Installation	6
3.1	EML Transcription Server Version Windows 1.4.pdf.....	7

Allgemeine Hinweise

ASC steht im Kontext dieses Dokuments für die ASC Technologies AG, deren Tochtergesellschaften, Niederlassungen und Vertriebsbüros. Deren aktuelle Übersicht kann auf der Webseite unter <https://www.asctechnologies.com> eingesehen werden.

ASC übernimmt keinerlei Gewähr für die Aktualität, Korrektheit, Vollständigkeit oder Qualität der in den Anleitungen bereitgestellten Informationen.

ASC kontrolliert regelmäßig den Inhalt der veröffentlichten Anleitungen auf Übereinstimmung mit der beschriebenen Hard- und Software. Dennoch können Abweichungen nicht ausgeschlossen werden. Notwendige Korrekturen sind in den nachfolgenden Auflagen enthalten.

Einige Aspekte der ASC-Technologie werden in allgemeiner Form beschrieben, um das Eigentum und die vertraulichen Informationen und/oder Geschäftsgeheimnisse von ASC zu schützen.

Die Softwareprogramme und Anleitungen von ASC sind urheberrechtlich geschützt. Alle Rechte an den Anleitungen sind vorbehalten, auch die der Reproduktion und/oder Vervielfältigung in jeglicher Form, sei es fotomechanisch, drucktechnisch oder auf digitalen Datenträgern. Dies gilt auch für Übersetzungen. Nachdruck der Anleitungen, vollständig oder auszugsweise, ist nur mit schriftlicher Genehmigung von ASC gestattet.

Maßgebend ist, soweit nicht anders angegeben, der technische Stand zum Zeitpunkt der Auslieferung von Software, Geräten und Anleitungen durch ASC. Technische Änderungen ohne gesonderte Ankündigung bleiben vorbehalten. Bisherige Anleitungen verlieren ihre Gültigkeit.

Es gelten die Allgemeinen Verkaufs- und Lieferbedingungen von ASC in ihrer jeweils gültigen Fassung.

Diese Anleitung beschreibt die Installation der Audioanalysesoftware EML Transcription Server der Firma EML für Windows-Betriebssysteme zur Nutzung mit dem neo-Aufzeichnungssystem.

EML Transcription Server ermöglicht die Transkription zur Übertragung von Audio zu Text oder die Schlüsselwörtererkennung für die Suche nach Schlüsselwörtern.

Die Audioanalyse-Jobs werden im Audioanalyse-Modul der Applikation INSPIRATIONneo konfiguriert und verwaltet.

Transkription

Die Transkription basiert auf der Large-Vocabulary-Continuous-Speech-Recognition-Technologie (LVCSR).

Die Transkription wandelt Audio-Aufzeichnungen in Texte um, die dann zur Analyse zur Verfügung stehen. Um alle Wörter erkennen zu können, werden Wörterbücher hinterlegt, mit denen die Sprachdaten abgeglichen werden. Dadurch, dass jedes einzelne Wort erkannt und in Text umgewandelt wird, ist dieser Ansatz zunächst aufwendiger als die Schlüsselwörtererkennung. Dafür ist nach einer Transkription die gesamte Audio-Aufzeichnung als Text verfügbar, so dass jedes denkbare Wort über eine Volltextsuche gefunden werden kann.

Das Ergebnis (Text) wird über eine XML-Schnittstelle in die INSPIRATIONneo-Datenbank eingetragen.

Ein großer Vorteil bei der Suche nach Worten im Volltext ist, dass die Suchterme im Kontext angezeigt werden können. So können Missverständnisse, z. B. bei doppeldeutigen Begriffen, ausgeschlossen werden. Die Texte stehen für weitere Analysen zur Verfügung und können zu diesem Zweck auch an andere Systeme transferiert werden.

Transkribiert wird in Echtzeit (auf einem Core einer Standard-Server-CPU). Die Qualität der Transkription hängt von der Anzahl der Kanallizenzen ab.

Es gibt keine Obergrenze für die Audiolänge und jede Audiodatei muss eine Mindestlänge von 200 Millisekunden vorweisen, um verarbeitet werden zu können.

ASC empfiehlt Stereo-Gespräche für die Transkription zu nutzen.



Die Transkription von Mono-Gesprächen ist möglich, aber nicht empfehlenswert.

Da bei Mono-Gesprächen alle Gesprächsteilnehmer auf eine Spur zusammengelegt werden, werden alle Ergebnisse einem Teilnehmer zugeordnet. Eine Überlagerung durch gleichzeitiges Sprechen der Gesprächsteilnehmer kann die Sprachanalyse-Engine nicht eindeutig trennen, was zu verminderter Transkriptionsqualität führt.

Schlüsselwörtererkennung

Mit Hilfe der Schlüsselwörtererkennung können Sie Sessions nach bestimmten Thematiken filtern oder kategorisieren. Dazu stellen Sie alle Begriffe und Phrasen (Schlüsselwörter), die ein Thema umschreiben, in einer Analyseliste zusammen. Sessions werden dann automatisch nach den definierten Schlüsselwörtern durchsucht.

Dadurch dass dieser Ansatz sich auf das Erkennen einzelner Wörter und Phrasen begrenzt, können die Sessions schnell durchsucht werden. Da man die zu suchenden Begriffe im Voraus definiert, eignet sich dieser Ansatz vor allem zur Identifizierung bereits bekannter Thematiken, die sich öfter wiederholen.



Informationen zur Konfiguration der Audioanalysesoftware EML Transcription Server finden Sie in der Administrationsanleitung *Konfiguration Sprachanalyse-Software von EML*.



Informationen zur Erstellung von Audioanalyse-Jobs und deren Anwendung finden Sie in der Bedienungsanleitung *Bedienung Audioanalyse-Modul*.

3 Installation

Installieren Sie die Sprachanalyse-Software gemäß der folgenden Anleitung des Herstellers in diesem Kapitel.



Bitte beachten Sie, dass die Sprachanalyse-Software auf einem eigenen Server mit einer separaten PostgreSQL-Datenbank installiert werden muss.



Bitte beachten Sie, dass bei Neuinstallationen und für Updates von Sprachpaketen eine Decoder-Version $\geq 1.4.2$ benötigt wird.

Sehen Sie dazu auch

 EML Transcription Server Version Windows 1.4.pdf [► 7]



EML Transcription Server

Installation Instructions (Windows)

Version 1.4

October 2018

Document-History

Revisions of this document

Revision-number	Revision-date	Changes from previous revisions	Marked changes
1.0	2017-08-25	Initial version	N
1.1	2017-09-04	Major Update of Chapters 2 and 3	N
1.2	2018-02-09	Minor changes, Updated Workflow/Architecture pictures	N
1.3	2018-06-28	Update Post-Installation steps	N
1.4	2018-10-31	Minor changes	N



Contents

1.	Overview.....	5
1.1	Basic Architecture	5
1.2	Streaming Setup	6
1.3	Ports.....	6
1.4	Workflow	7
1.5	Best-Practice Setup	7
2.	Database & Transcription Server.....	8
2.1	System Requirements - mandatory	8
2.1.1	Operating System	8
2.1.2	Hardware	8
2.1.3	Firewall.....	8
2.1.4	Software Dependencies.....	8
2.2	Installation	8
2.2.1	Database: PostgreSQL.....	9
2.2.2	Transcription Server	9
2.3	Post-Installation Steps	9
2.3.1	Create Database.....	9
2.3.2	Transcription Server user	9
2.3.3	Configure Wildfly service	10
2.3.4	Configure Wildfly Port	10
2.3.5	Install Wildfly service	11
2.4	Verify Installation.....	11
2.5	Configuration.....	11
2.5.1	Update Configuration.....	11
2.6	Populate Model and Project databases	12
2.6.1	Deploy models via GUI	12
2.6.2	Create Project	13
2.7	Verify Configuration.....	14
3.	Decoder	15
3.1	System Requirements - mandatory	15
3.1.1	Operating System	15
3.1.2	Hardware	15
3.1.3	Firewall.....	15
3.1.4	Software Dependencies.....	15



EML Transcription Server – Installation Instructions

3.2	Installation	15
3.3	Configuration.....	16
3.4	Verify Installation & Configuration.....	16
4.	Streaming Service	17
4.1	Verify Installation.....	17
4.2	Configuration.....	17
4.3	Verify Configuration.....	17
5.	G2P	18
5.1	Verify Configuration.....	18
6.	Troubleshooting.....	19
6.1	EML Decoder Log	19
6.1.1	Log-Level	19
6.2	EML Transcription Server Log	19

1. Overview

The EML Transcription Server consists of the following components:


- *Decoder*: The decoder transcribes audio files from a queue server using a model.
- *Transcription Server*: The transcription server puts jobs into the queue the decoder listens to. It also provides a monitoring user interface for the queue server and manages the available models. Clients need to supply an audio URL from which the decoder can download the audio file and a second URL to which the decoder can send the results.

In order to be able to update a model independently of a specific client without the need to change the client, the transcription server keeps track of so called *projects*. A project is simply a mapping from a “project name” to a specific model. The client only provides the project name in the request to the transcription server, and the transcription server will translate it into a proper model name which can be used by the decoder.

- *Additional: Streaming Service*: The streaming server is used to establish a streaming transport of the audio and the result.

The streaming service introduces to notion of a language identifier (e.g. “en”) which is mapped in the streaming service to a project name of the transcription service, thus allowing changing the model or project independently of the clients (i.e. without needing to update the clients). Besides a streaming interface, the streaming service offers an easy to use HTTP interface to submit jobs (it allows to use a simple HTTP POST request to start transcription of an audio file).


1.1 Basic Architecture



The basic architecture consists of the Transcription Server, the Decoder and a Client application. The Client sends a job description document to the transcription server. The job is put into a queue, where it is picked up by a decoder. The decoder requests the audio from the client, transcribes it and sends the result to the client. In the above picture, each of the orange boxes represents a different host, although it is possible to all of the components on one machine (given that the system requirements are met).

There can also be run multiple decoders which connect to the same queue to scale vertically. Multiple decoders can be run on one or different machines


1.2 Streaming Setup



The client in this case holds a bi-directional connection to the streaming service, which in turn will post a corresponding job to the transcription server and will receive the results from the decoder. It can process the results and transmit only the requested information to the client, minimizing the amount of transferred data.

Since the streaming service is just an addition to the basic setup, both setups can be used in parallel.


1.3 Ports



The Transcription Server is starting the services on ports: 8080/TCP, 61616/TCP and 8161/TCP. The Transcription Decoder will listen to port 12345/TCP when management console is activated (active by default).

Note: All ports used in JEE Server, Queue and Decoder are configurable!

1.4 Workflow



An application that uses EML Speech Transcription Server sends the control-file to Transcription Server with an HTTP POST request. The control file is fetched by one of decoders which are subscribed to the queue. In the control file is a pointer to an URI where the audio data can be downloaded. The decoding is then done on a local copy of the audio data.

The control-file is enriched with the result of the speech-to-text processing and the resulting file is sent back to the application using a call-back URI which is provided in the control-file. After the successful processing and the transfer of the result the processing is acknowledged to the queue.

1.5 Best-Practice Setup

For large scale setups we recommend installing the EML Transcription Server and the Queuing Server on one host and out the decoders on separate hosts. For smaller setups, where only a few channels are needed the EML Transcription Server, the Queuing Server and the decoders may run on the same host.

2. Database & Transcription Server

The EML Transcription Server is the service responsible for the automatic transcription of audio. It is a highly scalable JEE Application running in a JEE application server (e.g. JBoss Wildfly). It is responsible for the automatic model deployment to the registered EML Transcription Decoders as well as the logging of the job status.

As part of the EML Transcription Server the EML Transcription Server Monitor is deployed. This is a browser based graphical management tool.

2.1 System Requirements - mandatory

Note: On Software Dependencies and Operating Systems we expect 64bit versions.

The Transcription Server comes with the following system requirements:

2.1.1 Operating System

- **Windows Server 2012R2**
No special requirements
- **Windows Server 2016**
No special requirements

2.1.2 Hardware

- *CPU*: No special requirements
- *RAM*: 16GB
- *Disk*: 10GB + 10 GB per language

2.1.3 Firewall

- *Mandatory open:*
 - 8080/TCP (*JEE Application server e.g. Wildfly*)
 - 61616/TCP (*ActiveMQ OpenWire protocol*)
 - 8161/TCP (*ActiveMQ admin and REST interface*)

2.1.4 Software Dependencies

- **Oracle Java 8**

The environment variable JAVA_HOME is required. You may need to add a new entry in environment variables.

- Name: JAVA_HOME
- Value: the directory where the Java software is located, for example C:\Progra~1\Java\jre1.8.0_181

2.2 Installation

The EML Transcription Server will install several components: Apache ActiveMQ, Wildfly and EML Transcription Server JEE Applications.

2.2.1 Database: PostgreSQL

We strongly recommend to use PostgreSQL 9.3, 9.4 or 9.5 (<https://www.postgresql.org/download/windows/>)

You can skip the database installation when there is already a proper PostgreSQL Version installed on your system.

Execute the installer and run through the wizard. Define postgres password (required also in a further configuration step). The other defaults are OK. You might want to change them, depending on your preferences. Skip the stackbuilder Wizard.

2.2.2 Transcription Server

To start installation issue double click:

EMLTranscriptionServer<version>.msi

There is no manual interaction required during installation. The EML Transcription Server is installed into

%ProgramFiles%\EML\TranscriptionServer

Other data like the model repository will be written into

%ProgramData%\EML\TranscriptionServer

ActiveMQ which is part of EMLTranscriptionServer.msi will be automatically installed as *Windows Service*. *Wildfly* will be installed as a Windows Service in a Post-Installation step.

2.3 Post-Installation Steps

2.3.1 Create Database

Start the PostgreSQL administration application “pgAdmin3” and double click on PostgreSQL 9.5.x (localhost:5432) and enter your password in the popup dialog. Right click on the node “Databases” and create a new database and enter as database name: sttdb

2.3.1.1 Fill Database



Activate the new database sttdb and click on the magnifying glass “SQL”

The .ddl files are located at: %ProgramFiles%\EML\TranscriptionServer\ddl

- Open “ddl_postgres_9.sql” and copy the content into the pgAdmin3 SQL Editor and execute the command (F5).
- Open “ddl_streaming_postgres_9.sql” and copy the content into the pgAdmin3 SQL Editor and execute the command (F5).

2.3.2 Transcription Server user

Note: Please activate in FileExplorer “show hidden files and directories” to make C:\ProgramData visible

The Installer is creating a Transcription Server user. This user will be used to access /Transcription-WebMonitor and /webSocket

The username and raw password is saved in a file

%ProgramData%\EML\TranscriptionServer\wildfly\transcriptionserver.users.raw.txt

You need to modify

%ProgramData%\EML\TranscriptionServer\streaming_config\configuration.properties
and replace the placeholder value "secret" in line "queue.pass" with the raw password from transcription-server.users.raw.txt

```
queue.host=http://localhost:8080
segmenter.minsil=60
queue.user=admin
queue.pass=secret
vmt.default_source=Android
service.port=8080
service.host=localhost
audio.dir=C:/ProgramData/EML/TranscriptionServer/tmp_audios
audio.dir.name.strategy=org.eml.stt.storage.names.PerKeyPerDateFile
NameStrategy
lang=de
```

2.3.3 Configure Wildfly service

Modify

%ProgramFiles%\EML\TranscriptionServer\wildfly\bin\service\service_config.bat
and replace "secret" in line 35: "set EMLDBPW=secret" with the database password defined in 2.2.1

```
set "EMLJDBC=jdbc:postgresql://localhost:5432/sttdb"
set "EMLDBUSER=postgres"
set "EMLDBPW=secret"
set "EMLLOGLVL=INFO"
```

2.3.4 Configure Wildfly Port

By default, the Wildfly Service will start listening on port 8080.

To check if port is already used by another process issue in CMD:

(EN) netstat -aon | findstr /R 8080 | findstr /i "listening"

(DE) netstat -aon | findstr /R 8080 | findstr /i "abhören"

When there is no output everything is fine and no other application is listening to that port. On the other side, if there is an output like this:

TCP	0.0.0.0:8080	0.0.0.0:0	ABHÖREN	3656
-----	--------------	-----------	---------	------

That means that there is already an application running on that port and you should change the wildfly port.

To change the port used by Wildfly modify:

%ProgramFiles%\EML\TranscriptionServer\wildfly\standalone\configuration\standalone.xml

```
<socket-binding name="http" port="${jboss.http.port:8080}"/>
```




EML Transcription Server – Installation Instructions

Note: If you change the port you need to replace in all the example URL's 8080 with the port you choose. Keep in mind to also change the port in further Configuration steps: 2.5.1 and 3.3

2.3.5 Install Wildfly service

Run

```
%ProgramFiles%\EML\TranscriptionServer\wildfly\bin\service\service_install.bat
```

and the Windows Service *Wildfly* will be installed.

Note: the startup takes up to 60 seconds

2.4 Verify Installation

You should check the Configuration. Wait at least 60 seconds after installing the Wildfly Service and then login into the Transcription Server Monitor (<http://x.x.x.x:8080/TranscriptionWebMonitor> by default) and go to "Config". If you experience "404 – Not found" please check the log file mentioned in 6.2

Note: The credentials to Transcription Server and other applications were saved during installation into

```
%ProgramData%\EML\TranscriptionServer\transcriptionserver.users.raw.txt
```

You can connect to the Active MQ admin interface (on <http://x.x.x.x:8161/> by default). Login credentials: (admin / admin) You should see at least one queue created eml-transcribe-stats with one listener. The queues are listed in "Manage ActiveMQ broker" -> "Queues"

2.5 Configuration

The installer will create an initial configuration with default values working well when all components (Transcription Server, Queue and Decoder) are running on same server [localhost]. When Decoder is running on a different server it's important to update your hostname configuration to an IP or name from which the server is reachable.

2.5.1 Update Configuration

The configuration is saved in the database and can be modified in "Config"-Tab in Transcription Server Monitor (on <http://x.x.x.x:8080/TranscriptionWebMonitor/> by default):

Key	Description	Default
hostname	The hostname or IP-address of the server the Transcription Server is running on and could be reached from the Transcription Decoders	localhost
port	The port on which the application server (Wildfly) is running	8080
repository.base	The directory on the server in which uploaded models will be stored.	%ProgramData%\EML\TranscriptionServer\modelRepository
sttweb.default-queue	The default queue to which jobs should be posted.	eml-transcribe



EML Transcription Server – Installation Instructions

<code>monitor.archiveFolder</code>	The directory on the server in which generated reports will be stored.	<i>%ProgramData%\EML\TranscriptionServer\reportArchive</i>
<code>sttweb.queue-server</code>	The queue server identifier to use to post jobs. This will be appropriately set when using the <code>add-queue-server.sh</code> script.	<i>default</i>
<code>sttweb.current-context</code>	The web context in which the sttweb component is running. This will be automatically set. Do not change this value.	<i>/eml-stt</i>
<code>monitor.current-context</code>	The web context in which the EML Transcription Server Monitor component is running. This will be automatically set. Do not change this value.	<i>/TranscriptionWebMonitor</i>
<code>sttweb.speaker-cache</code>	The local cache directory where dynamic lexicon files and speaker adaptations will be saved.	<i>%TMP%</i>

2.6 Populate Model and Project databases

You need to populate the model and project database with entries in order to post jobs.


2.6.1 Deploy models via GUI

To upload and create entries manually, use the Transcription Server Monitor (on <http://x.x.x.x:8080/TranscriptionWebMonitor/> by default):


1. Go to the “Files” panel and upload your models files. Make sure to select the right type in the drop down menu. Usually the filename is an indicator of the type like “AM-...”, “LM-....”
Alternatively, if the model files are already present at the repository location set up above, you can simply import them.
2. Go to “Models”. Select the correct tab (“Directory” for complete models, “Acoustic” for Acoustic Models and “Language” for Language Models). Click the “Add new Model” button and fill out the form properly.

Example (Separated): You’ve got three files like

- i. “AM-bcn06.hbn.b.zip”
- ii. “LM-BCN_DeDE_10_161108_142740--2”
- iii. “IMAGES-bcn06.hbn.b_BCN_DeDE_10_161108_142740--2_cfg_stream.txt--1705.zip”



Create “Accoustic Model” (AM) entry



Create “Language Model” (LM) entry

IMAGES.zip does not need to be defined in “Models”! Now you can proceed with 2.6.2

Note that all of these operations also can be executed using the REST interface.


2.6.2 Create Project

Open Transcription Server Monitor and go to “Projects” in top menu navigation. Click the “Add new project” button. Select a project name and afterwards select the created model entries. There is a switch button “Separated | Directory” to get a list of either complete models (directory) or separated models (acoustic, language and images).

In the separated view there are two additional parameters: AM config and LM config:

The AM config is usually also listed in the filename of the images archive (e.g. if the image file is named IMAGES-bcn06.hbn.b_BCN_DeDe_10_161108_142740--2_**cfg_stream.txt**--1705.zip the AM config that has to be referenced is **cfg_stream.txt**).

The LM config is usually named lm.cfg.

**Add new project dialog with separated model**

2.7 Verify Configuration

After you have created the project entry, you can submit your first job to the Transcription Server. This job should appear in the proper queue (see the EML Transcription Server Monitor). Since no decoder is running yet, of course it will not get dispatched.

In order to post a job, the easiest way is to use the EML command-line tool `queue-files.bat` which is located in the `%ProgramFiles%\EML\TranscriptionServer\tools` directory.

```
queue-files.bat -if y.y.y.y -host x.x.x.x -queue <queue> -project <project> -  
files <audio.wav>
```

Where `y.y.y.y` is the IP address of the computer on which the script runs and `x.x.x.x` is the host on which the EML Transcription Server runs. `<queue>` is usually “`eml-transcribe`” and `<project>` is the one created in 2.6.2

Since no decoder is yet running, the script will block indefinitely and you should abort it by pressing `Ctrl+C`.

If the job appears in the queue the installation is complete and working. Purge the queue in the EML Transcription Server Monitor before proceeding to set up the decoders.

3. Decoder

3.1 System Requirements - mandatory

The Decoder internally consists of several decoding threads, each acting as a full decoder instance. Since each thread loads a model into memory, the requirements depend on how many threads are configured to run.

Note: On Software Dependencies and Operating Systems we expect 64bit versions.

3.1.1 Operating System

- **Windows Server 2012R2**
No special requirements
- **Windows Server 2016**
No special requirements

3.1.2 Hardware

- **CPU:** One physical core per decoding thread
- **For Transcription:**
 - **RAM:** Depending on model, typically 4-8 GB per decoding thread
 - **Disk:** 20GB + 10 GB per language
- **For KWS**
 - **RAM:** 512MB per decoding thread
 - **Disk:** 5GB per language

3.1.3 Firewall

- *12345/TCP (default management port used by EML Transcription Server Monitor)*

3.1.4 Software Dependencies

- Oracle Java 8
- Transcription Server installed and configured

3.2 Installation

To start installation issue double click:

EMLTranscriptionDecoder<version>.msi

There is no interaction required during installation. The EML Transcription Decoder is installed into

%ProgramFiles%\EML\emDecoder

Other data like log files will be written into

%ProgramData%\EML\emlDecoder

EMLTranscriptionDecoder will be automatically installed as *Windows Service*.

3.3 Configuration

To configure the decoder, modify “decoder.properties” and make the changes required for your environment. Having a proper configuration is crucial. The default configuration assumes the EML Transcription Server has been installed on the same host as the decoder. If this is not the case, change the “defaultServer” parameter accordingly. If the default port of the Transcription Server was changed in a previous installation step you need change the “defaultServerPort”. The “defaultQueue” parameter sets the name of queue to which to connect. The queue will be created automatically if it is not existing in the queue server.

The “numInstances” parameter controls the number of decoding threads. The “modelRepositoryPath” parameter denotes the directory where the decoder will unpack the model files downloaded from the transcription server. Make sure the location exists and is writeable by the user the decoder is running as. Uncomment the “managementConsole” parameters to enable a REST service to query the state of the decoders and visualization in the EML Transcription Server Monitor.

To configure the logging system, modify “log4j.properties”. The default settings are running on a minimum log on INFO level. Have a look at the log4j project on what this configuration file may contain. If you experience any issues on decoding, you can increase the log level to DEBUG.

Note: Changes on “decoder.properties” or “log4j.properties” requires to restart the EMLTranscriptionDecoder Windows Service.

3.4 Verify Installation & Configuration

You can have a look at the log file

```
%ProgramData%\EML\emlDecoder\log\emlDecoder.log
```

For each instance you should see a line saying “Starting to process messages.” You can use the EML Transcription Server Monitor on the EML Transcription Server to check whether the Decoder is connected to the right queue. You should see for each decoding thread 1 consumer on the queue. This means the queue configuration on both ends is correct and working.

To check whether decoding is working, make sure that you have a project, which references to a model for which you have uploaded the model to the transcription server. If this is the case, submit a job for that project to the queue. You should see the job appearing in EML Transcription Server Monitor. The job will disappear from the queue *after* the job has been completely processed by the decoder. In the decoder’s log file, you should see several things happen: First of all, the message that a job was received, next details of the job will be printed (e.g. which model to use). After that, it is checked whether the model already exists in the model repository path, and if not it will be downloaded and extracted. If that is done the following workflow will take place:

1. Initialization of Engines: For each decoding there might be multiple engine processes that need to be spawned and initialized with the model. For future decodings with the same model, the already initialized engines will be re-used. So this is a one-time setup time.
2. Download of the audio: The audio is downloaded from the given URL.
3. Decoding
4. Sending the result(s): The results are posted to the given call back URL.

Please note, that the first few decodings will usually take longer (due to the initialization steps) then subsequent ones. Since the initialization time is a one-time setup, it is typically not included in real-time factor calculations.

4. Streaming Service

As the streaming service is part of the Transcription Server installation package no further installation is required. You can skip this part if it's not required to use streaming API.

4.1 Verify Installation

Point your browser to `http://x.x.x.x:8080/webSocket` and login with the Transcription Server credentials.

4.2 Configuration

After installation please check the Streaming Service configuration located at `%ProgramData%\EML\TranscriptionServer\streaming_config\configuration.properties`

After finishing on the configuration, create a new authentication key in menu “keys”. After that, create a new language identifier. See the manual for the streaming service if you run into problems with that. Make sure you have setup the transcription server configuration items correctly before creating a language entry. Also make sure you have created at least one project in the transcription server. When creating a language id, you have to assign a project to it. Therefore, the streaming service requests a list of projects from the transcription server.

4.3 Verify Configuration

To verify that the configuration is working, use the REST interface with a WAV audio file with the proper sampling rate:

```
curl -H "Content-Type: application/octet-stream" --data-binary @<file>
"http://x.x.x.x:port/webSocket/rest/batch/<language-identifier>/<authentication-key>/?encoding=wav"
```

The result of this command should be the following actions:

- In the Transcription Server log file, you see a new request (look for RESTART messages)
- When the file has been transmitted, you will see a “Posting job to ...” message. If there is no exception, the message has been posted to the transcription server. The processing on the transcription server and on the decoder eventually starts (check those logs)
- In the Transcription Server log you will see more messages when the results arrive from the decoder.
- It is quickly processed and should be printed as result of the curl call on your command line.

After this step was successful, use our command line tools, to stream the audio file using the Websocket connection. The processing steps detailed above should be the same.


5. G2P

As the grapheme-to-phoneme (G2P) is part of the Transcription Server installation package no further installation is required. This is an optional tool to create pronunciations (e.g. used in KWS).

5.1 Verify Configuration

Point your browser to http://x.x.x.x:8080/g2p/phonetize/DeDE_2/Hallo/5 and wait a few seconds until you see the pronunciations. The first request may take 15-20 seconds until the engine is initialized.

The g2p output should look like



```
- <phonetizationResult>
  - <phonetizedWords wordClass="">
    <word>Hallo</word>
    - <phonetizations>
      <phonetization soundslike="Hallo" language="DeDE_2">h a l o:</phonetization>
      <phonetization soundslike="Hallo" language="DeDE_2">h a l O</phonetization>
      <phonetization soundslike="Hallo" language="DeDE_2">h E l o:</phonetization>
    </phonetizations>
  </phonetizedWords>
</phonetizationResult>
```




6. Troubleshooting

In case you have any problems you cannot solve yourself and you want to contact the support make sure to include the relevant parts of the EML Decoder Log and the EML Transcription Server Log.

6.1 EML Decoder Log

By default, the log file is located at

`%ProgramData%\EML\emlDecoder\log\`

6.1.1 Log-Level

By default, the Log-Level is set to INFO which only writes minimal information to the logs. If there is an issue with the Transcription Decoders please set the Log-Level to DEBUG, run your test again and send us the logs produced with DEBUG.

Edit `%ProgramFiles%\EML\emDecoder\log4j.properties`

Replace

```
log4j.logger.de.emld=INFO
log4j.logger.org.eml=INFO
```

by

```
log4j.logger.de.emld=DEBUG
log4j.logger.org.eml=DEBUG
```

To apply the changes, install the Decoder service again by execute `service_uninst` and `sevice_inst`.

6.2 EML Transcription Server Log

By default, the log file is located at

`%ProgramFiles%\EML\TranscriptionServer\wildfly\standalone\log\`